2015 Hollister Urban Area Urban Water Management Plan

July 2016







Sunnyslope

PUBLIC DRAFT July 2016

HOLLISTER2015 URBAN WATERURBANMANAGEMENT PLAN

Date Plan Submitted to the Department of Water Resources:

San Benito County Water District Sunnyslope County Water District City of Hollister

Todd Groundwater

CONTACT SHEET

SAN BENITO COUNTY WATER DISTRICT

Name of Primary Contact Person: Jeff Cattaneo, District Manager

Phone: (831) 637-8218

Email address: jcattaneo@sbcwd.com

The water supplier is a: Water district and water wholesaler

Utility services provided by the water supplier include: Water service

Is this agency a Bureau of Reclamation Contractor? Yes

Is this agency a State Water Project Contractor? No

SUNNYSLOPE COUNTY WATER DISTRICT

Name of Primary Contact Person: Don Ridenhour, General Manager

Phone: (831) 637-4670

Email address: don@sscwd.org

The water supplier is a: Water district and water retailer

Utility services provided by the water supplier include: Water and sewer service

Is this agency a Bureau of Reclamation Contractor? No

Is this agency a State Water Project Contractor? No

CITY OF HOLLISTER

Name of Primary Contact Person: Henry Gonzales

Phone: (831) 636-4377

Email address: Henry.Gonzales@hollister.ca.gov

The water supplier is a: City water department and water retailer

Utility services provided by the water supplier include: Water and sewer service

Is this agency a Bureau of Reclamation Contractor? No

Is this agency a State Water Project Contractor? No

TABLE OF CONTENTS

Executive Summary	ES-1
1. Introduction	1-1
2. Plan Preparation	
2.1 Plan Preparation And Adoption	2-1
2.2 Agency Coordination And Public Participation	2-2
2.3 Acknowledgements	2-2
3. System Description	3-1
3.1 Location	3-1
3.2 Service Area	3-1
3.3 Climate	3-1
3.4 Population	3-2
4. System Water Use	4-1
4.1 Water Uses By Sector	4-1
4.2 Projected Water Demand	4-2
4.3 Water Savings	4-3
4.4 Distribution System Water Losses	4-4
4.5 Water Use For Lower Income Households	4-5
4.6 Climate Change	4-6
5. Baselines And Targets	5-1
5.1 Updating Calculations From 2010 UWMP	5-1
5.2 Baseline Period	5-1
5.3 Service Area Population	5-2
5.4 Gross Water Use	
5.5 Baseline Daily Per Capita Water Use (Gpcd)	
5.6 2015 And 2020 Targets	5-3
5.7 2015 Compliance Daily Per Capita Water Use (Gpcd)	5-3
6. System Supplies	6-1
6.1 Imported Water	6-1
6.2 Groundwater	6-3
6.3 Surface Water	6-11
6.4 Storm Water	6-11
6.5 Wastewater And Recycled Water Opportunities	6-11
6.6 Desalination Water Opportunities	
6.7 Exchanges Or Transfers	6-16
6.8 Future Water Projects	
6.9 Summary Of Existing And Planned Sources Of Water	6-17
6.10 Climate Change Impacts To Supply	6-18
7. Water Supply Reliability Assessment	7-1
7.1 Constraints On Water Sources	7-1
7.2 Reliability By Type Of Year	7-4
7.3 Supply And Demand Assessment	
7.4 Regional Supply Reliability	
8. Water Shortage Contingency Planning	
8.1 Stages Of Action	
8.2 Prohibitions On End Users	8-2

8.3 Penalties, Charges, Other Enforcement Of Prohibitions	8-4
8.4 Consumption Reduction Methods By Agencies	8-4
8.5 Determining Reductions	8-5
8.6 Impact On Revenues And Expenses	8-5
8.7 SBCWD Ordinance	8-5
8.8 Catastrophic Supply Interruption	8-6
8.9 Minimum Supply Next Three Years	
9. Demand Management Measures	9-1
9.1 Wholesale Agency Programs	9-1
9.2 Demand Management Measures For HUA	9-1
9.3 Implementation Over The Past Five Years	
9.4 Planned Implementation To Achieve Water Use Targets (Retail Agencies Only)	9-14
9.5 Members Of The California Urban Water Conservation Council	9-15
10. Completed Uwmp Checklist	10-1
11. References	

LIST OF TABLES (LOCATED AT THE END OF EACH SECTION)

Table 2-1 Retail Only: Public Water Systems Table 2-2: Plan Identification Table 2-3: Agency Identification Table 2-4 Retail: Water Supplier Information Exchange Table 2-4 Wholesale: Water Supplier Information Exchange Table 3-1a Retail: Population - Current and Projected Table 3-1b Retail: Population - Current and Projected Table 3-1 Wholesale: Population - Current and Projected Table 4-1a Retail: Demands for Potable and Raw Water – Actual Table 4-1b Retail: Demands for Potable and Raw Water - Actual Table 4-1 Wholesale: Demands for Potable and Raw Water - Actual Table 4-2a Retail: Demands for Potable and Raw Water – Projected Table 4-2b Retail: Demands for Potable and Raw Water - Projected Table 4-2 Wholesale: Demands for Potable and Raw Water - Projected Table 4-3 Retail: Total Water Demands Table 4-3 Wholesale: Total Water Demands Table 4-4a Retail: 12 Month Water Loss Audit Reporting Table 4-4b Retail: 12 Month Water Loss Audit Reporting Table 4-4 Wholesale: 12 Month Water Loss Audit Reporting Table 4-5 Retail Only: Inclusion in Water Use Projections Table 5-1 Baselines and Targets Summary Table 5-2: 2015 Compliance Table 6-1a Retail: Groundwater Volume Pumped Table 6-1b Retail: Groundwater Volume Pumped Table 6-1 Wholesale: Groundwater Volume Pumped Table 6-2 Retail: Wastewater Collected Within Service Area in 2015 Table 6-3 Retail: Wastewater Treatment and Discharge within Service Area in 2015 Table 6-3 Wholesale: Wastewater Treatment and Discharge within Service Area in 2015 Table 6-4a Retail: Current and Projected Recycled Water Direct Beneficial Uses within Service Area Table 6-4 Wholesale: Current and Projected Retailers Provided Recycled Water within Service Area Table 6-5 Retail: 2010 UWMP Recycled Water Use Projection Compared to 2015 Actual Table 6-5 Wholesale: 2010 UWMP Recycled Water Use Projection Compared to 2015 Actual Table 6-6 Retail: Methods to Expand Future Recycled Water Use Table 6-7 Retail: Expected Future Water Supply Projects or Programs Table 6-7 Wholesale: Expected Future Water Supply Projects or Programs Table 6-8a Retail: Water Supplies — Actual Table 6-8b Retail: Water Supplies — Actual Table 6-8 Wholesale: Water Supplies — Actual Table 6-9 Retail: Water Supplies — Projected Table 6-9 Wholesale: Water Supplies - Projected Table 7-1a Retail: Basis of Water Year Data Table 7-1b Retail: Basis of Water Year Data Table 7-1c Retail: Basis of Water Year Data Table 7-1 Wholesale: Basis of Water Year Data Table 7-2 Retail: Normal Year Supply and Demand Comparison Table 7-2 Wholesale: Normal Year Supply and Demand Comparison

- Table 7-3 Retail: Single Dry Year Supply and Demand Comparison
- Table 7-3 Wholesale: Single Dry Year Supply and Demand Comparison
- Table 7-4 Retail: Multiple Dry Years Supply and Demand Comparison
- Table 7-4 Wholesale: Multiple Dry Years Supply and Demand Comparison
- Table 8-1 Retail: Stages of Water Shortage Contingency Plan
- Table 8-1 Wholesale: Stages of Water Storage Contingency Plan
- Table 8-2 Retail Only: Restrictions and Prohibitions on End Uses
- Table 8-3 Retail Only: Stages of Water Shortage Contingency Plan Consumption Reduction Methods
- Table 8-4 Retail: Minimum Supply Next Three Years
- Table 8-4 Wholesale: Minimum Supply Next Three Years
- Table 10-1 Retail: Notification to Cities and Counties
- Table 10-1 Wholesale: Notification to Cities and Counties (select one)

LIST OF FIGURES (LOCATED AT THE END OF EACH SECTION)

- Figure 1-1 Location Map Hollister Urban Area
- Figure 3-1 Location Map Service Areas
- Figure 3-2 Annual Precipitation Hollister Urban Area
- Figure 4-1 Historical and Current Demand by Customer Type
- Figure 6-1 San Benito Portion of the Gilroy-Hollister Groundwater Basin
- Figure 6-2 Historical and Current Supply by Source Type
- Figure 6-3 District Defined Groundwater Subbasins
- Figure 6-4 Hydrographs of Key Wells
- Figure 6-5 Generalized Areas of Total Dissolved Solids Concentrations
- Figure 6-6 Location of Groundwater Wells and Wastewater Treatment Plants

LIST OF APPENDICES

- Appendix A Notice to Adopt
- Appendix B DWR Population Tool
- Appendix C Future Water Demands
- Appendix D Water Loss Audits
- Appendix E Climate Change Vulnerability Assessment
- Appendix F SB 20x2020 Compliance
- Appendix G Water Shortage Contingency Plan
- Appendix H Water Shortage Emergency Response
- Appendix I SBCWD Ordinance No. 2015-04
- Appendix J Water Conservation Plan
- Appendix K Retailer Water Rates
- Appendix L Public Outreach

EXECUTIVE SUMMARY

PURPOSE AND SCOPE

The 2015 Hollister Urban Area (HUA) Urban Water Management Plan (UWMP) has been prepared as a collaborative effort between the San Benito County Water District (District), Sunnyslope County Water District (Sunnyslope or SSCWD), and the City of Hollister (Hollister). The plan has been prepared in accordance with the Urban Water Management Planning Act and guidelines prepared by the Department of Water Resources (DWR). The 2015 HUA UWMP is intended to help guide the area's future water management efforts.

This Plan builds on and updates the 2010 UWMP, accounting for changes in the California Water Code and local planning and water management efforts. Specifically, Senate Bill 7 (Statewide Water Conservation), water loss data, and new water conservation programs have been included in this 2015 UWMP.

The HUA agencies have provided for agency coordination and community participation in their urban water management planning efforts. Much of the coordination and community participation regarding water conservation within the HUA is undertaken by the agency members of the Water Resources Association (WRA) of San Benito County. The WRA serves water customers of Hollister, Sunnyslope, the District, and the City of San Juan Bautista. The WRA has played an integral role in the preparation of this UWMP.

This UWMP presents the following elements relating to water supply and demand in the HUA:

- A description of the HUA service area, which is a regional alliance of the District, Sunnyslope, and Hollister.
- Past and current water demand as reported by the agencies in the HUA.
- Water Loss Audit consistent with AWWA methodology.
- Baseline daily per capita water demand, as required by Senate Bill 7.
- Projected water demand based on estimated population and per capita daily demand reductions as required by Senate Bill 7.
- A water use reduction plan.
- A summary of sources of water supply and plans for future water supply facilities.
- Discussion of water supply reliability and comparison of supply and demand, including the effects of drought and emergencies on water supply availability and the contingency plans in place to manage shortages.
- Details of the demand management measures employed within the HUA.

FINDINGS

The HUA is an approximately 20 square mile area comprising all of the incorporated, and some unincorporated county lands, surrounding the City of Hollister. This is the same area that was used in the 2010 UWMP and in the Hollister Urban Area Water and Wastewater Master Plan (Master Plan). There are two municipal water purveyors within the HUA: the City of Hollister and Sunnyslope County Water District. These water purveyors provide water supply to their individual service areas from sources described in Section 6 of this report. The District has the responsibility and authority to manage groundwater in San Benito County, which includes managing groundwater and surface water supplies. In addition, the District holds the contract for water through the Central Valley Project (CVP) and is the imported water wholesaler from the CVP to Zone 6, which includes the HUA.

Table ES-1 Population — Current and Projected										
2015 2020 2025 2030 2035										
Total HUA Population	41,922	49,422	57,871	68,152	80,659					
Potable Water Demand (acre-feet per year, AFY)	4,880	6,820	7,740	8,840	10,170					
Potable Water Supply - Normal Water Year (AFY)	4,880	6,820	7,740	8,840	10,170					
Potable Water Supply - Single Dry Water Year (AFY)	4,880	5,549	6,285	6,717	7,716					

POPULATION

The annual estimates for the population of the HUA (for which water is supplied by Sunnyslope and Hollister) were updated through 2015. These historical population estimates are based on data from the online DWR population tool.

Population for the HUA was also estimated through 2035 in five-year intervals. Future population was estimated as part of the Master Plan through examination of general development plans for the City of Hollister and San Benito County. These population growth estimates were based on the Master Plan with some adjustments, as indicated in Section 4.2.

BASELINE AND FUTURE DEMAND

Historical population was combined with measured water use to calculate baseline per capita daily demand for the HUA, in accordance with DWR guidelines and Senate Bill 7. The baseline period selected for the HUA is 1996 through 2005. These calculations were performed for HUA as a region; the per capita daily demand over the baseline period was 157 gpcd for the entire HUA regional alliance. The actual 2015 per capita demand for the region was 105 gcpd, successfully surpassing the 2015 target and 2020 target of 142 gcpd and 126 gcpd, respectively. Consistent with Senate Bill 7 and DWR guidelines, the target daily per capita water use value that the HUA will need to achieve by 2020 is 126 gpcd. Detailed discussions of the baseline and target water demands are presented in Section 5.

Future water demands have been calculated based on the target water use values and the population projections summarized above and described in detail in the relevant sections. The resulting annual water demands are summarized in **Table ES-1**.

WATER SUPPLY

The HUA relies on both local groundwater and imported water from the CVP for municipal water supply. The District manages all CVP imports for both agricultural and municipal and industrial (M&I) water deliveries. The District also manages the groundwater resources of the County, particularly the highly developed basins in the northern County, where the District activities include managed aquifer recharge, monitoring water levels and water quality, and annual reporting. The basins in the northern County are subject to the 2014 Sustainable Groundwater Management Act, which requires development of Groundwater Sustainability Plans by 2022.

Since the initiation of CVP importation and the construction and recent expansion of the Lessalt Water Treatment Plant, the use of groundwater for M&I supply has declined. However, groundwater remains a major source of supply, particularly in drought. In the past five years (2011 through 2015) groundwater has accounted for approximately 73 percent of the total water supplied by Hollister and Sunnyslope. The District's management has resulted in a reliable groundwater resource but levels have declined locally due to pumping and prolonged drought. However, due to groundwater quality concerns groundwater use is expected to decrease.

Blending groundwater with CVP imported water will help the HUA deal with various water quality issues. The quality of groundwater has been described as highly mineralized and of marginal quality for drinking and agricultural purposes. Because of this less-than-desirable water quality, groundwater may be blended with CVP supply; the Master Plan may recommend that groundwater be less than a third of supply. This goal is to achieve better water quality for supply and wastewater but may be temporarily relaxed during drought conditions. In addition, concerns about the concentration of Chromium VI have restricted groundwater pumping to no more than 50 percent in the City of Hollister wells; this is a regulatory

agreement and cannot be relaxed. The blending requirement may be adjusted in the future if the concentration of Chromium VI in groundwater increases.

The District's contract for municipal and industrial CVP deliveries with the United Stated Bureau of Reclamation (USBR) exceeds the current treatment capacity within the HUA. Hollister and Sunnyslope have increased the operational capacity of the Lessalt water treatment plant and are in the process of constructing a second water treatment facility to treat CVP imports for delivery to areas of the HUA not currently served by Lessalt. Eventually, these two facilities will have a combined capacity capable of treating the entire volume of the municipal and industrial CVP contract.

WATER SUPPLY RELIABLITY

Many factors could result in inconsistency of supply and shortages, including legal, environmental, water quality, climatic, or a combination of these. Hollister, Sunnyslope, and the District are preparing for these threats to water supply through their portfolio of supplies, improvement of facilities (e.g., treatment plant expansion and groundwater banking), and demand management. Section 7 presents a detailed discussion of the factors affecting water supply, the steps taken by the HUA agencies to address these factors, and a comparison of supply and demand during water shortages caused by drought.


WATER CONSERVATION

The HUA agencies have a new Water Shortage Contingency Plan (WSCP), which is described in Section 8. In addition to shortage-related prohibitions, the agencies have many ongoing programs to encourage water conservation. These programs, discussed in depth in Section 9, have been successful in reducing water demand by more than 25 percent to meet the state mandated water use reduction. To meet the future water use per capita demand targets, the HUA and WRA, through their water conservation coordinator, plan to focus their efforts on several demand management measures (DMMs) including public outreach, rebates, and turf removal programs. These specific DMMs are targeted as opportunities for maximum water savings.

1. INTRODUCTION

This Urban Water Management Plan (UWMP or Plan) has been prepared for the Hollister Urban Area (HUA) to help guide the area's water management efforts to the year 2020 and beyond. The HUA covers all of the City of Hollister and some of unincorporated areas beyond the city limits. The Hollister Urban Area UWMP is a collaborative effort between the City of Hollister (Hollister), Sunnyslope County Water District (Sunnyslope), and San Benito County Water District (District). The Plan has been prepared in accordance with the Urban Water Management Planning Act (Division 6 Part 2.6 of the Water Code §§10610 – 10656). The location of the HUA is shown in **Figure 1-1**.

This Plan builds on and updates the 2010 UWMP, accounting for changes in the California Water Code and local planning and water management efforts. Major changes include a more robust water contingency plan, expanded discussion of water loss, and tables uploaded.



2. PLAN PREPARATION

2.1 PLAN PREPARATION AND ADOPTION

This Plan documents Hollister's and Sunnyslope's sources of water supply, defines water demands, presents a water shortage contingency plan, describes implementation of water demand management measures, and projects water supply and demand to the year 2035. The plan also describes ongoing work by the District to ensure and expand water supply in the area. The two water systems and their connections and 2015 water supply are documented in **Table 2-1**.

As indicated in **Table 2-2**, the HUA represents a regional alliance, as defined by Water Code sections 10608.20(a)(1) and 10608.28. Hollister and Sunnyslope choose to plan, comply, and report on a regional basis. Where possible, information for each entity is displayed individually in addition to the regional totals for the entire HUA.

The HUA regional alliance is made up of both retailers (Hollister and Sunnyslope) and a wholesaler (the District), which is indicated in **Table 2-3** as required. Where applicable, the requirements for both retailers and wholesalers are addressed. Because the three agencies work together in preparation of future water demands and supply, **Tables 2-4 R** and **2-4 W** have been updated to reflect that they are aware of each other's planning process. (Note that R indicates Retailer and W indicates Wholesaler.)

Throughout the 2015 UWMP, units are in acre-feet and data are presented in calendar years, unless otherwise stated (**Table 2-3**). Water volumes and other data are shown to the nearest acre-foot (AF). These values are accurate to one to three significant digits, depending on the measurement. Values in the text may show more significant digits than are warranted to maintain as much precision as possible during subsequent calculations: results of calculations have been rounded to the appropriate number of significant digits.

In accordance with section 10642 of the Water Code and section 6066 of the Government Code, each agency held a public hearing prior to adoption of the Plan. A public notice was posted before the public hearing and included in **Appendix A**. The Final Plan will be adopted by Hollister on August 1, 2016, Sunnyslope on August 16, 2016, and the District on August 31, 2016.

The resolutions to adopt the Plan are included in **Appendix A**. The adopted Plan has been filed with the Office of Conservation in the Department of Water Resources and California State Library, as required by law. California regulations require Urban Water Management Plans to be updated at least once every five years in years ending in five and zero. However, DWR extended the deadline for the 2015 UWMP to July 1, 2016.

2.2 AGENCY COORDINATION AND PUBLIC PARTICIPATION

The HUA agencies have provided for agency coordination and community participation in their urban water management planning efforts. A Draft Plan was made available to the public in July 2016 for comment with public presentations to Hollister on August 1, 2016, Sunnyslope on August 16, 2016, and the District on August 31, 2016.

The Water Resources Association of San Benito County (WRA) is an ongoing means for agency coordination and public participation, focused on water conservation. The WRA serves water customers of the following agencies: City of Hollister, City of San Juan Bautista, Sunnyslope County Water District and San Benito County Water District. The WRA coordinates and conducts water conservation programs for its participating member agencies and maintains an active website, <u>www.wrasbc.org</u>.

The Draft Plan was sent to local organizations with a request to provide comments, including San Benito County and the City of San Juan Bautista. Final Plan copies are available at Hollister City Hall and the City Library. An electronic version is available on the websites of all three agencies (Hollister, Sunnyslope, and the District).

2.3 ACKNOWLEDGEMENTS

This Plan was prepared by Iris Priestaf, Maureen Reilly, and Chad Taylor of Todd Groundwater. We appreciate the considerable assistance provided by District, Hollister, and Sunnyslope staff, most notably Jeff Cattaneo and Shawn Novack. This Plan was prepared using the checklists and worksheets provided by the California Department of Water Resources (DWR) from their website,

http://www.water.ca.gov/urbanwatermanagement/uwmp2015.cfm

and their *Guidebook to Assist Urban Water Suppliers to Prepare a 2015 Urban Water Management Plan* (DWR 2016d).

Table 2-1 Retail Only: Public Water Systems									
Public Water System Number	Public Water System Name	Number of Municipal Connections 2015	Volume of Water Supplied 2015						
3510001	City of Hollister	City of Hollister 6,324							
3510003	Sunnyslope CWD	5,497	1,941						
TOTAL 11,821 5,041									
NOTES: SSCWD data is from PWSS 2015. COH connections from PWSS 2015, water supplied from 2015 PWSS with volume of recycled water added to the total									

Table 2-2: Plan Identification (Select One)								
	Individual	Individual UWMP						
7	J	Regional UWMP (RUWMP) (checking this triggers the next line to appear)						
	Select One:							
	\checkmark	RUWMP includes a Regional Alliance						
	RUWMP does not include a Regional Alliance							
NOTES:	•							

Table 2-3: Agency Identification								
Type of Ag	ency (select one or both)							
\checkmark	☑ Agency is a wholesaler							
\checkmark	☑ Agency is a retailer							
Fiscal or Ca	Fiscal or Calendar Year (select one)							
\checkmark	UWMP Tables Are in Calendar Years							
	UWMP Tables Are in Fiscal Years							
If Using F	iscal Years Provide Month and Day that the Fiscal Year Begins (dd/mm)							
	dd/mm							
Units of M	Units of Measure Used in UWMP (select from Drop down)							
Unit AF								
NOTES:								

Table 2-4 Retail: Water Supplier Information Exchange
The retail supplier has informed the following wholesale supplier(s) of projected water use in accordance with CWC 10631.
Wholesale Water Supplier Name (Add additional rows as needed)
San Benito Water District
NOTES:

Table 2-	4 Wholesale: Water Supplier Information Exchange (select one)
	Supplier has informed more than 10 other water suppliers of water supplies available in accordance with CWC 10631. Completion of the table below is optional. If not completed include a list of the water suppliers that were informed.
	Provide page number for location of the list.
V	Supplier has informed 10 or fewer other water suppliers of water supplies available in accordance with CWC 10631. Complete the table below.
Water Su	upplier Name (Add additional rows as needed)
	City of Hollister
	Sunnyslope County Water District
NOTES:	

3. SYSTEM DESCRIPTION

3.1 LOCATION

The HUA is located about 90 miles south of San Francisco in the northern portion of San Benito County, California. The HUA is in a broad valley between the Gabilan Range on the west and the Diablo Range on the east. As shown in Figure 1-1, the San Benito River runs through the southwestern portion of the HUA and Santa Ana Creek flows through the eastern portion of the HUA. The Arroyo de Las Viboras and Arroyo Dos Picachos flow to the northeast of the HUA. The City of Hollister was incorporated in 1872 and is the largest community in San Benito County. Other communities near the HUA include San Juan Bautista and Tres Pinos, which are also in San Benito County, and Gilroy in Santa Clara County. The HUA overlies a portion of the Gilroy-Hollister groundwater basin, designated as DWR Basin No. 3-3.

3.2 SERVICE AREA

The HUA is an approximately 20 square mile area comprising all of the incorporated, and some unincorporated county lands, surrounding the City of Hollister (**Figure 1-1**). This area has been used in the previous 2010 UWMP (Todd 2011) and the Water and Wastewater Master Plan (HDR 2008a).

There are two municipal water purveyors within the HUA: the City of Hollister and Sunnyslope County Water District. These water purveyors provide water supply to their individual service areas from sources described in Section 4 of this report. The year 2000 service areas for Hollister and Sunnyslope are shown on **Figure 3-1**.

The District was formed by a special act of the State with responsibility and authority to manage groundwater in San Benito County. As part of its management activities, the District manages recharge to the basin, explores expanded groundwater banking, monitors water levels and water quality, and reports annually on the basin. In addition, the District is the imported water wholesaler from the Central Valley Project (CVP) to Zone 6, the northern portion of the County. HUA is located completely within Zone 6.

3.3 CLIMATE

San Benito County has a moderate California coastal climate, with a hot and dry summer season typically lasting from May through October. Average annual rainfall ranges from 7 inches in the drier eastern portion of the County to 27 inches per year in high elevations to the south (PRISM, 2010). The City of Hollister, some 30 miles inland from the coast and separated from it by the Gabilan Range, receives an annual average rainfall of almost 13 inches. Snowfalls in the mountains are infrequent and relatively light. A comparatively long growing season of 265 days or more per year prevails, and year-round cropping is practiced to some extent. The area has a high percentage of sunny days, particularly in summer. Most of the rainfall occurs in the late fall, winter, and early spring, generally between November and April. Therefore, significant irrigation is required during summer months (HDR 2008a).

Figure 3-2 is a graph of annual rainfall in Hollister from 1975 to 2015. While rainfall data have been collected monthly since 1875, precipitation and other weather data have been collected since June 1994 from a California Irrigation Management Information System (CIMIS) station located by the San Benito County Water District office in Hollister (Station #126). As shown, annual precipitation is subject to wide annual variations.

Evapotranspiration (ET) is the loss of water to the atmosphere by evaporation from soil and plant surfaces and transpiration from plants. It is an indicator of how much water is needed by plants (e.g., crops and landscaping) for healthy growth and productivity. ET from a standardized well-watered grass surface is the common reference, denoted as ETo. The least ET occurs in the cool wet winter months and greatest ET occurs during the hot dry summer months. This results in peak monthly water demands in summer that are three times the comparable winter demand. Average annual ETo in the HUA is 49 inches, peaking at 6.2 to 6.8 inches per month in June, July, and August.

Average monthly temperatures in the HUA range from approximately 48 degrees Fahrenheit in January and December to near 65 degrees in July and August. In these two months, daily maximum temperatures typically reach as high as 86 degrees.

3.4 POPULATION

The HUA is the urban center of a highly productive agricultural area that has been in continuous production for over one hundred years. The primary industry of the HUA is agriculture and agriculture related businesses, although in recent years there has been an increase in the number of residents who commute to other areas for work. The area is characterized primarily by single family residences, with less than sixteen percent of the population in multifamily dwellings.

Tables 3-1 Hollister Retail and 3-1 Sunnyslope Retail show the population for 2015 through 2035 in five year increments for Hollister and Sunnyslope, respectively. The current population is based on the information provided by the DWR online population tool. Additional information on the calculation of the current population is included in **Appendix B**. Population is anticipated to increase in the coming years, as planned developments are constructed. The 2020 through 2035 populations for the City and Sunnyslope are based on the projected connections reported by the retailer, and the average household size. Based on the DWR online tool, the household size for Hollister is 3.39 for single family and 18.93 for multiple family residences. In Sunnyslope, the household size is 3.31 and 10.4 for single family and multiple family residences, respectively. Information about the projected connections is discussed in Section 4.2. While the District is a wholesaler of CVP water to HUA, it does not provide urban water supply directly in the HUA. **Table 3-1 W** shows the total population of the two retailers (Hollister and Sunnyslope) served by the District.


Additional increases in population are expected to occur in the unincorporated part of the county, outside the Hollister Urban Area. The City of Hollister and Sunnyslope have no plans to serve this increase and thus, these increases are not included in the future population or future demand calculations. However, it is recommended that development in neighboring areas continue to be tracked as increases in groundwater pumping for these developments may impact groundwater resources of the HUA.


Table 3-1 Hollister Retail: Population - Current and Projected							
Population	2015 2020 2025 2030 2035 2040						
Served	22,542	25,803	29,477	33,946	39,384		
						•	

NOTES: Hollister. 2015 population based on DWR tool, future population based on projected number of connections

Table 3-1 Sunnyslope Retail: Population - Current and Projected								
Population 2015 2020 2025 2030 2035 2040(d								
Served	19,380	23,619	28,395	34,205	41,275	0		
NOTES: Sunnyslope. 2015 population based on DWR tool, future population based on projected number of connections								

Table 3-1 Wholesale: Population - Current and Projected								
Population	2015	2020	2025	2030 2035		2040(opt)		
Served	41,922	49,422	57,871	68,152	80,659			
NOTES: Assum	ned same as	s retailer to	tal					





4. SYSTEM WATER USE

Hollister's and Sunnyslope's past, current and projected water demands are presented in this section. Current water demand is provided by water use sector and projected to 2035 in five-year increments. Current system losses are also provided and projected to 2035.

4.1 WATER USES BY SECTOR

Tables 4-1 Hollister Retail and 4-1 Sunnyslope Retail show the number of water service accounts and delivery volumes by customer type in 2015 for the City of Hollister and Sunnyslope, respectively. In recent years, the number of accounts (specifically residential connections) decreased slightly in Hollister but increased slightly in the Sunnyslope service area. Hollister and Sunnyslope water connections are classified into seven water use categories, which are described below along with selected California Water Code (CWC) citations:

- Single-family residential A single-family dwelling unit. A lot with a free-standing building containing one dwelling unit that may include a detached secondary dwelling.
- Multi-family Multiple dwelling units contained within one building or several buildings within one complex. It should be noted that the number of multi-family accounts is not the same as the number of multi-family units because one connection could supply multiple units.
- Commercial A water user that provides or distributes a product or service. CWC 10608.12 (d). This category also includes institutional uses. This type of user includes, among other users, higher education institutions, schools, courts, churches, hospitals, government facilities, and nonprofit research institutions. CWC 10608.12 (i).
- Industrial A water user that is primarily a manufacturer or processor of materials as defined by the North American Industry Classification System (NAICS) code sectors 31 to 33, inclusive, or an entity that is a water user primarily engaged in research and development. CWC 10608.12 (h). The following link is to the NAICS website: http://www.census.gov/cgi-bin/sssd/naics/naicsrch.
- Landscape-Water connections supplying water solely for landscape irrigation. Such landscapes may be associated with multi-family, commercial, industrial, or institutional/governmental sites, but are considered a separate water use sector if the connection is solely for landscape irrigation.
- Landscape (recycled water) Includes meters that only use recycled water solely for landscape irrigation.
- Distribution System Losses -Reporting of system losses is required in the 2015 UWMPs.

The delivery volumes by customer type for both Hollister and Sunnyslope from 1996 through 2015 are illustrated in **Figure 4-1**. The number of water service connections and volume of water served provide insight into water use volumes and trends associated with different types of users, which can be useful in defining effective water conservation measures. On average, single family residential represents most of the total demand at 68 percent. Multiple family homes and commercial uses each total about 10 percent of total demand. Other uses, including industrial and dedicated landscape irrigation, represent a

combined 10 percent of total demand. Water demand in the HUA peaked in the early 2000s and has decreased since then. The decline in total water demand reflects a water conservation response to the multiple year drought achieved through increased public outreach.

Table 4-1 W shows the volume of raw water that the District delivers to the Lessalt Water Treatment Plant (WTP). Raw water losses from conveyance and storage are typically 10 percent in a normal year and 20 percent in a dry year (Cattaneo 2016). Water losses associated with treatment are included in the retailers' estimates. Other water use sectors such as sales to other agencies, groundwater recharge, and conjunctive use are not performed by retailers in the HUA at this time, are not planned in the future, and are not included in these demand tables.

4.2 PROJECTED WATER DEMAND

Tables 4-2 Hollister Retail and 4-2 Sunnyslope Retail provide projections for water service connections and deliveries in five-year intervals between 2020 and 2035, for Hollister and Sunnyslope, respectively. Future water demands were calculated as part of the HUA Master Plan update, which is now underway. The HUA Master Plan update will be a comprehensive water and wastewater plan for the HUA through 2030. Water demand projections to support the HUA Master Plan update were available for this UWMP and are presented in the Water Demands Projection Memo (HDR 2016) included in **Appendix C**. Total future water demand increase for the HUA was calculated based on future population estimates, shown in **Table 3-1**. The table below details the expected water use by type of connection.

		Increase in	Water Demand				
	Single Family	-		Other	Losses	Cumulative Increase	Total
Base Demand	3,695	559	781	333	629	-	5,996
2020	630	80	63	-	51	824	6,820
2025	1,340	171	125	-	108	1,743	7,740
2030	2,203	281	188	-	172	2,844	8,840
2035	3,254	415	250	-	255	4,174	10,170

Cumulative Increase in Water Use (AFY)

Water conservation measures were considered but since the demands were developed based on historical consumption during a drought period, additional conservation was not included in the demand forecasts. The base demand period (2010 to 2015) has been part of a multiple year drought and many residents have already reduced water use in response to active water conservation outreach. Additional future reductions are not presumed (as recorded in **Table 4-5 R**).

The population growth and associated water demand increases projected in the 2008 Master Plan have not been realized. The population in the HUA has not increased as expected due in part to the economic downturn that began in 2008 and continued to affect the economy of the HUA until recently. In addition, the recent drought and increases in water conservation have decreased per capita water use.

Table 4-3 R sums the total water demand for the HUA including the non-potable demand that will be satisfied by recycled water (discussed in Section 6). Total water demand is expected to increase to 10,286 AFY by 2035, including recycled water. **Table 4-2 W** shows the expected volume of raw water the District will deliver to HUA WTP. **Table 4-3 W** summarizes the total volume of water the District anticipates delivering through 2035; this includes the CVP deliveries to Hollister and Sunnyslope plus expected raw water losses. **Tables 4-2W and 4-3W** are identical as the District has no plans to serve recycled water to the urban retailers. Losses occur within the District's CVP conveyance and storage system (e.g., from evaporation and seepage); these losses are counted in **Tables 4-2W and 4-3W**.

4.3 WATER SAVINGS

Water conservation is encouraged in the HUA through a variety of programs, which are discussed in depth in Section 9. To meet the future water use per capita demand targets, Hollister, Sunnyslope, the District, and the WRA, through their water conservation coordinator, plan to focus their efforts on several demand management measures (DMMs). These specific DMMs represent opportunities for maximum water savings, based on local experience during the recent drought. The DMMs that will continue to save water include state level programs:

1. Model Water Efficient Landscape Ordinance (effective December 1, 2015) – The revised ordinance is projected to reduce typical residential landscape demands by about 20 percent from demands estimated using the prior ordinance provisions. Commercial landscapes may reduce water demands by about 35 percent over the prior ordinance.

2. California Energy Commission Title 20 appliance standards for toilets, urinals, faucets, and showerheads – The appliance standards determine what can be sold in California and therefore will affect both new construction and replacement fixtures in existing homes.

3. CALGreen Building Code – The CALGreen Building Code requires residential and non-residential water efficiency and conservation measures for new buildings and structures that will reduce the overall potable water use inside each building and structure by 20 percent. The 20 percent water savings can be achieved in one of the following ways: (1) installation of plumbing fixtures and fittings that meet the 20 percent reduced flow rate specified in the CAL Green Code, or (2) by demonstrating a 20 percent reduction in water use from the building "water use baseline." The practical representation of the savings in unit water demands from this code would be to reduce indoor baseline unit demands for recently constructed residential units downward by 2 to 5 percent, although this may be redundant with any reduction already represented by the Title 20 appliance standards.

In addition, several local programs already in place may reduce future water demand:

- Retail conservation pricing "Conservation pricing" provides incentives to customers to reduce average or peak use, or both. All water rates and charges for Hollister, Sunnyslope, and the District are established through ordinance by the appropriate governing body. Currently, both Hollister's and Sunnyslope's rate structures for water service are increasing block structures for residential customers. Adjusting the rates or adding additional blocks for water rates may continue to improve water conservation.
- Public information programs One of the cornerstones of an effective water conservation program is effective public outreach and education. Public information and outreach—which convey the need for efficient water use and show how customers can reduce water use— supports all other elements of the program. Public outreach promotes water conservation in general, by informing customers of the needs, benefits, and methods of conserving water. Outreach can also foster understanding regarding how water conservation fits into the overall water management for the HUA. Current public outreach is focused on schools and students with classroom presentations promoting efficient water use and supplementation of presentations with grade level-appropriate education materials. Presentations are also given to local community groups and service organizations. While the effect of public outreach is unquantifiable, its qualitative effect on water conservation is considered very important.
- Water sense specifications (WSS) for residential development The WSS involves providing
 incentives (such as rebates, recognition programs, or reduced connection fees), or ordinances
 requiring residential construction to meet WSS for single-family and multi-family housing units
 until a state or federal regulation is passed requiring this standard. While the HUA agencies have
 not yet developed WSS incentives or adopted WSS codes, they do have a variety of rebate and
 retrofit programs that have successfully reduced water demand.
- Landscape This DMM applies to non-residential accounts with dedicated irrigation meters and to commercial, industrial, and institutional (CII) accounts with mixed-use meters. Both the City and Sunnyslope continue to implement landscape audit and incentive programs and these programs can be expanded to account for more water savings. In addition, the WRA has offered landscape efficiency programs over the past two years to encourage water conservation for large landscape and residential customers. Several DMMs are targeted to reducing water waste and increasing water efficiency. The turf removal program encourages irrigators to replace their high water demand turf with water efficient landscaping. The program, advertised in both English and Spanish, has been very successful in reducing water demand during the recent drought.

A complete list of the DMMs that will be employed by the HUA and the estimated water reductions resulting from their implementation is presented in **Section 9.**

4.4 DISTRIBUTION SYSTEM WATER LOSSES

Water losses for Hollister and Sunnyslope were calculated using the required methodology and audit tool developed by AWWA (www.awwa.org/resources-tools/water-knowledge/water-loss-control.aspx). The CWC requires reporting of losses for the most recent 12 months, for all three agencies this is the calendar

year. Reported losses for the most recent 12 months are shown in **Table 4-1 Hollister Retail and 4-1 Sunnyslope Retail** for Hollister and Sunnyslope, respectively. The water loss volume and reporting period are repeated in **Tables 4-4 Hollister Retail and 4-4 Sunnyslope Retail** for Hollister and Sunnyslope, respectively. The AWWA audit results for each retailer are included in **Appendix D**. The AWWA tool uses the total water supply and deliveries by agency to estimate the total water loss. The tool also breaks out apparent water losses (unmetered water or inaccurate meter readings) and real water losses (water leaving the system through leaks, or other physical issues).

In 2015, Sunnyslope reported a 3 percent water loss, equivalent to 66 AF. The agency attributes this to inaccurate meters and currently has a program to replace aging meters. During this same period, Hollister reported a 16 percent water loss, equivalent to 451 AFY. Hollister has a large number of unmetered water uses including line flushing for sampling, fire flows, construction uses, and other unmeasured and unclassified uses and losses. In the AWWA tool for Hollister, the default ratio of apparent and real losses is used due to lack of data. However, Hollister estimates most of its water losses are due to the apparent water loss of unmetered activities.

Losses associated within the CVP storage and distribution system are include in **Table 4-4 W**as raw water losses for the District. Losses are associated with evaporation and seepage as a result of storage in an open reservoir. It is estimated that water losses are 10 percent in normal years and 20 percent of supply in dry years for the CVP storage and distribution system operated by the District. As 2015 was a dry year, **Table 4-4 W** shows a 20 percent loss, equivalent to 430 AF.

4.5 WATER USE FOR LOWER INCOME HOUSEHOLDS

State legislation (SB 1087 and Government Code section 65589.7), effective January 1, 2006, specifies that local water agencies and sewer districts must grant priority for service hook-ups to projects that help meet the community's fair housing need.

In other words, policies and procedures should be written to provide priority service to new developments with affordable housing and these policies should be updated every five years. San Benito County completed a regional housing needs assessment (RHNA) in 2014 (Council of San Benito County Governments). The RNHA indicates that approximately 24 percent of the housing for both the City of Hollister and the County unincorporated areas serves the population in the very low income range. The values presented throughout this report represent 24 percent of the estimated single family and multifamily demand for each time period shown, as noted in **Table 4-5 R**.

4.6 CLIMATE CHANGE

Climate change can affect projected water demand. The climate change vulnerability assessment, available from the UWMP guidebook, was performed for the HUA. The checklist is included as **Appendix E**. Water demand may increase as water use varies by more than 50 percent seasonally. Climate change is likely to increase temperatures and ET, and may also increase the duration of high temperature/ET periods. This would increase water demand for landscape irrigation and other residential uses, with particular ramifications for summer months.

Table 4-1 Hollister Retail: Demands for Potable and Raw Water - Actual				
Use Type (Add additional rows as needed)		2015 Actual		
<u>Use Drop down list</u> May select each use multiple times These are the only Use Types that will be recognized by the WUEdata online submittal tool	Additional Description (as needed)	Level of Treatment When Delivered Drop down list	Volume	
Single Family		Drinking Water	1,409	
Multi-Family		Drinking Water	260	
Commercial	includes institutional	Drinking Water	389	
Industrial		Drinking Water	224	
Landscape		Drinking Water	145	
Other		Drinking Water	0	
Losses			451	
		TOTAL	2,879	
NOTES: Hollister data based on 2	015			

Table 4-1 Sunnyslope Retail: Demands for Potable and Raw Water - Actual				
Use Type (Add additional rows as needed)		2015 Actual		
<u>Use Drop down list</u> May select each use multiple times These are the only Use Types that will be recognized by the WUEdata online submittal tool	Additional Description (as needed)	Level of Treatment When Delivered Drop down list	Volume	
Single Family		Drinking Water	1,598	
Multi-Family		Drinking Water	195	
Commercial	includes institutional	Drinking Water	22	
Industrial		Drinking Water	0	
Landscape		Drinking Water	88	
Other		Drinking Water	39	
Losses			66	
		TOTAL	1,941	
NOTES: Sunnyslope PWSS 2015				

Use Type (Add additional rows as needed)	2	015 Actual	
<u>Use Drop down list</u> May select each use multiple times These are the only use types that will be recognized by the WUE data online submittal tool	Additional Description (as needed)	Level of Treatment When Delivered <i>Drop down list</i>	Volume
Sales to other agencies	Imported Water to WTP	Raw Water	1,791
Losses	Losses	Raw Water	358
		TOTAL	2,14

Use Type (Add additional rows as needed)	Additional Description	Report	Proje To the Exte	ected Wate ent that Rec		vailable
<u>Use Drop down list</u> May select each use multiple times These are the only Use Types that will be recognized by the WUEdata online submittal tool	(as needed)	2020	2025	2030	2035	2040-opt
Single Family		2,002	2,308	2,679	3,131	
Multi-Family		354	393	440	498	
Commercial	includes institutional	505	532	559	586	
Industrial		276	276	276	276	
Landscape	not include recycled water dei	178	178	178	178	
Other		0	0	0	0	
Losses		569	594	621	657	
	TOTAL	3,885	4,280	4,753	5,325	0

Use Type (Add additional rows as needed)		Renort	Proje To the Exte	ected Wate		vailahle
<u>Use Drop down list</u> May select each use multiple times These are the only Use Types that will be recognized by the WUEdata online submittal tool	Additional Description (as needed)	2020	2025	2030	2035	2040-opt
Single Family		2,322	2,727	3,219	3,818	
Multi-Family		285	337	399	476	
Commercial	includes institutional	63	98	134	170	
Industrial		0	0	0	0	
Landscape		108	108	108	108	
Other		47	47	47	47	
Losses		110	143	179	227	
	TOTAL	2,935	3,460	4,087	4,845	0

Use Type (Add additional rows as needed)		Rep	Proj port To the Ext	ected Water tent that Reco		ible
Drop down list May select each use multiple times These are the only Use Types that will be recognized by the WUEdata online submittal tool.	Additional Description (as needed)	2020	2025	2030	2035	2040 (opt)
Sales to other agencies	HUA agencies	4,360	5,200	5,200	6,880	
Sales to other agencies	Outside HUA	400	400	400	400	
Losses	system losses	872	825	825	825	
	TOTAL	5,632	6,425	6,425	8,105	0

Table 4-3 Retail: Total Water De	Table 4-3 Retail: Total Water Demands								
	2015	2020	2025	2030	2035	2040 (opt)			
Potable and Raw Water From Tables 4-1 and 4-2	4,820	6,820	7,740	8,840	10,170	0			
Recycled Water Demand From Table 6-4	116	116	116	116	116	0			
TOTAL WATER DEMAND	4,936	6,936	7,856	8,956	10,286	0			
NOTES:									


2015 2020 2025 2030 2035 2040(opt)						
	2015	2020	2025	2030	2033	2040(0pt)
Potable and Raw Water From Tables 4-1 and 4-2	2,149	5,632	6,425	6,425	8,105	0
Recycled Water Demand From Table 6-4	0	0	0	0	0	0
TOTAL WATER DEMAND	2,149	5,632	6,425	6,425	8,105	0

Table 4-4 Hollister Retail: 12 Month Water Loss Audit Reporting		
Reporting Period Start Date (mm/yyyy)	Volume of Water Loss	
01/2015	451	
NOTES: Hollister based on AWWA tool		

Reporting		
Reporting Period Start Date (mm/yyyy)	Volume of Water Loss	
01/2015	66	
NOTES: Sunnyslope based on AWWA tool		

Table 4-4 Wholesale: 12 Month Water Loss Audit Reporting					
Reporting Period Start Date (mm/yyyy) Volume of Water Loss					
01/2015 358					
NOTES: This is not an audited loss. It is estimated as a 20 percent loss during drought conditions. Losses associated with Lessalt WTP are included in the retailer water system losses.					

Table 4-5 Retail Only: Inclusion in Water Use Projections	
Are Future Water Savings Included in Projections? (Refer to Appendix K of UWMP Guidebook) Drop down list (y/n)	No
If "Yes" to above, state the section or page number, in the cell to the right, where citations of the codes, ordinances, etc utilized in demand projections are found.	
Are Lower Income Residential Demands Included In Projections? Drop down list (y/n)	Yes
NOTES:	



This Page Intentionally Blank

5. BASELINES AND TARGETS

In the 2015 Plan, water agencies must demonstrate compliance with their established water use target for the year 2015. This will also demonstrate whether or not the agency is currently on track to achieve its 2020 target. Compliance is verified by DWR's review of the SB X7-7 Verification Form submitted with an agency's 2015 UWMP. The SB X7-7 Verification Form, which includes all Tables labeled SBX7-7, is described in this section and included in **Appendix F** and summarized in **Tables 5-1 and 5-2**. The process for defining baseline water use and calculating target water use was defined by DWR. This process includes the identification of a suitable baseline period, estimation of the population served for all years in the baseline period, compilation of gross water use for each year of the baseline period, estimation of daily per capita water use for each year in the baseline period, and calculation of water use targets for 2015 and 2020.

5.1 UPDATED CALCULATIONS FROM 2010 UWMP

In the 2010 UWMP, the regional gross water use, baselines, and targets were calculated for Hollister and Sunnyslope separately and then the region's goals were presented as a weighted average of the two agencies. During review of the 2010 UWMP, DWR requested revision of the gross water use estimate. Because flow from the Lessalt WTP to the agencies is not always monitored discretely for each service area, gross water use for the baseline period must be calculated as a regional total (Huff, 2011). This revised gross water use affected the calculated baseline per capita daily use and the per capita demand targets. The revised regional totals from the 2010 UWMP process are included in **Appendix F**, and the methodologies for calculating baseline per capita daily water use and target water use are described below.

Throughout this section, the two retailers are treated as one regional alliance.

5.2 BASELINE PERIOD

In accordance with Senate Bill 7, water suppliers must define a 10- or 15-year water use Base Period. This Base Period is used to calculate a Base Daily per Capita Water Use, which is the baseline for computation of required future reductions. Senate Bill 7 requires retailer to reduce per capita daily water use 10 percent by 2015 and 20 percent by 2020, as compared to Base Daily per Capita Water Use. Because no recycled water was supplied within the HUA in 2008, a 10-year base period is required.

The baseline period selected for the HUA is 1996 through 2005. This period was representative of water use for each retailer; water use in more recent years was artificially low because of drought and economic factors. Base period information including the full 10 year period and the 5-year base period used to calculate the minimum Water Use Reduction Requirement is shown in **SBX7-7 Table 1**, located in **Appendix F**.

5.3 SERVICE AREA POPULATION

Calculation of per capita daily water use for the baseline period requires annual estimates of population. DWR developed an online tool designed specifically for estimating annual population within UWMP areas for baseline and target years. This tool is based on 2010 United States Census (Census) data. The population estimates used in this UWMP were derived from DWR's tool, as noted on **SBX7-7 Table 2**. The Hollister and Sunnyslope populations were estimated separately and added together to produce annual estimates of population for the entire HUA. The first step is to estimate population of the service areas using US Census data. As noted on **SBX7-7 Table 2**, the online population tool provided for UWMP was used and the total population for HUA is shown in **SBX7-7 Table 3**.

5.4 GROSS WATER USE

HUA annual gross water use for the baseline period was calculated for the region rather than for the individual agencies separately. As noted above, this is required because Lessalt WTP water deliveries are not measured separately for the Hollister and Sunnyslope service areas. Regional gross water use for the HUA is shown in **SB X7-7 Table 4**.

Gross water use includes all water into the system, which comes from the following sources:

- CVP imported water total flow in to the Lessalt WTP is metered; flow out to Hollister and Sunnyslope is not individually measured
- Hollister produced groundwater –monitored at the point of production (e.g. wells)
- Sunnyslope produced groundwater –monitored at the point of production (e.g. wells)
- Unaccounted for water losses, etc.

The contribution of each of these water sources are shown in **SB X7-7 Table 4 A.**

5.5 BASELINE DAILY PER CAPITA WATER USE

The annual population estimates and gross water use data for the HUA were used to calculate per capita daily water use for each year of the baseline period, as shown in **SB X7-7 Table 5**. This is a simple calculation wherein the annual gross water use is converted to average daily water use and then divided by population for each year. As shown in **SB X7-7 Table 5** baseline per capita daily water use for the HUA was 157 gallons per capita day (gpcd).

SB X7-7 Table 5 includes calculations of the five-year baseline per capita water use for the HUA. The five-year baseline period was 2003 through 2007 as noted above, and the same period was used for both agencies. Average per capita daily water use during this five year period in the HUA was 155 gpcd.

SB X7-7 Table 5 also shows estimated per capita daily water use for 2015, which was 103 gpcd. Baseline and 2015 daily per capita water use estimates are summarized in **SB X7-7 Table 6**.

5.6 2015 AND 2020 TARGETS

Four methods are allowed by Senate Bill 7 for calculating the 2015 and 2020 water use targets. The first method is to simply calculate 90 and 80 percent of the baseline daily per capita water use as the 10 percent reduction for 2015 and 20 percent reduction for 2020. This first method was used for the HUA because it is the most applicable to the available data as well as the water use and demographic characteristics of the HUA. Target water use in 2020 should be 80 percent of baseline daily per capita water use. For the HUA, the calculated 2020 water use target is 126 gpcd (157 gpcd x 0.80 = 125.6 gpcd). The regional calculation is shown in **SB X7-7 Table 7A**.

Water Code requires that the HUA also calculate the minimum water use reduction requirement because the five-year baseline per capita water use is greater than 100 gpcd (Water Code Section 10608.22). The minimum reduction requirement, **SB X7-7 Table 7F,** ensures that the retailers, regardless of method used to generate future targets, will reduce water demand by an adequate amount. The target 2020 per capita water use target cannot exceed 95 percent of the 5-year baseline water use. For the HUA, the 2020 minimum water use target is 147 gpcd (0.95 x 155 gpcd = 147.25 gpcd). The calculated water use target from Method 1 above is a smaller volume than the minimum reduction requirement (126 gpcd versus 147 gpcd). Therefore, the retailers meet the minimum reduction requirement and are free to use the target calculated by Method 1.

Water Code also requires that 2015 UWMPs track progress towards meeting the 2020 goal of 20 percent water use reductions. DWR has established a target requirement for 2015 that is halfway to the 2020 target. The HUA regional water use target for 2015 is 142 gpcd (the average of the baseline use and 2020 target values). The HUA regional 2015 and 2020 water use targets are shown in **SB X7-7 Table 8**. The 2020 target per capita water use of 126 gpcd applies to all years beyond 2020, including the five year increments used throughout this UWMP (i.e. 2025, 2030, and 2035).

5.7 2015 COMPLIANCE DAILY PER CAPITA WATER USE

SB X7-7 Table 9 compares actual 2015 per capita use to the interim target. While DWR allows optional adjustments to the interim target, these allowances do not apply to the HUA. Based on estimated population (using the DWR population tool) and gross water use, the actual 2015 per capita daily water use was 103 gpcd. The HUA not only met, but exceeded the interim goal of 142 gpcd.

5.8 WHOLESALER PARTICIPATION

As the wholesaler, the District is not required to establish and meet baseline and targets for daily per capita water use. However, wholesale agencies are required to provide an assessment of their present and proposed future measures, programs and policies that will help the retail water suppliers meet water use targets. These demand management programs are administered by the WRA, which is funded in large part by the District. The demand management programs and DMMs developed and administered by the WRA are detailed in **Section 9**.

This Page Intentionally Blank

Table 5-1 Baselines and Targets SummaryRetail Agency or Regional Alliance Only										
Baseline Period	Start Year	End Year	Average Baseline GPCD*	2015 Interim Target *	Confirmed 2020 Target* <i>126</i>					
10-15 year	1996	2005	157	142						
5 Year	2003	2007	155							
*All values are in Gallons per Capita per Day (GPCD)										
NOTES:										

Actual 2015 GPCD	2015 Interim Target GPCD	Optional Adjustments to 2015 GPCD "0" for adjustments not used Methodology 8 Extraordinary Economic Weather TOTAL				Enter <i>From</i> Adjusted	2015 GPCD (Adjusted if applicable)	Did Supplier Achieve Targeted Reduction for 2015? Y/N
103	142	Events	Adjustment	Normalization	Adjustments 0	2015 GPCD 103	103	Yes

6. SYSTEM SUPPLIES

The HUA relied historically on the San Benito County portion of the Gilroy-Hollister Valley Groundwater Basin (**Figure 6-1**) for its municipal water supply. Since 2003, CVP water imported by the District has been available for urban uses. This section describes the existing water sources plus recycled water, a planned future supply. The historical and current supply by source for the HUA is shown in **Figure 6-2**.

6.1 IMPORTED WATER

The CVP is a Federal water system operated by the U.S. Bureau of Reclamation (USBR) and created to protect the Central Valley from water shortages and floods; improve navigation on the Sacramento River; provide supplies of municipal and industrial water; enhance water quality; generate electric power, conserve fish and wildlife; and create opportunities for recreation. The CVP consists of 20 dams and reservoirs, 11 power plants, and 500 miles of major canals, conduits, and tunnels. About nine million AFY of water are managed by the CVP and about seven million AFY of water for agricultural, urban, and wildlife uses are delivered annually. An average of five million AFY of CVP water is provided to farms to irrigate about three million acres of land and about 600,000 AFY of water is provided for municipal and industrial uses. About 800,000 AFY are provided for fish and wildlife habitats and 410,000 AFY to State and Federal wildlife refuges and wetlands, pursuant to the Central Valley Project Improvement Act (CVPIA). Finally, the CVP generates 5.6 billion kilowatt hours of electricity annually (Mintier Harnish 2009).

The San Benito County Water District has a 40-year contract (extending to 2027) for a maximum of 8,250 AFY of municipal and industrial (M&I) water and 35,550 AFY of agricultural water. The District negotiated the renewal of this contract in May 2007. Imported water is delivered to agricultural, municipal, and industrial customers in Zone 6 through 12 subsystems containing approximately 120 miles of pressurized pipeline laterals (SBCWD 2011). Zone 6 is the District's zone of benefit for CVP water, and it overlies the Pacheco, Bolsa Southeast, San Juan, Hollister East, Hollister West, and Tres Pinos groundwater subbasins (as defined by SBCWD, see **Figure 6-3**).

The District distributes CVP water to both agricultural and M&I customers in Zone 6. Hollister and Sunnyslope purchase CVP water directly from the District as they are the primary M&I CVP customers. Other M&I uses of CVP water include urban irrigation, golf courses, and potable supply for the Stonegate community. Actual CVP deliveries are modified on an annual basis by USBR, reflecting hydrologic conditions (e.g., drought), reservoir storage, and the environmental status of the Sacramento-San Joaquin Delta. In water year 2015, the allocation for M&I users was 25 percent of historical use while agricultural users received zero percent of contract amounts. Reductions in recent years are primarily the result of the cumulative effects of the sustained state-wide drought (Todd 2015a).

The USBR has instituted its Shortage Policy in five of the past six years in response to drought, overcommitment of CVP supplies, and supply limitations imposed by environmental, regulatory, and legal constraints in the Sacramento-San Joaquin River Delta (Delta). The Shortage Policy provides that the allocation of M&I CVP water will be based on a contractor's historical use of CVP M&I water, with opportunities for adjustments to account for growth, extraordinary conservation measures, and use of non-CVP water. The historical M&I usage served by the District is currently set at 8,250 AFY, which is the District's full CVP M&I contract volume.

WATER SUPPLY FACILITIES

Water treatment for potable M&I supplies within the HUA is provided by the Lessalt WTP, a facility owned by the District and operated by Sunnyslope. The Lessalt WTP, placed into operation in January 2003, is designed to treat imported CVP water using microfiltration and chlorine disinfection (HDR 2008a). In 2015, the plant was upgraded to not produce THMs through granulated activated carbon filtration to remove organic materials prior to. In addition, further treatment to remove iron and manganese was added. Treated water is distributed to Hollister and Sunnyslope customers. The Lessalt WTP was constructed to provide an additional source of water and to improve water quality by supplementing existing groundwater with higher quality surface water. The Lessalt WTP was completed in 2002 with a nominal design capacity of 3 million gallons per day (MGD). Because of hydraulic constraints, process limitations, and reductions in CVP water availability, the WTP has, until recently, operated at an average rate less than 1.6 MGD. A WTP expansion completed in April 2015 increased the operational capacity of Lessalt to 2.0 MGD, which extends the current capacity of the WTP to an annual total of 2,240 AFY. Currently, direct use of CVP water for M&I purposes within the HUA is limited by the capacity of the Lessalt WTP.

The District manages San Justo Reservoir as storage for imported CVP water. In times of full allocation, the District is able to purchase additional water to keep as a reserve for future dry years. The District's planned reserve is 3,000 AF, sufficient to provide 1,000 AF for each dry year for up to three years. Based on future demand and supply calculations, this reserve may only be needed when CVP allocations are at or below 50 percent.

FUTURE WATER PROJECTS

The HUA agencies are currently moving forward with a second surface water treatment plant to treat CVP imports for delivery to urban areas not served by the Lessalt plant. The new plant, which will be called the West Hills WTP, has been sized to treat an additional annual capacity of 2.25 MGD, with a peak monthly treatment capacity of 4.5 MGD. This will increase the treated M&I CVP water available to the HUA by 2,520 AFY. Construction of the West Hills WTP has begun and the plant is expected to be online by the end of 2017. With the West Hills and Lessalt WTPs, the HUA will have the capability to treat up to 4,760 AFY.

6.2 GROUNDWATER

Groundwater is a major source of supply for Hollister and Sunnyslope. The two retailers pump directly from wells located in the HUA. The District, formed by a special act of the State, has regional responsibility and authority to manage groundwater. As part of its management activities, the District provides recharge to the basin, explores expanded groundwater banking, monitors water levels and water quality, and reports annually on groundwater conditions in the basin.

6.2.1 BASIN DESCRIPTION

LOCATION

The HUA overlies the Gilroy- Hollister basin, designated as DWR Basin No. 3-3, shown on **Figure 6-1** (DWR 2016a). The basin covers 200 square miles of the Pajaro River watershed and is drained by its tributaries, most notably the San Benito River. The San Benito River, intermittent in some parts of the basin, runs through the southern portion of the basin before reaching the Pajaro River. The San Benito River, when flowing, is a recharging stream along much of its channel, but groundwater contributes some base flow upstream of its confluence with the Pajaro River. The Hernandez Reservoir, located upstream of the basin on the San Benito River, is operated to enhance flow in the river and recharge the groundwater basin.

GEOLOGY

The Gilroy-Hollister groundwater basin lies within the Coast Ranges of California, which are a series of elongated ranges and valleys with a predominantly northwesterly trend. The Hollister Valley's origin and shape has been controlled by folding and faulting of basement rocks in the area, resulting in low-lying areas that have been infilled with unconsolidated to poorly consolidated alluvium of Tertiary and Quaternary age. The Quaternary alluvial deposits compose the valley floor and generally define the groundwater basin (California Geologic Survey 2002, Todd 2004). Numerous investigators have recognized the difficulty in describing the subsurface stratigraphy of the basin, due, in part, to sparse geophysical log data and a lack of distinctive textures and composition among the sedimentary units (Kilburn 1972, Faye 1974 and 1976, Luhdorff and Scalmanini 1991).

Major geologic faults, including the San Andreas and Calaveras, trend northwestward through the area. Most notably, the Calaveras fault is active and cuts through the basin, trending north-northwest from Hollister to the Pajaro River at San Felipe Lake, and separating the northern valley into two distinct geologic units at depth. The fault is perceived to impact groundwater flow locally, perhaps due to the presence of low permeability rock fragments and blocks displaced upward and adjacent to more permeable alluvial material along the fault zone (Todd 2004).

The Quaternary-age alluvium contains the main aquifers in the groundwater basin. The aquifers are the coarse-grain layers of sands and gravels with interbedded layers of silts and clays. The geometry of the basin suggests that basin-fill units were deposited in alluvial fan and fluvial environments from a variety of source rocks and directions. These deposits interfinger in the subsurface, making the differentiation of

discrete aquifer packages difficult on a regional basis. This also results in variable aquifer properties across the basin. Previous investigators indicate wide variability in aquifer transmissivities (Luhdorff and Scalmanini 1991, Faye 1974). Although poorly defined, regional variations in permeability likely create preferential pathways for groundwater, especially in paleo-channel deposits, which may exist beneath current major stream courses or elsewhere in the basin (Todd 2004).

SUBAREAS

Figure 6-3 shows the eight subbasins delineated in 1996 for the District annual reports: Bolsa, Bolsa Southeast (SE), Pacheco, Hollister East, Tres Pinos, Hollister West, and San Juan subbasins, and the Llagas subbasin in Santa Clara County. This definition of subbasins is maintained in this report, supporting consistent reporting of groundwater conditions.

The Hollister Urban Area overlies the Hollister East, Hollister West, and Tres Pinos subbasins. Hollister and Sunnyslope pump directly from these subbasins. In water year 2015, 45 percent of Hollister and Sunnyslope pumping was located in the Hollister West subbasin, 35 percent in the Tres Pinos subbasin and 20 percent in the Hollister East subbasin. The subbasins are hydrologically connected and pumping in the HUA affects the entire groundwater basin.

GROUNDWATER LEVELS AND FLOW

In general, groundwater in the basin flows from the southeast and eastern portions of the basin toward the western and northwestern portions of the basin to the Pajaro River. However, general flow directions have been reversed in the Bolsa subbasin due to groundwater pumping; groundwater in the Bolsa subbasin near the Pajaro River flows southeast toward lower water levels.

Groundwater levels have been recorded in the basin since at least 1913 by various agencies including USBR, DWR, Pacheco Pass Water District, San Benito County, University of California Cooperative Extension, and the United States Geological Survey (USGS) (Clark 1924, Kilburn 1972, Farrar 1981, Creegan & D'Angelo 1990). The District monitors water levels in approximately 80 to 100 wells on a semiannual and, more recently, a quarterly basis and reports the data to CASGEM. Water levels and trends are presented in the District annual reports (e.g. Todd 2015a). Groundwater generally occurs under unconfined and confined conditions. Surficial clay deposits, especially in the Bolsa and San Juan Valley subbasins, create confining layers. These layers have resulted in local artesian conditions wherein groundwater levels in wells have risen to the surface.

Figure 6-4 illustrates long term changes in groundwater levels in the basin. Water elevations in key wells from each subbasin for each monitoring event have been averaged to produce representative hydrographs for each subbasin. These key wells are shown on the map in **Figure 6-4**. It should be noted that these subbasin hydrographs represent average conditions in each subbasin and illustrate long term trends, but do not show localized variations in water levels.

GROUNDWATER RECHARGE

The District owns and operates two reservoirs along the San Benito River. Hernandez Reservoir (capacity 17,200 AF) is located on the upper San Benito River in southern San Benito County. Paicines Reservoir (capacity 2,870 AF) is an offstream reservoir between the San Benito River and Tres Pinos Creek. It is filled by water diverted from the San Benito River, with some of the diversions consisting of natural runoff and some consisting of water released from Hernandez Reservoir. Water stored in the two reservoirs is released for percolation in Tres Pinos Creek and the San Benito River to augment groundwater recharge during the dry season. Since 1996, releases from Hernandez have ranged between 0 AFY and 26,300 AFY, generally reflecting variations in inflow. The total releases from Paicines Reservoir range from 0 AFY to 6,139 AFY (Todd 2015a).

In the past, the District has purchased and percolated additional CVP imported water for groundwater management. This program began in 1988, and CVP percolation peaked in 1997 at 11,087 AFY. Managed CVP percolation volumes were reduced following 1997 in response to successful recovery of the groundwater basin from overdraft. In recent years, no significant releases of CVP imported water have occurred due to reduced allocations and local areas of high water levels.

Hollister and Sunnyslope percolate treated wastewater discharge to the groundwater basin. The City of Hollister Domestic Wastewater Treatment Plant (DWWTP) represents the major portion, amounting to 1,816 AF in water year 2015. Wastewater percolation has been decreasing in recent years and is expected to continue to decrease as recycled water use increases.

WATER QUALITY

The District conducts semiannual sampling (spring and fall) of more than 24 wells distributed spatially over the basin. In addition, water suppliers with more than six connections, including Hollister and Sunnyslope, are required to monitor and report water quality to the State Water Resources Control Board Division of Drinking Water (DDW). These data and others are used by the District to monitor and track the status of water quality basin-wide.

A comprehensive water quality database for the District was created in 2004. This database, funded in part by a DWR grant, involved compilation of all available water quality data with the intent of regular update with future data. The first major update occurred as part of the 2007 Annual Groundwater Report. The database is now regularly updated with readily available local data. A more complete update of the water quality database, including research at local, regional, and state agencies, occurs on a triennial basis. The database was updated in November 2013, as part of the Annual Groundwater Report for Water Year 2013 (Todd 2013).

The quality of groundwater in the Gilroy-Hollister groundwater basin has been described as highly mineralized and of marginal quality for drinking and agricultural purposes. The mineralized water quality is typical of other relatively small Coast Range groundwater basins, but has also been impacted by decades of human-related activities, both agricultural and urban.

A general measure of groundwater quality is total dissolved solids (TDS). For drinking water purposes, TDS concentration of 500 milligrams per liter (mg/L) or less are recommended; however, TDS concentrations up to 1,000 mg/L are acceptable. TDS concentrations are affected by both natural and anthropogenic sources. **Figure 6-5** shows generalized areas of similar TDS concentrations. The map is based on the maximum historical concentrations of TDS of all monitored wells and was updated in 2013 (Todd 2013).

The agencies in the HUA plan to blend treated imported CVP water with local groundwater to reduce TDS in Hollister and Sunnyslope's water supplies. If CVP is available, at least 65 percent of the M&I water supplied in the HUA is planned to come from CVP imports, with the remaining 35 percent of supply made up from groundwater. This blending would result in better water supply, and sufficient wastewater quality to produce high quality recycled water and meet wastewater discharge requirements with the California Regional Water Quality Control Board (RWQCB).

Recent analyses of water quality in Hollister wells reported hexavalent chromium (also known as chromium VI, or CrVI) concentrations above the newly reduced California maximum contaminant level (MCL) of 10 micrograms per liter (μ g/L) (SWRCB 2015). These problematic concentrations occurred in all four of Hollister's existing active water supply wells, located on the west side of the City (Todd 2015b). Treatment for CrVI is expensive, and not all of the wells have equal treatment options. As such, Hollister investigated the source of CrVI in the wells and assessed the potential to reduce CrVI concentrations by modifying the construction of the wells. These assessments addressed geologic, water quality, well construction, and water distribution system information (Todd 2015b) and included a field investigation with vertical flow and water quality profiling of a selected well (Hollister Well 4). Subsequent analysis of field data showed that CrVI was present throughout the perforated interval in Hollister Well 4, and indicated no feasible well modification to reduce CrVI concentrations in this well or the other three Hollister wells, which have similar lithology and construction (Todd 2015c). Therefore, Hollister is pursuing the option of blending groundwater from the existing wells with treated imported water from the West Hills WTP currently under construction. DDW has approved the HUA's proposal for a 50/50 blend of groundwater and treated water from the West Hills WTP (SWRCB 2016). Sunnyslope is currently monitoring their wells for CrVI problems and will continue to plan for possible water quality issues.

Other chemicals of concern (COC) for the groundwater basin include boron, chloride, hardness, nitrate, and total dissolved solids (TDS). In some parts of the basin, groundwater does not meet water quality standards; accordingly, the District, water purveyors, and other agencies are examining ways to improve quality in these areas. In addition to the historical COCs, current operations by regulated facilities have introduced new local COCs including perchlorate, metals, and volatile organic chemicals. All areas where these COCs have been discovered are regulated by the Regional Water Quality Control Board (RWQCB) (Todd 2010).

In most of the basin, water quality has remained stable in recent years. Other areas, such as the eastern portion of the San Juan subbasin, have shown variable but increasing trends in key constituents like nitrate and chloride. This limited change in water quality results from local factors including nearby regulated facilities, land use changes, and high groundwater levels.

The preferred and required blending of groundwater with imported CVP water results in a linkage between groundwater supply and CVP allocations. In dry years, when CVP allocations are low, the volume of groundwater supply used by the HUA agencies for urban supplies will be limited to maintain the planned blending ratio. While the blending required for mitigating CrVI concentrations (groundwater limited to 50 percent of supply) is unlikely to be relaxed, blending to achieve other water quality goals may be relaxed on a short term basis in response to drought conditions.

WATER BALANCE AND SUSTAINABLE YIELD

The District produces an annual report that examines changes in groundwater levels and storage as basic indicators of net water balance conditions. A complete water balance for the basin—including detailed estimation of all inflows, outflows, and changes in storage—is documented on a triennial basis. All values for the basin-wide water balance in this section are those calculated and reported in the Annual Groundwater Report for water year 2014 (Todd 2014). The water balance encompasses the subbasins underlying the HUA.

Major inflows include deep percolation from rainfall, return flow from urban and agricultural uses, recharge of reclaimed water, stream percolation (both natural and managed through reservoir and CVP releases), and subsurface inflow from adjacent groundwater basins. Most of these inflows are controlled by hydrological conditions and are generally greater in wet years and reduced in dry years.

Major outflows include pumping from agricultural and urban sources and subsurface outflow to adjacent basins. Agricultural groundwater pumping is measured in Zone 6, but not in other parts of the basin. The volume of agricultural pumping in Zone 6 in any given year is dependent on the volume of CVP imports and the amount and distribution of rainfall, as growers often rely on both groundwater and CVP for water supply. In 2015, domestic, municipal, and industrial pumping decreased in response to the state-wide conservation mandate. As noted, municipal pumping is largely concentrated in the Hollister West, Hollister East, and Tres Pinos subbasins.

The annual change in groundwater storage can be determined by computing the difference in outflows and inflows or by independently assessing change in groundwater levels. The change in storage is calculated by change in water levels annually and by water balance triennially in the District annual report. From 2010 to 2015, the volume of groundwater in storage in Zone 6 decreased every year. The annual decrease ranged from 683 AF to 19,268 AFY. These storage declines show the effect of drought and limited imported water availability on the groundwater basin, and that the basin serves as a reserve during dry times. It is anticipated that in normal and wet years the basin will recover, but recovery rates and extents will depend on precipitation, runoff, water availability, and water use patterns.

Previous studies have estimated safe yield values, defined as the amount of groundwater that can be continually withdrawn without adverse impacts. These estimates of safe yield were completed prior to 2003, and they range from 40,000 to 54,000 AFY (Kennedy/Jenks 2003). No recent safe or sustainable

yield evaluations have been completed for the HUA or the rest of the groundwater basin. ¹ One means of quickly estimating sustainable yield on a large scale is to identify the volume of outflow associated with time period corresponding to relatively stable groundwater elevation and groundwater storage conditions. The period from 2006 through 2008 represents such a period of stable conditions. The storage change during this period was a relatively small decrease of 1,116 AFY, generally indicating equilibrium. Estimated average annual groundwater outflow during this period was 17,852 AFY for the subbasins in which the HUA is located (Hollister East, Hollister West, and Tres Pinos). Despite recent drought conditions and groundwater storage decreases, the HUA sustainable yield value of 16,000 AFY remains applicable for planning purposes (Todd 2010).

Hollister and Sunnyslope are not the only users of the three subbasins that the HUA is within. Agricultural users, small water purveyors, and domestic well users also rely on these groundwater subbasins for their water supply. The District measures all groundwater use in Zone 6 and records the amount of groundwater pumped semi-annually (February and September). In water year 2015 (October to September), groundwater pumped from the Hollister East, Hollister West, and Tres Pinos subbasins totaled 14,908 AFY (Todd 2015). Hollister and Sunnyslope pumped a total of 3,308 AFY (1,960 AFY and 1,348 AFY from Hollister and Sunnyslope, respectively) over the same period. In water year 2015, the retailers represented only 22 percent of total pumping in these three subbasins.

The portion of the local sustainable yield available to Hollister and Sunnyslope in the future is better represented by long-term averages, and not the use patterns observed during the recent drought. This extended state-wide drought had the effect of decreasing water demand in Hollister and Sunnyslope as a result of conservation and limited availability of treated CVP water for municipal supply. In addition, other water users in these subbasins increased pumping due to lack of CVP water for agricultural supply. Moreover, it is anticipated that future urban development will be concentrated in the Hollister and Sunnyslope service areas, thereby increasing demand for local groundwater and potentially altering some land uses with high water demands. As noted above, future use of local groundwater supply may be limited or require treatment due to water quality concerns.

6.2.2 GROUNDWATER MANAGEMENT

The District manages the water resources for all of San Benito County. The District is a California Special District formed in 1953 by the San Benito County Water Conservation and Flood Control Act. The District has jurisdiction throughout San Benito County, and has formed three zones of benefit to fund surface water and groundwater management activities. Zone 1 covers the entire county and provides the funding base for certain District administrative expenses. Zone 3 generally covers the San Benito River Valley to the confluence with the Pajaro River, from the Highway 25 Bridge nine miles south of the town of Paicines to San Juan Bautista, plus the Tres Pinos Creek Valley from Paicines to the San Benito River. Zone 3 provides the funding base for operation of Hernandez and Paicines reservoirs and related percolation and

¹ These estimates will be revised with local implementation of the Sustainable Groundwater Management Act.

groundwater management activities. Zone 6 includes the six major delineated subbasins in the northern portion of the Gilroy-Hollister groundwater basin and provides the funding base for importation and distribution of CVP water and related groundwater management activities (Todd 2010, HDR 2008a).

SUSTAINABLE GROUNDWATER MANAGEMENT ACT (SGMA)

The 2014 Sustainable Groundwater Management Act (SGMA) continues to unfold through development of regulations by the Department of Water Resources (DWR) and clarifications to the law through Senate Bill 13 (effective January 1, 2016). In brief, SGMA requires sustainable groundwater management for designated medium- and high-priority groundwater basins, which includes the Gilroy-Hollister basin. Future SGMA activities may change the way the Gilroy-Hollister basin is managed, including the preparation of a Groundwater Sustainability Plan (GSP) expected in 2022. While SGMA does not affect this 2015 UWMP, it is expected to be a central part of the next UWMP due in 2020.

ANNUAL GROUNDWATER REPORT

Each water year, the District oversees the preparation of an Annual Groundwater Report that describes current groundwater conditions in the District and two zones of benefit: Zone 3 and Zone 6. The report documents water supply sources and use, groundwater levels and storage, and District management activities over the water year (October to September). Recommendations are provided with regard to the future water year imports, groundwater replenishment, groundwater pumping, and groundwater charges. This Annual Report is prepared at the request of the District to meet its information needs and to fulfill statutory reporting requirements (Todd 2015).

GROUNDWATER MANAGEMENT PLAN (GWMP)

The GWMP is a voluntary planning process for groundwater basin management. The GWMP process was established in 1992 by the State Legislature through Assembly Bill (AB) 3030, amended in 2002 by Senate Bill (SB) 1938 and codified in the Water Code. While the Water Code lays out specific requirements (used for State funding eligibility), a GWMP is voluntary. A completed GWMP must be sponsored and adopted by one or more eligible public agencies (such as the City or County), but is intended to be a collaborative process with local landowners, groundwater users, and other interested people. Such a plan describes groundwater conditions, addresses groundwater issues, identifies basin management objectives and actions to achieve objectives, and lays out an implementation plan for actions including funding sources, continued monitoring, and regular reporting.

In 1998, the first GWMP was prepared for the San Benito portion of the Gilroy-Hollister Valley Groundwater Basin as a collaborative effort among major water retailers and wholesalers of the basin including Aromas Water District, the cities of Hollister and San Juan Bautista, the District, Sunnyslope, and Tres Pinos County Water District. The GWMP was updated in 2003 and attached as an appendix to the 2010 UWMP.

WATER RIGHTS

The Gilroy-Hollister basin is not an adjudicated basin and groundwater entitlements or rights have not otherwise been defined. The long-term reliability of groundwater supply for the HUA is not likely to be predicated on water rights, but is likely to be defined by the overall state of the groundwater basin.

6.2.2 OVERDRAFT CONDITIONS

Water levels over time have varied in response to precipitation, groundwater pumping, and artificial recharge conditions. Water levels are estimated to have been at historical highs prior to 1913 before development of groundwater pumping (Kilburn 1972). In the drought conditions of the late 1970s, water levels in some areas had declined more than 150 feet from the estimated highs (Creegan & D'Angelo 1990). With the exception of a few areas of persistent water level lows, by 1998 groundwater levels had recovered close to the historical highs as a result of decreased pumping (following CVP importation), increased precipitation, and artificial recharge (Jones & Stokes 1999). During the recent drought that began in 2012, groundwater levels have declined over much of the basin, most notably in agricultural areas of the basin that rely on groundwater. These subbasins have now sustained four successive years of drought with limited CVP imports. During this time groundwater elevations have declined slightly or remained steady in areas of municipal pumping including Hollister East and Tres Pinos subbasins.

Groundwater elevation declines during drought do not constitute overdraft; nevertheless, the continued reduced supplies of imported water in tandem with increased groundwater demands are a warning of potential groundwater overdraft. It appears that sufficient storage remains in the basin to accommodate additional dry conditions with limited imported water availability. However, if drought conditions persist, avoidance of significant impacts will require delivery of alternative supplies to sensitive areas or more rigorous water demand management.

6.2.3 HISTORICAL PUMPING

Table 6-1 Hollister Retail and Table 6-1 Sunnyslope Retail show the historical pumping of Hollister and Sunnyslope, respectively. In general, municipal pumping in the area has decreased over time due to increased treatment and use of imported water and water conservation measures (**Figure 6-2**). Average municipal pumping in water years 1995 through 2003 (before Lessalt WTP came online) was 6,319 AFY. The average pumping in water years 2003 through 2015 (after Lessalt WTP) was 4,561 AFY, a 28 percent reduction in groundwater pumping.

The groundwater basin is a shared resource and other users (mainly agricultural) rely on groundwater supplies from the same subbasins. Total pumping in the three subbasins of the Hollister Urban Area has ranged from 8,345 AFY in 2011 to 16,614 AFY in 1993. Municipal pumping has ranged between 22 and 56 percent of total pumping in these basins. Locations of municipal wells in the HUA are shown on **Figure 6**.

6.3 SURFACE WATER

While local surface water is not directly used for water supply, it is used as a source of managed recharge to the groundwater aquifer. In most years, local surface water released from Hernandez and Paicines Reservoirs is percolated along the San Benito River and Tres Pinos Creek. Releases of local surface water have been limited typically to percolation upstream of the confluence of San Benito River and Tres Pinos Creek. This has helped maintain groundwater levels without causing shallow groundwater problems and competing for available storage space with the City of Hollister wastewater percolation ponds.

For the past two years (water years 2014 and 2015) both Paicines and Hernandez were dry for the entire year because of ongoing drought conditions; there were no releases from either reservoir.

6.4 STORM WATER

Currently, storm water is not diverted for direct beneficial use. However, some runoff that enters the City's storm water system is treated in the wastewater industrial plant and some stormwater runs off to the San Benito River. The collected storm water serves to increase the volume recharged in the disposal ponds and improves the discharge water quality.

6.5 WASTEWATER AND RECYCLED WATER OPPORTUNITIES

This section presents a summary of HUA wastewater collection, treatment, and disposal; current and projected recycled water use; programs to encourage recycled water use; and the HUA plan for optimizing recycled water use.

6.5.1 RECYCLED WATER COORDINATION

In 2004, the City of Hollister, the County, and the District executed a Memorandum of Understanding (MOU) forming a partnership to undertake the development of the Master Plan for the HUA. The MOU was amended in 2008 to include Sunnyslope. A new MOU with Hollister was completed in 2014 that allowed the District to receive recycled water from the Hollister wastewater treatment plant and make it available to agricultural customers in the area. These parties have undertaken a coordinated effort to plan water supply and wastewater strategies for the HUA. These strategies include the collection and treatment of wastewater as well as disposal and recycled use, as appropriate.

Planning for recycled water use has included the preparation of a Recycled Water Feasibility Study prepared by the District in 2005 (RMC 2005) and a subsequent Recycled Water Feasibility Study Update prepared jointly by the District and Hollister (HDR 2008b), the Long Term Waste Water Master Plans (LTWWMPs) prepared respectively by Hollister and Sunnyslope, and the Master Plan prepared jointly by Hollister, Sunnyslope, and the District (HDR 2008a). A Master Plan update is expected to be completed later in 2016.

Recycled water is currently being used for irrigation at one site within the HUA. While there are no detailed plans to increase recycled water use in the HUA, there are coordinated efforts to supply recycled water to areas outside of the HUA for agricultural irrigation (HDR 2008a, HDR 2008b). Currently, these agricultural customers rely on CVP imports and groundwater. If irrigation demands are met by recycled water, groundwater pumping in the area could be reduced, increasing available groundwater supplies for other parties, including the HUA retailers.

Although recycled water is currently available, and will become more widely available in the near term, neither increased non-potable use offsetting existing uses nor potable reuse opportunities are targeted for implementation within the HUA because of water quality concerns. A major goal of the 2008 MOU was to improve the quality of treated wastewater in order to provide recycled water with TDS concentrations between 500 and 700 mg/L. As efforts to improve potable water quality become more effective, recycled water quality will also improve and use in the area will increase.

6.5.2 WASTEWATER COLLECTION, TREATMENT AND DISCHARGE

As indicated on **Table 6-2 R**, five wastewater treatment plants treat the domestic, commercial, and industrial wastewater flows generated within the HUA (**Figure 6-6**). The existing wastewater facilities are owned by three separate agencies: Hollister, Sunnyslope, and San Benito County (Cielo Vista Estates Wastewater Treatment Plant). The facility descriptions are included below, organized by agency.

Current wastewater collection and treatment volumes for each of the treatment plants are presented on **Table 6-3 R**. The Hollister Water Reclamation Facility treated 2,061 AF of wastewater in 2015. While most of the treated wastewater was disposed in percolation ponds, 116 AFY of recycled water was used for irrigation.

CITY OF HOLLISTER WASTEWATER FACILITIES

Hollister owns and operates two waste water treatment plants (WWTPs); the domestic wastewater treatment plant/water reclamation facility (DWWTP/WRF) and the industrial wastewater treatment plant (IWWTP). The DWWTP/WRF, located on the western edge of the HUA (**Figure 6-6**), was built in 1979 to treat Hollister's domestic wastewater. The IWWTP (located west of downtown Hollister) treats seasonal industrial wastewater and storm water from the downtown area. The City of Hollister's collection system consists of gravity pipelines and force mains ranging from 4- to 36-inches in diameter.

The Hollister DWWTP/WRF began operating in March 1980, was renovated in 1987 to increase capacity, improved in 2002 and 2003 to improve treatment efficiency, and upgraded in 2009 to include the WRF and improve treatment to tertiary levels. Construction of distribution systems connecting to the City of Hollister Reclamation facility have begun. This system will increase the use of recycled water in the District. Recycled water will augment supply to agricultural users in the Hollister subbasin area. The DWWTP/WRF receives wastewater flow from all municipal and most industrial customers within Hollister City limits, including portions of the Sunnyslope service area. The system treats water to disinfected tertiary recycled water standards through the use of a Membrane Bioreactor (MBR).

The DWWTP/WRF is currently capable of treating up to 4 MGD and the current dry weather average flow is approximately 3 MGD. The DWWTP/WRF can be expanded to accommodate peak flows of 5 MGD through the installation of additional membranes, when required by additional development.

The Hollister IWWTP began operating in 1971 and is located on 78 acres less than a mile east of the DWWTP/WRF (**Figure 6-6**). The facility was constructed to treat effluent from local tomato canneries and storm water. Only one of the canneries, San Benito Foods, is currently in operation from mid-June through mid-October. The IWWTP is a conventional aerated pond treatment system that produces secondary-treated discharge. The capacity of the IWWTP has been estimated to be as high as 7.5 MGD; however, the current RWQCB permit limits flows to 3.5 MGD during the canning season and 1.72 MGD of storm water during the non-canning season (HDR 2008a). The estimated maximum cannery wastewater flow is 4.0 MGD, and the maximum sustained disposal capacity is 2.6 MGD. The Industrial WWTP receives approximately 0.2 million gallons of storm water flow per inch of rainfall (RMC 2005).

The secondary effluent from the IWWTP is discharged to evaporation and percolation ponds, which recharge the Hollister West and San Juan groundwater subbasins (RMC 2005).

SUNNYSLOPE COUNTY WATER DISTRICT WASTEWATER FACILITIES

The domestic wastewater treatment plant serving the Ridgemark Estates community is managed by Sunnyslope. A new wastewater treatment plant was constructed at the Ridgemark I facility (**Figure 6-6**). The new treatment plant is a sequential batch reactor facility with sludge handling facilities and four percolation ponds. The plant was completed in September 2013 and can treat 330,000 gallons per day. In 2015 the total treated wastewater was 178 acre feet or approximately 159,000 gallons per day. The Ridgemark II facility was converted to a pump station to pump the wastewater to the new treatment plant constructed at the Ridgemark I facility. At the Ridgemark II site, the treatment ponds and disposal ponds, are being dried out but will remain as excess facilities owned by Sunnyslope.

Sunnyslope has no plans to provide recycled water for irrigation in the next 5 years. In the past, Sunnyslope had planned to provide recycled water for Ridgemark Golf Course but this would require additional upgrades to its WWTP.

OTHER WASTEWATER FACILITIES

Wastewater treatment within the HUA by parties other than the two municipal water purveyors is limited to the Cielo Vista Estates, operated by San Benito County, and private residential septic systems.

Cielo Vista Estates is a residential development within Sunnyslope's service area and includes approximately 75 single-family homes located at the intersection of Airline Highway and Fairview Road. Wastewater from the community is treated by a Sequencing Batch Reactor (SBR) system operated by San Benito County. Secondary effluent from the treatment system is infiltrated to the groundwater basin via a leach line system. The Cielo Vista development is complete and new connections to the wastewater system are not anticipated (Schaaf & Wheeler 1999). Some private residences within the HUA are still serviced by individual septic systems. No estimate has been made of the quantity of wastewater generated from these small systems.

6.5.3 RECYCLED WATER SYSTEM

The wastewater treatment facilities within the HUA utilize a number of treatment methods, which result in varying effluent quality, as described above. Current requirements for recycled water use are administered by Title 22 of the California Code of Regulations, referred to hereafter as Title 22. The Hollister DWWTP/WRF has the capacity to meet the requirements for disinfected tertiary recycled water as defined by Title 22. The remaining wastewater treatment facilities produce effluent that meets the Title 22 requirements for undisinfected secondary recycled water. However, the effluent streams from all of the treatment facilities have high levels of TDS, which may preclude local reuse on orchards and vineyards or non-food bearing trees. The parties to the MOU have committed to reducing these high concentrations by reducing the TDS of supplied water as part of the Master Plan (HDR 2008a). The Hollister DWWTP/WRF currently treats all wastewater flows to tertiary standards, but only disinfects what is used offsite for landscape irrigation.

As previously noted, the remaining wastewater treatment facilities (the Ridgemark WWTP and Cielo Vista Estates) produce undisinfected secondary effluent, which is disposed of through evaporation and/or percolation.

There are no plans to upgrade or expand the Cielo Vista Estates wastewater treatment system.

The current and anticipated future quantities of wastewater treated to recycled water standards are presented in **Table 6-4 R.** Recycled water will be available from only Hollister's domestic wastewater treatment plant/water reclamation facility (DWWTP/WRF). There are no plans to provided recycled water from other facilities.

6.5.4 RECYCLED WATER BENEFICIAL USES

CURRENT USES

Offsite reuse of recycled water from the DWWTP/WRF takes place at Riverside Park (formerly known as the Brigantino Site). Irrigation at these sites began in a limited capacity in 2009 and use increased in 2010 as the projects neared completion. In 2015, 116 AF of recycled water was delivered to Riverside Park, while no recycled water was delivered to the airport site. The remaining treated wastewater from the DWWTP/WRF is currently disposed of by evaporation and percolation. The DWWTP/WRF will increase the quantity of disinfected tertiary recycled water that it produces as demand for recycled water increases, in accordance with the Master Plan.

PLANNED VERSUS ACTUAL USE OF RECYCLED WATER

In the 2010 UWMP, recycled water use in the HUA was projected to be 1,091 AFY by 2015. The actual recycled water use in 2015 was 116 AF. In **Table 6-5 R**, The projected recycled water use from the 2010 UWMP is compared to the 2015 actual use. The volume of landscape irrigation is significantly lower and the projected use of golf course irrigation did not occur. The recycled water distribution system is still under construction and the water quality targets for the wastewater have not been met. In addition, Sunnyslope has not pursued recycled water as a supply source and thus did not provide recycled water to Ridgemark golf course as planned.

FUTURE USES

Current plans for use of HUA recycled water focus primarily on agricultural irrigation of high value, qualitysensitive crops. This agricultural use is currently outside the service areas of Hollister and Sunnyslope. Planning for recycled water use is an ongoing and iterative process that has been carefully considered by the parties to the MOU. Any agricultural recycled water use will depend on the ability of the MOU parties to meet their TDS goals of 500 to 700 mg/L. The MOU established 2015 as the target date for meeting these water quality goals. Plans to meet these goals are described in the Master Plan (HDR 2008a).

Currently, these agricultural customers rely on CVP imports and groundwater pumping. If irrigation demands are met by recycled water, groundwater pumping in the area could be reduced, increasing the available groundwater supply for the HUA retailers.

6.5.5 ACTIONS TO ENCOURAGE AND OPTIMIZE FUTURE RECYCLED WATER USE

There are no current plans to increase recycled water use in the HUA. Accordingly, no implementation strategies are listed on Table 6-6 R and Table 6-7 R. The District plans to distribute the recycled water produced by the City's WWTP for agricultural users outside the HUA. Sunnyslope may pursue recycled water in the future but has no plans in place.

6.6 DESALINATION WATER OPPORTUNITIES

The 2008 Master Plan PEIR examined the demineralization of urban wells as a potential project to increase water supply reliability and improve water quality. This improved water quality would in turn improve wastewater and recycled water quality. Groundwater pumped from local wells would be treated using reverse osmosis (R/O). The Master Plan developed a phased approach for implementation. The phasing would result in 3 mgd (3,400 AFY) of demineralization capacity by 2015, and a total of 5 mgd (5,600 AFY) by 2019. This schedule represents the earliest implementation of phased demineralization of urban wells (AECOM 2011). Facilities may include a mix of existing and new wells, with either wellhead or centralized treatment. The timing and capacity of demineralization facilities are being considered but there are no plans to begin a demineralization project at this time.

The District, Hollister, and Sunnyslope are not considering desalination from ocean water or brackish surface water at this time because of a lack of such water sources in the region.

6.7 EXCHANGES OR TRANSFERS

Through its CVP contract, the District has the capability to engage in transfer or exchange with other CVP customers.

6.7.1 EXCHANGES AND TRANSFERS

The District is the CVP wholesaler to many agricultural and M&I users in addition to Hollister and Sunnyslope. During the next water shortage, Hollister and Sunnyslope may be eligible to purchase additional water that the District has obtained from its water transfers with other CVP customers, purchases on the spot market, and water banked at the Semitropic water bank. The amount of available water would be variable, based on the District's overall water needs. Currently, the District has 4,500 AFY stored with Semitropic.

6.7.3 EMERGENCY INTERTIES

Hollister and Sunnyslope share a connected water system and in an emergency, water can flow from one retailer to the other as needed.

6.8 FUTURE WATER PROJECTS

NORTH COUNTY GROUNDWATER

The 2008 Master Plan identified north county groundwater subbasins as sources of additional long-term supply. Initial investigations indicated that north county pumping could provide additional supply to the Lessalt WTP and help alleviate local high groundwater conditions. In addition, banking groundwater in the north could provide opportunities for percolation and storage of relatively high quality imported supplies when available, and these supplies would then be available to the HUA agencies during dry years. The north county groundwater recharge project would include a combination of facilities to pump and recharge water, plus a network of monitoring wells. Water from the groundwater bank would be pumped into the Hollister Conduit for conveyance to the HUA. Initial investigations indicated that the north county groundwater recharge project could produce 1,400 to 2,000 AFY of groundwater with TDS concentrations less than 500 mg/L.

NEW MUNICIPAL WELLS

In light of water demand projections and water quality concerns for existing wells, Hollister and Sunnyslope are considering new municipal wells. No specific sites or plans for new wells have been identified, but new wells are being considered as part of the current Master Plan process.

6.9 SUMMARY OF EXISTING AND PLANNED SOURCES OF WATER

The Hollister Urban Area currently relies on imported water from the CVP, groundwater, and a small volume of recycled water for limited landscape irrigation. **Tables 6-8 Hollister Retail and 6-8 Sunnyslope Retail** show the current water supply by source for 2015, for Hollister and Sunnyslope respectively. **Figure 6-2** shows the historical water supply by source for the HUA from 1995 through 2015.

Table 6-9 R documents future CVP supply availability based on projected combined capacity of the existing and new surface water treatment plants. By the end of 2017, the combined average annual imported water treatment capacity in the HUA is projected to be 4.25 MGD, which is equivalent to 4,760 AFY). These increased imported water treatment capacities come from the recently completed upgrades to the Lessalt WTP and the currently under construction West Hills WTP, which is scheduled to be completed in 2017. The upgraded Lessalt WTP now has a treatment capacity of 2MGD, or 2,240 AFY, and the West Hills WTP is designed to treat an additional 2.25 MGD, or 2,520 AFY. The West Hills WTP design includes the potential for future expansion to treat up to 4.5 MGD, which is an average annual volume of 5,040 AFY. If these expansions to the yet-to-be completed West Hills WTP are implemented, the total imported water treatment capacity in the HUA would be 6.5 MGD, which is 7,280 AFY. Based on the projected growth and limits on groundwater use, the West Hills WTP should be expanded at least partially to an average annual capacity of 3 MGD by 2025, and full expansion may be required by 2035 to achieve the preferred supply blend of 65 percent CVP and 35 percent groundwater.

Treated water entering Hollister's and Sunnyslope's water systems is metered and tracked. The goal is to deliver 50 percent of CVP imports to each retailer; however it is estimated the most of the treated water flows into the Sunnyslope system. During drought conditions, the CVP allocation could be reduced based on the Water Shortage Policy. This is discussed further in the Water Reliability section.

Table 6-9 R also shows the projected future groundwater supply for Hollister and Sunnyslope respectively. As discussed in the groundwater section, the HUA overlays three groundwater subbasins. These subbasins have a sustainable yield of roughly 16,000 AFY. Of this yield, 9,263 AFY would be available to Hollister and Sunnyslope; the remaining yield is available for agricultural users, small purveyors, and domestic wells. In addition, the north county groundwater bank and recycled water delivered to agricultural customers in the area could make additional groundwater available. In 2035, the HUA plans to use groundwater as a supplemental supply during normal, single dry, and multiple dry years. The projected volume of groundwater pumping required to meet normal, single dry, and multiple dry year demand in 2035 is within the sustainable yield of the subbasins that the HUA is within, as discussed in detail above.

It is expected that CVP imports will continue to be the most desirable water source for the HUA in the future and that additional demand will be met with local groundwater blended with imported supplies. The preferred distribution is two thirds imported water and one third groundwater. However, this distribution could be relaxed to half groundwater and half imported water in order to meet regulatory water quality thresholds.

Table 6-9 R shows the projected recycled water use in Hollister; no recycled water use is expected in Sunnyslope's service area. The projected recycled water for the retailers in the HUA from 2010 to 2030 is expected to stay at 116 AFY as most of the recycled water will be delivered to agricultural customers, as shown in **Table 6-7 R**.

To meet future demand, the District, Hollister and Sunnyslope plan to rely on a portfolio of supplies. By utilizing different types of supply, the HUA agencies will reduce the impact of water shortage from each source.

6.10 CLIMATE CHANGE IMPACTS TO SUPPLY

Climate change is likely to affect water supply as well as demand (see Section 4.6). The climate change vulnerability assessment performed for the HUA is included as **Appendix E**. The most significant impact to supply will be the availability of imported water. Snowpack is expected to decrease as the climate warms and CVP allocations will likely decrease and become more variable as a result. In addition, CVP relies in part on the Delta, which is a climate-sensitive habitat where environmental requirements may also reduce CVP allocation.

Table 6-1 Hollister Retail: Groundwater Volume Pumped								
		Supplier does not pump groundwater. The supplier will not complete the table below.						
Groundwater Type Drop Down List May use each category multiple times	bp Down List Location or Basin Name		2012	2013	2014	2015		
Add additional rows as neede	d							
Alluvial Basin	Gilroy Hollister	1,601	2,004	2,953	2,754	1,949		
	TOTAL	1,601	2,004	2,953	2,754	1,949		
NOTES: Hollister PWSS (20	11, 2013, 2014,2015), Internal data 2	012						

Table 6-1 Sunnyslope Retail: Groundwater Volume Pumped								
	Supplier does not pump groundwater. The supplier will not complete the table below.							
Groundwater Type Drop Down List May use each category multiple times	Location or Basin Name	2011	2012	2013	2014	2015		
Add additional rows as needed	1							
Alluvial Basin	Gilroy Hollister	2,353	2,121	1,719	2,096	1,278		
	TOTAL	2,353	2,121	1,719	2,096	1,278		
NOTES: Sunnyslope PWSS								

Table 6-1 Wholesale: G	Table 6-1 Wholesale: Groundwater Volume Pumped								
	Supplier does not pump groundwater. The supplier will not complete the table below.								
Groundwater Type <i>Drop Down List</i> May use each category multiple times	Location or Basin Name	2011	2012	2013	2014	2015			
	TOTAL	0	0	0	0	0			
NOTES:									

Fable 6-2 Retail: Wastewater Collected Within Service Area in 2015										
	There is no wastewate	r collection system. T	he supplier will not compl	ete the table below.						
	Percentage of 2015 se	rvice area covered by	wastewater collection syst	em (optional)						
	Percentage of 2015 service area population covered by wastewater collection system (optional)									
Wastey	vater Collection			Recipient of Collected Waste	ewater					
Name of Wastewater Collection Agency	Wastewater Volume Metered or Estimated? Drop Down List	Volume of Wastewater Collected in 2015	Name of Wastewater Treatment Agency Receiving Collected Wastewater	Treatment Plant Name	Is WWTP Located Within UWMP Area? Drop Down List	Is WWTP Operation Contracted to a Third Party? (optional) Drop Down List				
Add additional rows as needed			2	•						
City of Hollister	Metered	2,468	City of Hollister	Hollister Water Reclamation Facility	Yes	No				
City of Hollister	Metered	21	City of Hollister	Industrial Wastewater Treatment Facility	Yes	No				
Sunnyslope County Water District	Metered	178	Sunnyslope County Water District	Ridgemark I	Yes	No				
Sunnyslope County Water District	Metered	0	Sunnyslope County Water District	Ridgemark II	Yes	No				
San Benito County	Estimated	18	San Benito County	Cielo Vista Estates Wastewater Treatment	Yes	No				
Total Wastewater Collected from	Service Area in 2015:	2,664								
NOTES:			-							

		o wastewater is treated or disposed of within the UWMP service area. ne supplier will not complete the table below.								
							2015 volumes			
Wastewater Treatment Plant Name	Discharge Location Name or Identifier	Discharge Location Description	Wastewater Discharge ID Number (optional)	Method of Disposal Drop down list	Does This Plant Treat Wastewater Generated Outside the Service Area?	Treatment Level Drop down list	Wastewater Treated	Discharged Treated Wastewater	Recycled Within Service Area	Recycled Outside of Service Are
Add additional rows as needed										
Hollister Water Reclamation Facility	2690 San Juan Hollister Road			Percolation ponds	No	Tertiary	2,061	2,061	116	0
Industrial Wastewater Treatment Facility	1335 South St. Hollister CA		WDR-3 350100002		No	Secondary, Undisinfected	21	16	0	0
Ridgemark I			R3-2004- 0065 3 351000001	Percolation ponds	No	Secondary, Undisinfected	178	178	0	0
Ridgemark II			R3-2004- 0065 3 351000001	Percolation ponds	No	Secondary, Undisinfected	0	0	0	0
Cielo Vista Estates Wastewate Treatment Plant	r			Percolation ponds	No	Secondary, Undisinfected	18	18	0	0
Cielo Vista Estates Wastewate	r			Percolation		Secondary,	18		-	18 0

Fable 6-3 Wholesale: Wastewater Treatment and Discharge Within Service Area in 2015										
7	Wholesale supplier does not provide supplemental treatment to recycled water it distributes. The supplier will not complete the table below.									
								2015 volu	umes	
Wastewater Treatment Plant Name	Discharge Location Name or Identifier	Discharge Location Description	Wastewater Discharge ID Number <i>(optional)</i>	Method of Disposal Drop down list	Does This Plant Treat Wastewater Generated Outside the Service Area?	Treatment Level	Wastewater Treated	Discharged Treated Wastewater	Recycled Within Service Area	Recycled Outside of Service Area
Add additional ro	ws as needed									
						Total	0	0	0	0
NOTES:										

Table 6-4a Retail: Current and Projected Recycled Water Direct Beneficial Uses Within Service Area								
	Recycled water is not used and is not planned for use within the service area of the supplier. The supplier will not complete the table below.							
Name of Agency Producing (Treating) the Recycle	d Water:							
Name of Agency Operating the Recycled Water D	istribution System:							
Supplemental Water Added in 2015								
Source of 2015 Supplemental Water								
Beneficial Use Type These are the only Use Types that will be recognized by the DWR online submittal tool	General Description of 2015 Uses	Level of Treatment Drop down list	2015	2020	2025	2030	2035	2040 (opt)
Agricultural irrigation								
Landscape irrigation (excludes golf courses)	Park Irrigation	Tertiary	116	116	116	116	116	
Golf course irrigation								
Commercial use								
Industrial use								
Geothermal and other energy production								
Seawater intrusion barrier								
Recreational impoundment								
Wetlands or wildlife habitat								
Groundwater recharge (IPR)								
Surface water augmentation (IPR)								
Direct potable reuse								
Other Type of Use								
		Total:	116	116	116	116	116	0
IPR - Indirect Potable Reuse								
NOTES:								

Table 6-4 Wholesale: Current and Projected Retailers Provided Recycled Water Within Service Area									
V	· · ·	cycled water is not directly treated or distributed by the supplier. oplier will not complete the table below.							
Name of Receiving Supplier or Direct Use by Wholesaler	Level of Treatment Drop down list	2015	2020	2025	2030	2035	2040 (opt)		
Add additional rows as needed	Add additional rows as needed								
	Total	0	0	0	0	0	0		
NOTES: Recycled water is not planned	d to be supplied by SBWD to urban	customers	•			•			

Table 6-5 Retail: 2010 UW	/MP Recycled Water	Use Projection Compared t	o 2015 Actual				
	Recycled water was not used in 2010 nor projected for use in 2015. The supplier will not complete the table below.						
Use Typ These are the only Use Types that WUEdata online su	will be recognized by the	2010 Projection for 2015	2015 actual use				
Agricultural irrigation		0	0				
Landscape irrigation (exclude	s golf courses)	960	116				
Golf course irrigation		131	0				
Commercial use							
Industrial use							
Geothermal and other energy	y production						
Seawater intrusion barrier							
Recreational impoundment							
Wetlands or wildlife habitat							
Groundwater recharge (IPR)							
Surface water augmentation	(IPR)						
Direct potable reuse							
Other	Required for this use						
	Total	1,091	116				
NOTES:							

Table 6-5 Wholesale: 2010 UWMP Recycled Water Use Projection Compared to 2015 Actual								
	Recycled water was not used or distributed by the supplier in 2010, nor projected for use or distribution in 2015. The wholesale supplier will not complete the table below.							
Name of Receiving Supplier or Direct Use by Wholesaler	2010 Projection for 2015	2015 actual use						
Add additional rows as needed								
Total	0	0						
NOTES:								

Table 6-6 Retail: Methods to Expand Future Recycled Water Use								
		Supplier does not plan to expand recycled water use in the future. Supplier will not complete he table below but will provide narrative explanation.						
	Provide page location of narrative in UWMP							
Name of Action	Description	Planned Implementation Year	Expected Increase in Recycled Water Use					
Add additional rows as nee	ded							
Total 0								
NOTES:								

Table 6-7 Retail: Exp	ected Future Wate	r Supply Projects	or Programs					
1	No expected future water supply projects or programs that provide a quantifiable increase to the agency's water supply. Supplier will not complete the table below.							
	ome or all of the supplier's future water supply projects or programs are not compatible with this table and are described n a narrative format.							
	Provide page location of narrative in the UWMP							
Name of Future Projects or Programs	Joint Project with other agencies?		Description (if needed)	Planned Implementation Year	Planned for Use in Year Type Drop Down List User may select more	Expected Increase in Water Supply to Agency		
	Drop Down List (y/n)	If Yes, Agency Name			than one.	This may be a range		
Add additional rows as n	eeded			- -				
NOTES:								

Table 6-7 Wholesale	: Expecte	ed Future Water S	upply Projects or Progra	ms						
	No expected future water supply projects or programs that provide a quantifiable increase to the agency's water supply. Supplier will not complete the table below.									
		Some or all of the supplier's future water supply projects or programs are not compatible with this table and are described in a narrative format.								
	Provide p	rovide page location of narrative in the UWMP								
Name of Future		roject with other agencies?	Description	Planned Implementation	Planned for Use in Year Type Drop Down list	Expected Increase in				
Projects or Programs	Drop Down Menu	lf Yes, Agency Name	(if needed)	Year	User may select more than one.	Water Supply to Agency				
Add additional rows as ne	eeded			•	•					
NOTES:										


Water Supply		2015				
Drop down list May use each category multiple times. These are the only water supply categories that will be recognized by the WUEdata online submittal tool	Additional Detail on Water Supply	Actual Volume	Water Quality Drop Down List	Total Right or Safe Yield <i>(optional)</i>		
Add additional rows as needed						
Purchased or Imported Water	CVP	429	Drinking Water			
Purchased or Imported Water	Pumped by Sunnyslope	589	Drinking Water			
Groundwater	Pumped by Hollister	1,892	Drinking Water			
Recycled Water		116	Recycled Water			
	Total	3,026		0		


Water Supply		2015			
Drop down list May use each category multiple times. These are the only water supply categories that will be recognized by the WUEdata online submittal tool	Additional Detail on Water Supply	Actual Volume	Water Quality Drop Down List	Total Right o Safe Yield <i>(optional)</i>	
Add additional rows as needed					
Purchased or Imported Water	CVP	1,285	Drinking Water		
Groundwater	Pumped by Sunnyslope	688	Drinking Water		
Groundwater	Pumped by Hollister	57	Drinking Water		


Table 6-8 Wholesale: Water Supplies — Actual							
Water Supply		2015					
Drop down list May use each category multiple times. These are the only water supply categories that will be recognized by the WUEdata online submittal tool	Additional Detail on Water Supply	Actual Volume	Water Quality Drop Down List	Total Right or Safe Yield <i>(optional)</i>			
Add additional rows as needed							
Purchased or Imported Water		1,714	Raw Water				
	Total	1,714		0			
NOTES: The value shows actual deliver	ies and does not include lo	sses in storage	system	•			


Water Supply		Projected Water Supply Report To the Extent Practicable							
Drop down list May use each category multiple times. These are the only water supply categories that will be recognized by the WUEdata online submittal tool	Additional Detail on Water Supply			2025		2030		2035	
		Reasonably Available Volume	Total Right or Safe Yield <i>(optional)</i>	Reasonably Available Volume	Total Right or Safe Yield <i>(optional)</i>	Reasonably Available Volume	Total Right or Safe Yield <i>(optional)</i>	Reasonably Available Volume	Total Right or Safe Yield (optional)
Add additional rows as needed									
Purchased or Imported Water		7,425	8,250	7,425	8,250	7,425	8,250	7,425	8,250
Groundwater		3,998	9,263	3,998	9,263	3,998	9,263	3,998	9,263
Recycled Water		116	116	116	116	116	116	116	116
	Total	11,539	17,629	11,539	17,629	11,539	17,629	11,539	17,629
NOTES: CVP imported water will	be reduced under	drought condi	-	cussed in Secti cent system los		nably available	e volume in a no	ormal year is tl	he full contract


Water Supply	Additional Detail on Water Supply	Projected Water Supply Report To the Extent Practicable							
		2020		2025		2030		2035	
Drop down list May use each category multiple times. These are the only water supply categories that will be recognized by the WUEdata online submittal tool		Reasonably Available Volume	Total Right or Safe Yield <i>(optional)</i>	Reasonably Available Volume	Total Right or Safe Yield <i>(optional)</i>	Reasonably Available Volume	Total Right or Safe Yield (optional)	Reasonably Available Volume	Total Right or Safe Yield <i>(optional)</i>
			Add additio	onal rows as need	ded				
Purchased or Imported Water	CVP	8,250	8,250	8,250	8,250	8,250	8,250	8,250	8,250
Other									
	Total	8,250	8,250	8,250	8,250	8,250	8,250	8,250	8,250














7. WATER SUPPLY RELIABILITY ASSESSMENT

7.1 CONSTRAINTS ON WATER SOURCES

The HUA has multiple water supply sources—CVP, groundwater, and recycled water—that increase overall water supply reliability. However, many factors could result in inconsistency of supply and shortages. These factors may include legal, environmental, water quality, and/or climatic considerations, as discussed below. Major factors affecting surface water supply from the CVP include environmental issues and climatic variation. The groundwater basin has a recent history of consistent supply, but may be affected by climatic variations and poor water quality. Increased future uses of recycled water may be affected by the water quality of the source and legal/environmental constraints on use.

Hollister, Sunnyslope, and the District are addressing these potential constraints on water supply through development of a portfolio of supplies, improvement of facilities (e.g., treatment plant expansion and groundwater banking), and through demand management as summarized in the Water Shortage Contingency Plan (Section 8).

The current Pajaro River Watershed Integrated Regional Water Management Plan (IRWMP), completed in 2006, does not address regional climate change. An expanded climate change section is expected in the next update of the IRWMP. Water supply reliability in general is a goal for the plan; planned water supply projects would increase reliability through groundwater banking and increase supplies such as recycled water to reduce dependence on CVP and groundwater for agricultural users (PRWIRMP 2006).

7.1.1 LEGAL

The Hollister basin has not been adjudicated, so specific groundwater rights have not been quantified. Although the possibility exists that adjudication proceedings could be initiated, the success of local groundwater management activities with stakeholder involvement reduces the likelihood that such lengthy and costly legal action will occur.

Imported water is secured for the future through contracts that include provisions for reductions in water supply. Such interruption of imported water would induce additional groundwater pumping that, depending on the magnitude and persistence of the interruption, could reduce groundwater storage and affect the reliability of the groundwater supply.

The collection, treatment, and disposal of wastewater and recycled water uses are governed by the MOUs between the County, the District, Hollister, and Sunnyslope, and regulatory requirements. The local parties have undertaken a coordinated effort to plan water supply and wastewater strategies for the HUA.

7.1.2 ENVIRONMENTAL

The most likely environmental factors affecting HUA water supplies would be reductions to CVP imports due to concerns over endangered species in the Delta. The potential for use of recycled water may also be limited by environmental concerns. Any and all potential recycled water uses will need to be in compliance with policies set by the RWQCB and other agencies. Other environmental concerns could

include substantially increased pumping from other groundwater basin users, resulting in basin overdraft; SGMA defines overdraft as involving undesirable impacts including chronic lowering of groundwater levels, reduction of groundwater storage, seawater intrusion, degraded water quality, land subsidence, and surface water depletions with adverse impacts on beneficial uses.

7.1.3 DELTA PUMPING RESTRICTIONS

The Sacramento-San Joaquin Delta is a key component to the state's water system (DWR 2009b), as much of the water that feeds the State Water Project and Central Valley Project flows through the Delta. The Delta is also home to a sensitive ecosystem with several federally listed threatened species. In 2007, pumping from the Delta for water supply was limited by a federal court to protect the Delta Smelt, a federally listed threatened species. Further restrictions have been imposed to protect other fish species, including the Longfin Smelt and Chinook salmon. Further appeals have upheld these restrictions (Los Angeles Times 2014).

These pumping limits directly affect the amount of CVP imported water available to the HUA and other San Benito County users.

7.1.4 WATER QUALITY

Water samples from the municipal wells are monitored for various water quality constituents. If these constituents are detected at concentrations higher than the drinking water standard or maximum concentration limit (MCL) set by the U.S. Environmental Protection Agency (USEPA) or the DDW, the well may be taken offline. In the past, municipal wells have been taken offline as a result of high nitrate concentrations. Although high nitrate concentrations can be treated, removal of wells from the system and fitting for treatment technology may temporarily impact the system and affect the cost of supply.

As discussed in the supply section, local groundwater is highly mineralized and the relative poor water quality may limit some uses of groundwater. The HUA agencies are taking steps to improve water quality of the groundwater supply. The new CrVI thresholds will require Hollister to blend groundwater with imported water to meet water quality goals. The blending requirement may limit the volumes of groundwater that can be used if insufficient imported water is available for blending.

As with groundwater, the water quality of recycled water (also characterized by high TDS concentrations) may also limit its potential uses. The 2008 Master Plan (HDR 2008a) includes procedures by which the quality of recycled water can be improved over time. The changing quality of recycled water was taken into consideration in the projection of future use.

7.1.5 CLIMATIC

The climatic events most likely to affect water supply are droughts, which are addressed in other sections of this report by examining historical droughts and considering their impact on current and future water supply and demand. However, future climate change—and specifically global warming—brings additional uncertainty to water supply management. It is notable that five of the six extreme drought years have occurred within the past 26 years, suggesting greater climatic variability in recent decades.

DROUGHT

Recorded droughts have been sufficiently intense and prolonged to temporarily affect groundwater levels in the basin, but have not affected the long-term consistency of supply. However, paleoclimatic data indicate that extreme prolonged droughts have occurred in prehistoric California and current climate research indicates that extreme drought may occur more frequently with climate change. This is discussed in more detail below.

As reported in past UWMPs, basic review of groundwater hydrographs for wells in the basin suggested that one or even three consecutive extreme dry years did not have a discernable impact on groundwater levels. However, as experienced in the current drought, CVP allocations may be significantly reduced during these periods. Future water supply will need to be managed as a portfolio to take advantage of local storage and supplies that are more robust in drought times.

GLOBAL CLIMATE CHANGE

While global climate change is recognized as a serious threat to water supply, potential local impacts are not fully understood. According to the Intergovernmental Panel on Climate Change, global warming could significantly alter California's hydrologic cycles and water supply. These impacts could include decreased Sierra snowpack, increased temperatures, more severe droughts, sea level rise, and increased floods. Climate models indicate that precipitation as rainfall is expected to increase as snowfall decreases over the Sierra Nevada and Cascade mountain ranges. By the end of this century, the Sierra snowpack is projected to be 48 to 65 percent less than the historical average (DWR 2016c). This reduction would directly impact the volume of imported water available for all the District CVP customers, including Hollister and Sunnyslope. Sierra snowmelt feeds rivers that flow to the Delta, the source of CVP imported water. The Delta is also at risk from the predicted increases in climate variability associated with climate change. More severe flooding and rising sea levels threaten the waterways that serve as a vital link in the CVP system within the Delta.

Climate change may also increase regional temperatures and cause more variable weather patterns. The minimum daily temperature in California has increased over one degree Fahrenheit and continues to rise (DWR 2009). In addition to decreasing snowpack, these increased temperatures may also increase water demand. Higher temperatures could increase water demand throughout the state through increased agricultural irrigation and in the HUA through increased outdoor residential and commercial irrigation. Changing weather patterns could cause more severe flooding and longer droughts.

The State of California and DWR in particular are working to reduce the effects of climate change through reduction of emissions and strategies to address the impacts of climate change. The State of California plans to reduce its impact on climate change through recent legislation such as AB 32, which called for a reduction in greenhouse gas emissions. DWR voluntarily joined the California Climate Action Registry, a tool to track and report emissions. DWR is also working to add more clean and renewable energy resources to its power portfolio and to reduce its carbon footprint. To address the impacts of climate change, DWR has included an extensive discussion of the topic in the state's Water Plan Update 2014. In addition, DWR has developed strategies to address impacts including increased monitoring of climatologic

and water resource conditions, reduction of greenhouse gas emissions from water management activities, study of the combined effects of increased atmospheric carbon dioxide and increased temperature (to predict future water demand), and adaptation of statewide water management systems by incorporating more flexibility. In 2012, DWR adopted phase 1 of its Climate Action Plan, a Department-wide Greenhouse Gas Emissions Reduction Plan. Phase 2, guidance for consistent incorporation and alignment of analysis for climate change impacts, is expected in 2016 (DWR 2016b).

7.1.6 CATASTROPHIC WATER SHORTAGE

The Urban Water Management Planning Act requires that water purveyors describe actions to be taken in the event of catastrophic water supply interruption, such as earthquake and regional power outage. Regional power outages represent a potential interruption in water supply.

REGIONAL POWER OUTAGE

Heat waves have resulted in power outages in the HUA that disrupt water supply. To ensure that the water system is capable of providing an adequate level of service during power outages, Hollister Well Nos. 4 and 5 are equipped with standby power. Hollister also has portable generators to supply emergency power for the other active wells (HDR 2008a). Sunnyslope has portable generators at all potable well sites, wastewater pump stations, and their wastewater treatment plant. A backup generator has not been installed at the Lessalt WTP because the size of the generator that would be required to run the plant and pump stations is cost prohibitive. However, the treatment plant has been wired with a quick-connect electrical connection so that a rental generator could easily be brought in and quickly connected to power the plant if needed.

NATURAL DISASTERS

Disasters such as earthquakes could disrupt water delivery infrastructure. The wholesalers that provide imported water to the HUA are taking steps to ensure water supply reliability. USBR is responsible for about 370 storage dams and for dikes that form a significant part of the water resources infrastructure for the western United States. As the owner of these facilities, USBR is committed to providing the public and the environment with adequate protection from the risks inherent to collecting and storing large volumes of water for later distribution and/or release (USBR 2016). The District routinely monitors the conditions of Hernandez and Paicines dams used for both water supply and flood prevention.

Recognizing the proximity of the San Andreas and Calaveras faults, the City of Hollister, San Benito County, and the District have a joint water shortage emergency response plan included in **Appendix G**.

7.2 RELIABILITY BY TYPE OF YEAR

The California Urban Water Management Planning Act requires that each water supplier provide an assessment of the reliability of its water supply during normal, dry, and multiple dry years. This section considers the impact on water supplies during a single extreme dry year and a multiple dry year period. In addition, a catastrophic water shortage could also occur, for example, as a result of earthquake damage,

regional power outage, or water quality emergency. This section presents the response to potential water shortages for Hollister, Sunnyslope, and the District, including catastrophic water supply interruption and drought. **Table 7-1 R** shows the base years selected to define average, single-dry year, and multiple-dry year period.

7.2.1 TYPES OF YEARS

AVERAGE CONDITIONS

Rainfall data have been collected monthly in the Hollister area since 1875. Precipitation and other weather data have been collected from a California Irrigation Management Information System (CIMIS) station located by the District office in Hollister since June 1994 (Station #126). The average rainfall from 1875-2015 was 12.8 inches in Hollister (**Figure 3-3**).

Rainfall in 1986, 1992, 2003, 2004, and 2011 was about average. For the purposes of this UWMP, 2011 is selected as the typical average year because the most recent year is representative of current basin operations.

SINGLE-DRY YEAR

DWR guidelines suggest that a single dry year should be the lowest supply available to the retailers, in addition to lower precipitation. Supply has been reduced due to reductions in the CVP allocations for both agricultural and M&I (municipal and industrial) uses. A decrease in agriculture allocations, while not affecting the retailers directly, indirectly affects supply as groundwater pumping from other uses in the basin generally increases. This increased groundwater use could affect groundwater availability in the long term.

In water year 2014, the year selected as a single dry year, local precipitation was 5.4 inches, 41 percent of normal and the lowest annual precipitation recorded at the San Benito CIMIS station. In addition, CVP allocations for agricultural and M&I users were 0 percent and 50 percent, respectively, the second lowest allocations since imported water began over twenty five years ago. In addition. The low allocations and low precipitation resulted in significant groundwater level drawdown. Accordingly, 2014 is representative of a severe single-dry year.

MULTIPLE - DRY YEAR PERIOD

DWR guidelines suggest that a multiple dry year period should represent the lowest average water supply availability for a consecutive multiple year period (three years or more). As with the single dry year, CVP allocations significantly affect available supply.

In water years 2013 through 2015, CVP allocations for both agricultural and M&I users were the lowest on record. For example, the M&I allocation was 70, 50, and 25 percent of historical use for years 2013, 2014, and 2015, respectively. In addition, average annual precipitation for the three years was 7.4 inches, or 58 percent of normal. While other three-year periods had lower rainfall, the low rainfall during this

period (combined with the low CVP allocation) significantly decreased the retailers' available water supply.

7.2.2 SOURCES FOR WATER DATA

Information regarding local climate conditions is available from the CIMIS station located in Hollister, while imported CVP allocations are available from the USBR. Groundwater availability and storage change is reported in the District's Annual Groundwater Reports (Todd 2015).

7.2.3 AGENCIES WITH MULTIPLE SOURCES OF WATER

While the HUA agencies have multiple water sources, the sources are interdependent. For example, lower CVP allocation results in higher groundwater use which could limit supply in the long term. The HUA region chooses to provide aggregated information for all sources, rather than examining each water source separately.

7.3 SUPPLY AND DEMAND ASSESSMENT

7.3.1 IMPACTS TO WATER SUPPY

The HUA relies primarily on groundwater and CVP imported water, with some use of recycled water. Both groundwater and CVP supplies are impacted during dry years.

Table 7-1 W shows the supply reliability of CVP imported water for the District. Tables 7-1 Imported WaterRetail, 7-1 Groundwater Retail, and 7-1 Recycled Water Retail show the retailer supply reliability of CVPimported water, groundwater, and recycled water based on the different year types.

Table 7-1 W estimates the reduction in CVP for single and multiple year droughts based on past allocations. The District renegotiated the shortage policy with USBR in 2015. Now the District will receive allocations as percentage of their full M&I contract (8,250 AFY), even in dry years. In past years if the allocation were decreased due to water shortages (an allocation of 75 percent or less), the District received the allocated percent of historical use, not contract volume. In 2014, for example, the historical use was 5,556 AFY. In Water Year 2015, the District was allocated 25 percent of the full contract volume of 8,250 AFY. This could increase the M&I amount allocated to the District, and therefore available to Hollister and Sunnyslope, in shortage years.

Although past allocations were reduced based on the shortage policy, CVP imports have historically been limited more significantly by M&I treatment capacity at the Lessalt WTP. The upgraded treatment capacity of Lessalt WTP is now approximately 2,240 AFY. Total surface water treatment capacity is expected to increase another 3,360 AFY when the West Hills WTP is completed in late 2017.

Increased treatment capacity, combined with the changes in application of the USBR shortage policy, would allow full use of the M&I CVP contract by Hollister and Sunnyslope. The table below shows the M&I allocations as reported by the San Luis & Delta-Mendota Water Authority (SLDMWA) for the USBR water year (March through February).

USBR		
Water		
Year	Allocation	Year Type
2006	100%	wet year
2007	100%	
2008	75%	
2009	60%	
2010	75%	
2011	100%	average year
2012	75%	
2013	70%	multiple dry year
		single and multiple dry
2014	50%	year
2015	25%	multiple dry year

CVP M&I allocations for the District

As shown in the table, in 2011 (an average year) M&I allocation was 100 percent or as much as 8,250 AFY under the adjusted shortage policy. During the single dry year of 2014, the allocation was 50 percent, or up to 4,125 AFY. The allocations during the three year drought were 70, 50, and 25 percent for 2013, 2014, and 2015, respectively.

The allocation in 2015 was the most severe restriction of M&I supply that has ever occurred and the likelihood of a repeat is considered small. The severity of the allocation was due in part to outstanding agreements and contracts that reduced available supply to CVP users. It is assumed these one-time agreements and contracts will not affect the CVP allocation to such a critical extent in the future. In addition, the US Bureau of Reclamation published a Municipal and Industrial Water Shortage Policy and Environmental Impact Statement for the Central Valley Project in August 2015 (USBR 2015). The M&I shortage policy recognizes that CVP M&I water is needed to meet Public Health and Safety (PHS) needs but cannot guarantee allocation. The minimum M&I water service allocation would be 50 percent of historic use (full contract for the District) or unmet PHS need to the extent that CVP supplies are available (USBR 2015). A reasonable expected allocation for the third year of a multiple year drought is 50 percent, as occurred in the single dry year of 2014. These allocations result in 5,775 AFY, 4,125 AFY, and 4,125 AFY for the 1st, 2nd and 3rd year of the multiple year drought. **Table 7-1 Imported Water Retail** shows the total CVP water available for the retailers, representing the allocation less CVP conveyance and storage losses. These losses are estimated as 10 percent in normal years and 20 percent during years with 50 percent or less allocation (given that losses are increased with less water in the system). Losses include evaporation and seepage as a result of storage in an open reservoir.

The District supplies approximately 400 AFY to M&I customers other than the City and Hollister. This additional M&I demand will be met during normal years, a single dry year, or the first year of a multiple year drought. In the event of a prolonged drought, this non-urban demand may be unmet in order to provide the minimum human health and safely for urban residents.

In **Table 7-1 Groundwater Retail**, the volume of available groundwater is not reduced from the sustainable yield of 9,263 AFY (discussed in **Section 6**). The yield available to Hollister and Sunnyslope is based on the sustainable yield of the three groundwater subbasins currently supplying the HUA less the groundwater pumped by other users in the area. Actual total pumping by Hollister, Sunnyslope, and other users in the three HUA subbasins has ranged from 10,000 AFY to 16,600 AFY depending on factors including CVP allocations. Overall, groundwater levels remain relatively stable; although localized declines have occurred during the most recent drought (see hydrographs on **Figure 6-4**). As shown, groundwater levels in the Hollister East and Tres Pinos subbasins remained steady, while groundwater levels in Hollister West continued a long term trend slightly decreasing from historical highs in the late nineties. As reported in past UWMPs, review of groundwater hydrographs for wells in the basin suggest that one or even three consecutive extreme dry years did not have a discernable impact on groundwater levels.

The level of recycled water is based on 2015 values, 116 AF. Recycled water is also not reduced in **Table 7-1 Recycled Water Retail** because the source is not affected significantly by year to year hydrological variability. However, a significant long-term increase of groundwater use (for example due to low CVP allocation and assuming no wellhead demineralization) could affect wastewater quality and thus the quality of the recycled water. A decrease in recycled water quality would affect its desirability as a supply for some sensitive uses.

7.3.2 COMPARISON OF SUPPLY AND DEMAND

The volume of groundwater used by the HUA is dependent on the CVP allocation. Groundwater quality in the area is relatively poor and users prefer the higher quality CVP water. All of the CVP allocation is expected to be used by Hollister and Sunnyslope and groundwater is expected to be used as a supplemental source. Groundwater volumes in **Tables 7-2 through 7-4** reflect this water preference and have been checked to ensure that groundwater pumping does not exceed yield. Groundwater yield is the sustainable yield of the three subbasins in which the HUA is located (Hollister East, Hollister, West, and Tres Pinos) less the pumping from other users. In addition, the need to blend groundwater with CVP supply due to water quality concerns is taken into account. Groundwater must be less than 50 percent of supply for regulatory requirements but it is preferred to be less than 35 percent of supply to achieve water quality goals.

The District manages San Justo Reservoir as storage for imported CVP water. In times of full allocation, the District is able to purchase additional water to keep as a reserve for future dry years. The District plans to reserve sufficient water to provide up to an additional 500 AF for a limited time during the most severe droughts for up to two years. The District also banks surplus water in Semitropic Water Storage District; this banking provides additional reserve during severe droughts.

In addition, as seen in the most recent drought, water conservation can reduce demand effectively. Through public outreach and a water shortage contingency plan, it is expected that in a single dry year and multiple dry years, water demand will be reduced by 20 percent in 2020 and 2025, and by 25 percent in 2030 and 2035. Additional conservation may be possible if required.

Table 7-2 R shows the projected supply totals and demands in normal years from 2020 through 2035 in five year intervals. **Table 7-3 R** shows the supply totals and demands for a single dry year (similar to 2014)

for the same time period. And **Table 7-4 R** shows the supply totals and demands for each year of a multiple year drought (similar to 2013 through 2015) for the same time period. Additional tables are shown in the text summarizing categories of supply and describing how much of the supply is groundwater, for blending goals, and expected conservation.

Normal Year	2020	2025	2030	2035
Supply totals (<i>autofill from Table 6-9</i>)	7,336	8,256	9,356	10,686
CVP	4,760	5,600	5,600	7,280
Groundwater	2,460	2,540	3,640	3,290
Recycled Water	116	116	116	116
Drought Demand	7,336	8,256	9,356	10,686
CVP Users Outside HUA	400	400	400	400
Projected Full HUA Demand (including recycled water)	6,936	7,856	8,956	10,286
Less Conservation	0	0	0	0
Difference	0	0	0	0
% Groundwater	25%	24%	28%	24%
Required conservation	0%	0%	0%	0%

Normal Year Supply and Demand

Table 7-3 R provides a comparison of supply and demand in a single dry year. In a typical single dry year, CVP allocations are expected to be 50 percent of the contracted amount less losses, which is a total of 3,300 AFY. Because of water quality concerns, groundwater would also be limited to 3,300 AFY to meet the 50 percent blending requirement. Additional supply to District M&I customers outside of the HUA area is needed to meet demand in a single dry year. Recycled water is expected to be available to meet the full potential recycled water use of 116 AFY. As discussed above, the District manages San Justo reservoir and Semitropic Water Storage District to keep surplus CVP imported water from past years as a reserve. In dry years, the District is able to release up to 1,500 AFY from the reserve to meet demand. The WSCP would be triggered to at least Stage 2 to achieve the required conservation (up to 25 percent in 2035).

Single Dry Year	2020	2025	2030	2035
Supply totals	5,949	6,685	7,117	8,115
CVP	3,300	3,300	3,300	3,300
CVP - reserve		100	500	1,399
Groundwater	2,533	3,169	3,201	3,300
Recycled Water	116	116	116	116
Drought Demand	5,949	6,685	7,117	8,115
CVP Users Outside HUA	400	400	400	400
Projected Full HUA Demand (including recycled water)	6,936	7,856	8,956	10,286
Less Conservation	(1,387)	(1,571)	(2,239)	(2,572)
Difference	0	0	0	0
% Groundwater	43%	49%	49%	50%
Required conservation	20%	20%	25%	25%

Single Dry Year Supply and Demand

Table 7-4 R provides a comparison of supply and demand in multiple dry year periods, respectively. As with the single dry year, supply is limited by the CVP allocations and the 50 percent groundwater blending requirements. In the first dry year (similar to 2013), the CVP allocation is expected to be 70 percent of the contract less 10 percent for losses, 5,197.5 AFY. The HUA WSCP could be triggered to decrease water demand up to 10 percent in 2035. In the second dry year (similar to 2014), the CVP allocation is expected to be 50 percent of the contract less 20 percent for losses, or 3,300 AFY, and thus groundwater would be limited to 3,300 AFY, to meet blending requirements. The District supplies approximately 400 AFY to M&I customers other than the City and Sunnyslope and will deliver that supply in the first year of a multiple year drought. In the event of a prolonged drought, this non-urban demand may be unmet in order to provide the minimum human health and safely for urban residents.

Conservation would be needed to reduce demand by up to 25 percent by year 2030 (Stage 3 in the WSCP). In the third dry year (similar to 2015), CVP allocation is expected to be 50 percent of the contract less 20 percent for losses (3,300 AFY). The rationale for projecting these allocations is discussed in section 7.3.1.

Because CVP allocations are limited, groundwater would also be limited to the same volume for blending. Based on the projected future supply, water demand would have to be reduced up to 25 percent by 2035. This 25 percent demand reduction can be obtained through the WSCP and water conservation. The CVP reserve release would not be needed until CVP allocations drop to 50 percent, expected in a single dry or the end of a multiple year drought.

Multiple Dry Years Supply and Demand

Multiple Dry Year 1	2020	2025	2030	2035
Supply totals	6,296	7,078	8,013	8,629
CVP	4,760	5,198	5,198	5,198
CVP - reserve				
Groundwater	1,420	1,764	2,699	3,315
Recycled Water	116	116	116	116
Drought Demand	6,296	7,078	8,013	8,629
CVP Users Outside HUA	400	400	400	400
Projected Full Demand (including recycled water)	6,936	7,856	8,956	10,286
Less Conservation	(1,040)	(1,178)	(1,343)	(2,057)
Difference	0	0	0	0
% Groundwater	23%	25%	34%	39%
Required conservation	15%	15%	15%	20%
Multiple Dry Year 2	2020	2025	2030	2035
Supply totals	5,549	6,285	6,716	7,715
CVP	3,300	3,300	3,300	3,300
CVP - reserve				999
Groundwater	2,133	2,869	3,300	3,300
Recycled Water	116	116	116	116
Drought Demand	5,549	6,285	6,716	7,715
CVP Users Outside HUA	0	0	0	0
Projected Full HUA Demand	6,936	7,856	8,956	10,286
(including recycled water)	0,950	7,850	8,930	10,280
Less Conservation	(1,387)	(1,571)	(2,239)	(2,572)
Difference	0	0	0	0
% Groundwater	39%	47%	50%	50%
Required conservation	20%	20%	25%	25%
Multiple Dry Year 3	2020	2025	2030	2035
Supply totals	5,549	6,285	6,716	7,715
CVP	3,300	3,300	3,300	3,300
CVP - reserve				999
Groundwater	2,133	2,869	3,300	3,300
Recycled Water	116	116	116	116
Drought Demand	5,549	6,285	6,716	7,715
CVP Users Outside HUA	0	0	0	0
Projected Full HUA Demand (including recycled water)	6,936	7,856	8,956	10,286
Less Conservation	(1,387)	(1,571)	(2,239)	(2,572)
Difference	0	0	0	0
% Groundwater	39%	47%	50%	50%
Required conservation	20%	20%	25%	25%

7.4 REGIONAL SUPPLY RELIABILITY

The HUA agencies are currently working to increase their regional supply reliability by increasing recycled water and using groundwater as available. The HUA continues to pursue water conservation to reduce the need for additional imported supplies. In addition, enhanced groundwater management, or improvements in regional water management and coordination will strengthen the local supply sources.

Table 7-1 Wholesale: Basis of Water Year Data						
	Available Supplies if Year Type Repeats					
Base Year		volume only, percent or both				
	Volume Available	% of Average Supply				
2011	8,250	100%				
2014	4,125	50%				
2013	5,775	70%				
2014	4,125	50%				
2015	4,125	50%				
	Base Year 2011 2014 2013 2014	Available Year TypBase YearAgency may provide only,Agency may provide Only,Volume Available20118,25020144,12520135,77520144,125				

NOTES: The volume of supply does not reflect system losses.

Table 7-1 Imported Water Retail: Basis of Water Year Data						
			Supplies if De Repeats			
Year Type	Base Year	Agency may provide volume only, percent only, or both				
		Volume Available	% of Average Supply			
Average Year	2011	7,425	100%			
Single-Dry Year	2014	3,300	50%			
Multiple-Dry Years 1st Year	2013	5,198	70%			
Multiple-Dry Years 2nd Year	2014	3,300	50%			
Multiple-Dry Years 3rd Year	2015	3,300	50%			
Multiple-Dry Years 4th Year Optional						
Multiple-Dry Years 5th Year Optional						
Multiple-Dry Years 6th Year Optional						

NOTES: CVP Imported Water less District system losses

Table 7-1 Groundwater Retail: Basis of Water Year Data						
		Available Supplies if Year Type Repeats Agency may provide volume only, percent only, or both				
Year Type	Base Year					
		Volume Available	% of Average Supply			
Average Year	2011	9,263	100%			
Single-Dry Year	2014	9,263	100%			
Multiple-Dry Years 1st Year	2013	9,263	100%			
Multiple-Dry Years 2nd Year	2014	9,263	100%			
Multiple-Dry Years 3rd Year	2015	9,263	100%			
Multiple-Dry Years 4th Year Optional						
Multiple-Dry Years 5th Year Optional						
Multiple-Dry Years 6th Year Optional						

NOTES: Maximum Groundwater Available. The volume of supply does not take into account limitation for blending groundwater with treated water to achieve water quality goals

Table 7-1 Recycled Water Retail: Basis of Water Year Data						
		Available Supplies if Year Type Repeats				
Year Type	Base Year	Agency may provide volume only, percent only, or both				
		Volume Available	% of Average Supply			
Average Year	2011	116	100%			
Single-Dry Year	2014	116	100%			
Multiple-Dry Years 1st Year	2013	116	100%			
Multiple-Dry Years 2nd Year	2014	116	100%			
Multiple-Dry Years 3rd Year	2015	116	100%			
Multiple-Dry Years 4th Year Optional						
Multiple-Dry Years 5th Year Optional						
Multiple-Dry Years 6th Year Optional						

NOTES: Recycled Water volumes based on actual 2015 supply

Table 7-2 Retail: Normal Year Supply and Demand Comparison						
	2020	2025	2030	2035	2040 (Opt)	
Supply totals						
(autofill from Table 6-9)	11,539	11,539	11,539	11,539	0	
Demand totals						
(autofill from Table 4-3)	6,936	7,856	8,956	10,286	0	
Difference	4,603	3,683	2,583	1,253	0	

NOTES: Demand totals include non-potable demand and CVP users outside of the HUA. CVP imported water will be reduced under drought conditions, this is discussed in Section 7. The reasonably available volume in a normal year is the full contract less 10 percent system losses.

Table 7-2 Wholesale: Normal Year Supply and Demand Comparison					
	2020	2025	2030	2035	2040 (Opt)
Supply totals (autofill from Table 6-9)	8,250	8,250	8,250	8,250	0
Demand totals (autofill fm Table 4-3)	5,632	6,425	6,425	8,105	0
Difference	2,618	1,825	1,825	145	0
NOTES:					

Table 7-3 Retail: Single Dry Year Supply and Demand Comparison							
2020 2025 2030 2035 2040 (Opt)							
Supply totals	7,336	8,256	9,356	10,686			
Demand totals	7,336	8,256	9,356	10,686			
Difference	0	0	0	0	0		

NOTES: Assume CVP allocations at 50 percent (4,125 AFY), groundwater limited to 4,125 AFY due to blending requirements. The WSCP would be triggered to at least Stage 2 to achieve the required conservation (up to 20 percent in 2035). Demand totals include non-potable demand and CVP users outside of the HUA.

Table 7-3 Wholesale: Single Dry Year Supply and Demand Comparison					
	2020	2025	2030	2035	2040 (Opt)
Supply totals	4,125	4,125	4,125	4,125	
Demand totals	4,125	4,125	4,125	4,125	
Difference	0	0	0	0	0
NOTES:					

Table 7-4 Retail: Multiple Dry Years Supply and Demand Comparison						
		2020	2025	2030	2035	2040 (Opt)
	Supply totals	6,296	7,078	8,013	8,629	
First year	Demand totals	6,296	7,078	8,013	8,629	
	Difference	0	0	0	0	0
	Supply totals	5,549	6,285	6,716	7,715	
Second year	Demand totals	5,549	6,285	6,716	7,715	
	Difference	0	0	0	0	0
	Supply totals	5,549	6,285	6,716	7,715	
Third year	Demand totals	5,549	6,285	6,716	7,715	
	Difference	0	0	0	0	0
NOTES:						

2020 2025 2030 2035 2040 (Opt)						
	Supply totals	5,950	6,497	6,497	6,497	
First year	Demand totals	5,950	6,497	6,497	6,497	
	Difference	0	0	0	0	0
	Supply totals	4,125	4,125	4,125	5,124	
Second year	Demand totals	4,125	4,125	4,125	5,124	
	Difference	0	0	0	0	0
Third year	Supply totals	4,125	4,125	4,125	5,124	
	Demand totals	4,125	4,125	4,125	5,124	
	Difference	0	0	0	0	0

8. WATER SHORTAGE CONTINGENCY PLANNING

The District, the City, and Sunnyslope have all passed ordinances/resolutions to address shortages in water supply. In addition, the HUA agencies have developed a Water Shortage Contingency Plan (WSCP) that details how to reduce demand in the event of a water supply shortage. The WSCP was updated to include five water waste prohibitions cited by the Governor Brown in Executive Order B-37-16, on May 9, 2016. The entire WSCP is included in **Appendix G**.

Emergency responses to natural disasters are also discussed in a joint Water Shortage Emergency Response Plans to assist in planning and managing supply disruption, **Appendix H.**

8.1 STAGES OF ACTION

The HUA agencies have developed a water shortage response plan in the event of supply interruption. The plan includes a four-stage rationing plan with voluntary and mandatory rationing depending on the severity and duration of the water supply shortage. This water shortage response was based on the Sunnyslope No Water Waste Ordinance No. 45 and was first documented for the HUA as part of the 2000 UWMP.

Table 8-1 R shows the four stages of action based on a series of triggers. Because water supply is dependent on CVP and blending requirements tie groundwater with the amount of imported water, an important trigger for conservation stages is the CVP allocation. The table below shows the reduction of CVP allocation and the resulting water shortage stage. It should be noted that other factors can cause a water supply shortage (e.g., water quality issues or natural disasters) and may be cited in declaring a water shortage.

		Demand
Stage	CVP Allocation	Reduction
0	100 to 75 percent	0 percent
1	50 to 75 percent	10-15 percent
2	50 percent, single dry year	15-25 percent
	50 percent, for more than one	
3	year	25-35 percent
4	Less than 50% for multiple years	50 percent

* Additional water from the District will reduce reductions

The first stage occurs when current supply is reduced by up to 15 percent and uses voluntary rationing to reach the demand reduction goal of up to 15 percent. The other stages operate in a similar manner using mandatory rationing to reach the stage goal.

8.2 PROHIBITIONS ON END USERS

Table 8-2 R shows the restrictions and prohibitions on end users by stage; these are discussed below.

8.2.1 WATER USE PRIORITIES AND END USERS

Potential implementation of restrictions and prohibitions on end users is based on a fundamental prioritization of domestic supply for human health and safety over non-essential uses, including landscape irrigation. In the event of a water shortage, water service may be restricted or prohibited for non-essential uses, recognizing that certain end users may be required to save more water than others because of their specific use. Prohibitions on end uses will affect user types differently:

- For urban residential users (who typically rely on HUA agencies for domestic supply), water service will continue during a shortage with restrictions on outdoor water use in Stages 1 through 3 and prohibitions in Stage 4.
- Rural residential users of CVP M&I water (i.e., five-acre parcels) would also be subject to restrictions and prohibitions on outside water features and landscape irrigation.
- Landscape irrigators (e.g., golf courses, dedicated irrigation meters) are subject to the restrictions listed below for Stages 1 through 3 and the prohibition in Stage 4.

8.2.2 LANDSCAPE IRRIGATION

Restrictions and prohibitions on irrigation include:

- Water Waste Landscape irrigation cannot occur within 48 hours following measurable rainfall at any stage, per Executive Order B-37-16.
- Water Hours Beginning in Stage 1 the watering is discouraged between the hours of 9:00 a.m. and 5:00 p.m. Under Stage 2, watering during these hours is prohibited.
- Water Duration Watering or irrigating of lawn, landscape or other vegetated area with potable water using a landscape irrigation system or a watering device that is not continuously attended is limited. In stage 1 irrigation can be no more than three days a week with a total fifteen (15) minutes watering per water day per station. Due to clay soils in most areas of the HUA, irrigators are recommended to break up irrigation times into five (5) minute intervals. Instead of constant irrigation for fifteen (15) minutes, schedule five (5) minute cycles, let the soil rest for at least an hour, than do another five (5) minute interval. This will reduce puddling and runoff.
- Limits on Watering Days In Stage 2 Watering or irrigating of lawn, landscape or other vegetated area with potable water is limited to three days per week from April through October. Watering is limited to two days a week in Stage 3.
- Types of Irrigation Stage 3 restricts the irrigation of roadway medians and irrigation for new homes. In Stage 4, no potable water for irrigation is permitted.

8.2.3 COMMERCIAL, INDUSTRIAL, AND INSTITUTIONAL (CII)

During a drought several CII prohibitions come into effect including:

- Dish Washing Water Use Restaurants are required to Use Water Conserving Dish Wash Spray Valves. The prohibition is triggered by Stage 2 but is encouraged under Stage 1.
- Water by Request Only Beginning in Stage 1, restaurants and hotels are prohibited from providing drinking water to any person unless expressly requested.
- Commercial Car Wash Systems Commercial conveyor car wash systems must have installed operational re-circulating water systems in Stage 2, this is encouraged under Stage 1.
- Single Pass Cooling Systems Installation of single pass cooling systems is not recommended in Stage 1 and prohibited in Stage 2.
- Hotel Laundry Commercial lodging establishments must provide guests option to decline daily linen services in Stage 1 and increase the program under stage 2.

8.2.4 WATER FEATURES AND SWIMMING POOLS

Water features including decorative water features and does not apply to swimming pools or spas.

- Water feature restrictions In Stage 1, use of recirculated water is encouraged in operating a water fountain or other decorative water features. In Stage 2 recirculation is required. While under Stage 3, filling or re-filling ornamental lakes or ponds with potable water is prohibited, except to the extent needed to sustain aquatic life.
- Pools are treating differently than water features. Pools are required to have pool covers to reduce evaporation when Stage 2 is triggered.

8.2.5 OTHER

Other restrictions include:

- Hoses Hoses are required to have automatic shut off nozzles for vehicle washing at any stage, per Executive Order B-37-16.
- Hard Surfaces Use of potable water for washing hard surfaces is only permitted with hand held buckets or hoses with shut off nozzles at any stage, per Executive Order B-37-16.
- Leaks Customers must repair leaks, breaks, and malfunctions in a timely manner. Broken or malfunctioning sprinkler heads must be repaired within 48 hours after the customer receives a notification from the water agency; all leaks or breaks must be repaired by the customer within 48 hours of receiving a notification from the water agency. In Stage 3, all leaks must be repaired in 72 hours; under stage 3 and 4, this decreases to within 48 and 24 hours, respectively.
- Dust Control In Stage 3, use of potable water for construction and dust control is prohibited.
- Vehicle Washing In Stage 2, it is prohibited to wash vehicles at facilities except those using recycled or recirculating water.

- Drought Rates In Stage 4, the agencies may consider adopting rate structures and other pricing mechanisms to maximize water conservation.
- No new Building Permits Upon declaration of a Stage 4 Water Supply Shortage Emergency condition, the City Administrator and/or County Administrator, is authorized to implement a program in his or her discretion to limit or withhold the issuance of building permits which require new or expanded water service

8.3 PENALTIES, CHARGES, OTHER ENFORCEMENT OF PROHIBITIONS

Any customer violating the regulations and restrictions on water use set forth in the "No Waste" Ordinances will receive a written warning for the first violation. On the third violation, the customer will receive a third written warning and the retailer may install a flow-restrictor. If a flow-restrictor is placed, the violator will pay the cost of installation and removal. Any willful violation occurring subsequent to the issuance of the second written warning will constitute a misdemeanor and may be referred to the District Attorney's office for prosecution pursuant. Misdemeanor convictions could include imprisonment and/or fines. The length of time for imprisonment and the magnitude of the fine vary between Hollister and Sunnyslope. If water service is disconnected, it will be restored only upon payment of a reconnection charge. These penalties apply at any time but are likely to be more closely adhered to during drought periods.

8.4 CONSUMPTION REDUCTION METHODS BY AGENCIES

Consumption reduction methods are actions that are taken by the water agency to reduce their consumption, whereas the prohibitions on end uses, addressed in Section 8.2, restricts end uses that are the responsibility of end users. These consumption reduction methods are shown in **Table 8-3**. It has been shown during the current drought (2013-2015) that increases in public outreach has had a significant impact in reducing demand. Public outreach was expanded by 200 percent and over a 25 percent reduction was achieved by both Hollister and Sunnyslope. Based on this recent experience, the implementation of the specific consumption reduction methods listed below is expected to reduce demand during drought or water supply interruptions.

- 1. Expand Public Information Campaign Newsletter and other flyers in both English and Spanish were used to publicize programs and explain the importance of drought conservation.
- 2. Improve Customer Billing Customers with higher than average bills were contacted and possible water savings were recommended.
- 3. Offer Water Use Surveys Both residential and landscape surveys help high water users to identify areas of potential conservation.
- 4. Provide Rebates or Giveaways of Plumbing Fixtures and Devices Rebates and plumbing retrofits are available at all times but are publicized more during drought conditions. Plumbing retrofits including hose nozzles, faucet aerators, and shower heads are available at no cost to customers. Rebates are available for low flow toilets and high efficiency washing machines.

- 5. Provide Rebates for Landscape Irrigation Efficiency There is currently a landscape efficiency rebate program that provides rebates for landscape conversion, low-volume sprinkler heads, rain sensors, hose timers, and also includes customized sprinkler schedules.
- 6. Increase Water Waste Patrols Examples include: Implement a Water Waste Patrol program; Increase staffing for Water Waste Patrol; Increase authority of Water Waste Patrol.
- 7. Moratorium or Net Zero Demand Increase on New Connections The agencies have added a no new connection element to their WSCP that is triggered in Stage 4.
- 8. Implement or Modify Drought Rate Structure or Surcharge –a drought rate structure may be implemented in future droughts.

8.5 DETERMINING REDUCTIONS

Under normal water supply conditions, potable water production values for Hollister and Sunnyslope are recorded daily and reported monthly to the Water Supervisor. During a Stage I or Stage II water shortage, daily production figures will be reported to the Water Supervisor of each agency. The Supervisor will compare the weekly production to the target weekly production to verify that the reduction goal is being met. Weekly reports will be forwarded respectively to the General Manager of Sunnyslope, the Public Works Director at the City of Hollister and to the Program Manager of the WRA. During a Stage III or Stage IV water shortage, the daily production report will be provided to the General or City Manager of each agency. In Stages I through IV, monthly reports will be sent to the City Council and the Sunnyslope Board of Directors. If reduction goals are not met, the respective managers will notify the governing board of each agency that additional action is required.

8.6 IMPACT ON REVENUES AND EXPENSES

All surplus revenues that the District, Hollister, and Sunnyslope collect are currently reinvested into the water supply system.

Based on projected and observed declines in revenue during shortages, the entities determined rate increases may be needed in Stage II through IV. In Stage I, no additional water purchases and no rate increases are required. For stages II, III, and IV, a rate increase of 25, 50, and 100 percent may be needed, respectively.

8.7 SBCWD ORDINANCE

In April 2015, the San Benito County Water District declared a Water Shortage Emergency and passed a resolution to implement the district's Water Shortage Contingency Plan. The ordinance No. 2015-04, include some elements that affect the HUA including voluntary conservation. Most of the end prohibitions and enforcement are directed to agricultural customers and M&I customers than directly receives water from the District. The ordinance is included as **Appendix I**.

8.8 CATASTROPHIC SUPPLY INTERRUPTION

Hollister, Sunnyslope, and the District also have water shortage emergency response plans in place. Hollister has general emergency plans that include their water supply. Sunnyslope and the City have general Emergency Disaster Response Plan as well as a Power Failure Emergency Response Plans. The plans also include steps to be taken during and after a disaster and the use of the Standard Emergency Management System (SEMS). Copies of these plans are included as **Appendix H**. The District relies on their current Water User's Handbook and County emergency plans.

These plans develop the procedures for each agency before and during a disruption of water supply during a natural disaster. In 1999, the California Emergency Management Agency (Cal EMA) published *Emergency Planning Guidance for Public and Private Water Utilities* to improve coordination among water utilities and other emergency response agencies and to assist water utilities in developing or revising emergency plans and procedures. It is recommended that ongoing coordination between the City, Sunnyslope, and the District take place to ensure these water supply emergency plans remain consistent and meet the goals provided in the guidance documents. With these plans in place, the retailers in the HUA can adequately handle a water supply shortage due to a natural disaster or another interruption of the water supply (Cal EMA 1999).

8.9 MINIMUM SUPPLY NEXT THREE YEARS

Water agencies must provide an estimate of the minimum water supply available during each of the next three water years, 2016, 2017, and 2018. This will reflect the combined availability of all water sources and will assume the same hydrology as was noted during the historical multiple-dry year period. (Chapter 7, Section 7.3).

The estimate of the minimum supply for the next three years is shown in **Table 8-4 R**. The HUA is currently experiencing a multiple year drought. The average local precipitation of the last three water years has been 58 percent of normal. In addition, CVP allocation for M&I users in 2015 was the lowest on record for the HUA. The allocation during the three year drought were 70, 50, and 25 percent for 2013, 2014, and 2015, respectively. In response to this continued drought and decreased supply and expanded public outreach the HUA reduced its supply by over 25 percent. Given the deep conservation, historical low allocations, and expected growth water demand in 2015 likely reflects the minimum water supply required for the next three years.

Table 8-4 W shows the minimum wholesaler supply for the next three years. As with the retailer, 2015 likely reflects the minimum water supply required for the next three years. The delivered 1,719 AFY plus 20 percent to reflect system losses, for a total 2,149 AFY.

Table 8-1 Retail Stages of Water Shortage Contingency Plan					
		Complete Both			
Stage	Percent Supply Reduction ¹ Numerical value as a percent	Water Supply Condition (Narrative description)			
Add additional r	ows as needed				
1	15%	Any short term supply reduction			
2	25%	Moderate supply reductions, including but not limited to short term supply limitations (i.e. droughts, infrastructure issues, etc.)			
3	35%	Moderate to severe supply reductions, including but not limited to moderate supply shortages (i.e. prolonged droughts)			
4	50%	Severe water supply reductions, including but not limited to supply disruption (i.e. water quality issues or natural disasters) or prolonged droughts			
	¹ One stage in the Water Shortage Contingency Plan must address a water shortage of 50%.				
NOTES:	NOTES:				

Table 8-1 Wholesale Stages of Water Storage Contingency Plan					
		Complete Both			
Stage	Percent Supply Reduction ¹ Numerical value as a percentage	Water Supply Condition (Narrative description)			
Add additional r	Add additional rows as needed				
1	15%	Any short term supply reduction			
2	25%	Moderate supply reductions, including but not limited to short term supply limitations (i.e. droughts, infrastructure issues, etc.)			
3	35%	Moderate to severe supply reductions, including but not limited to moderate supply shortages (i.e. prolonged droughts)			
4	50%	Severe water supply reductions, including but not limited to supply disruption (i.e. water quality issues or natural disasters) or prolonged droughts			
¹ One stage in the	1 One stage in the Water Shortage Contingency Plan must address a water shortage of 50%.				
NOTES:					

Table 8-2 R	Table 8-2 Retail Only: Restrictions and Prohibitions on End Uses				
Stage	Restrictions and Prohibitions on End Users Drop down list These are the only categories that will be accepted by the WUEdata online submittal tool	Additional Explanation or Reference (optional)	Penalty, Charge, or Other Enforcement? <i>Drop Down List</i>		
Add additiona	l rows as needed				
1,2,3,4	Landscape - Restrict or prohibit runoff from landscape irrigation	Excess runoff is discouraged under stage 1 and profited for Stage 2 and above	Yes		
1,2,3,4	Landscape - Limit landscape irrigation to specific times	Irrigation is discouraged between the hours of 9:00 a.m. and 5:00 p.m in Stage 1 and prohibited for Stage 2 and above	Yes		
2,3	Landscape - Limit landscape irrigation to specific days	Irrigation is limited to three days a week in Stage 2 and reduced to two days a week in Stage 3.	Yes		
4	Landscape - Prohibit certain types of landscape irrigation	Irrigation outside new homes or on medians is prohibited in Stage 3. No new turf is allowed in Stage 4	Yes		
4	Landscape - Prohibit all landscape irrigation		Yes		
1,2,3,4	Landscape - Other landscape restriction or prohibition	Irrigation within 48 hours after rainfall is prohibited.	Yes		
1,2,3,4	Landscape - Other landscape restriction or prohibition	Duration of irrigation is suggested to be no more than 15 minutes per watering in Stage 1. This limit is required in Stage 2			
1, 2,3,4	CII - Other CII restriction or prohibition	Commercial car washes are required to have recirculating systems. Recirculation is encouraged in stage 1 and required in stage 2 and above	Yes		
1,2,3,4	CII - Lodging establishment must offer opt out of linen service	Hotel programs are encouraged in stage 1 and required for Stage 2 and above	Yes		

Stage	Restrictions and Prohibitions on End Users Drop down list These are the only categories that will be accepted by the WUEdata online submittal tool	Additional Explanation or Reference (optional)	Penalty, Charge or Other Enforcement? Drop Down List
Add additiona	l rows as needed		
1,2,3,4	CII - Restaurants may only serve water upon request	Drinking water by request is encouraged in stage 1 and required for Stage 2 and above	Yes
1,2,3,4	CII - Other CII restriction or prohibition	Installation of Single Pass Cooling Systems are discouraged in Stage 1 and prohibited for stage 2 and above	
1,2,3,4	CII - Other CII restriction or prohibition	Washing a vehicle requires a hose with a shut valve in Stage 2 and above. This is encouraged in Stage 1	Yes
1,2,3,4	Water Features - Restrict water use for decorative water features, such as fountains	Recirculating water features are encouraged at all stages	Yes
3	Water Features - Restrict water use for decorative water features, such as fountains	Filling or refilling ornamental lakes and ponds are prohibited	Yes
1,2,3,4	Pools and Spas - Require covers for pools and spas	All new pools should have a pool cover, this is encouraged in stage 1 and required in stage 2 and above	Yes
2	Pools and Spas - Require covers for pools and spas	Existing pools should not be refilled	Yes
1,2,3,4	Other - Customers must repair leaks, breaks, and malfunctions in a timely manner	Fixing leaks is encouraged under stage 1. Leaks must be fixed with 72, 48 and 24 hours in Stages 2, 3 and 4, respectively	Yes
1,2,3,4	Other - Require automatic shut of hoses	Washing a vehicle requires a hose with a shut valve in all stages.	Yes
1,2,3,4	Other - Prohibit use of potable water for washing hard surfaces	Washing hard surfaces is prohibited in all stages.	Yes
4	Other - Prohibit vehicle washing except at facilities using recycled or recirculating water		Yes
4	Other	Limits on new water service, building permits, and annexation	Yes
3	Other	Agencies may consider drought rates, if applicable	Yes

Stage	Consumption Reduction Methods by Water Supplier Drop down list These are the only categories that will be accepted by the WUEdata online submittal tool	Additional Explanation or Reference <i>(optional)</i>
d additional	rows as needed	
1,2,3,4	Expand Public Information Campaign	
1,2,3,4	Improve Customer Billing	
1,2,3,4	Increase Frequency of Meter Reading	
1,2,3,4	Offer Water Use Surveys	
1,2,3,4	Provide Rebates on Plumbing Fixtures and Devices	
1,2,3,4	Provide Rebates for Landscape Irrigation Efficiency	
1,2,3,4	Provide Rebates for Turf Replacement	
<u> </u>	Reduce System Water Loss	
2,3,4	Increase Water Waste Patrols	
4	Moratorium or Net Zero Demand Increase on New Connections	
3,4	Implement or Modify Drought Rate Structure or Surcharge	

Table 8-4 Retail: Minimum Supply Next Three Years				
2016 2017 2018				
Available Water Supply	4,820	4,820	4,820	
NOTES: Reflects total water supply for 2015				

Table 8-4 Wholesale: Minimum Supply Next Three Years				
2016 2017 2018				
Available Water Supply	2,149	2,149	2,149	
NOTES: The delivered 1,719 AFY plus 20 percent to reflect system				
losses.				

This Page Intentionally Blank

9. DEMAND MANAGEMENT MEASURES

9.1 WHOLESALE AGENCY PROGRAMS

The District is the wholesaler to Zone 6 (Northern San Benito County) for CVP imported water, while Hollister and Sunnyslope are retailers that purchase CVP water from the District. These three agencies have a strong partnership to plan the future water supply for the HUA through this document and others, including the Master Plan. With regard to demand management, the District provides the conservation coordinator for the WRA, financial contribution and technical support to the WRA, and reporting on BMP implementation for Sunnyslope (not a signatory to the CUWCC MOU).

The District continues to:

- Join with retail water agencies to plan, design, implement, manage, and evaluate regional conservation programs
- Provide conservation-related technical support and information to retail agencies they serve
- Operate part of the conservation program
- Provide reports on BMP implementation within their service area by retail water agencies that are not signatories to the CUWCC MOU
- Encourage all of their retail agencies to be part of the Water Resources Association (WRA).

9.2 DEMAND MANAGEMENT MEASURES FOR HUA

Hollister, Sunnyslope, and the District are committed to implementing water conservation and water recycling programs. The three agencies, along with the City of San Juan Bautista, participate in the WRA of San Benito County. The WRA retains a Water Conservation Coordinator, who is a District employee, to serve the water conservation needs for the WRA members.

As required by USBR, the WRA coordinator also enters water conservation data to the CUWCC database for Sunnyslope and the District. Hollister's Utility Technician, a certified and functional Conservation Practitioner, enters this information into the CUWCC's database on behalf of the City. The CUWCC BMP number is included with each section for consistency with CUWCC reporting. The WRA coordinator also enters data for District activities into the Agricultural Water Management Council (AWMC) database each year as required by the Bureau. In addition, the WRA coordinator updates the Agricultural Water Management Plan for the District every five years.

UTILITY OPERATIONS RESOURCES – BMP 1

Water waste prevention ordinances. Both Hollister and Sunnyslope have approved water conservation ordinances to reduce water waste at all times. San Benito County has also created a Water Conservation Plan (also included in **Appendix G**). The plan prohibits certain water wasting uses, limits others, creates guidelines for plumbing fixtures in new developments, and encourages water conservation.

Metering. Hollister and Sunnyslope are fully metered and currently have meter replacement programs in place. Sunnyslope requires separate irrigation meters for commercial landscaping, parks, and other non-residential water services.

Tiered pricing. A tiered pricing structure is always in place and is not dependent upon a water shortage for implementation, although a future rate structures could include drought rate structures. Tiered pricing sends a signal to customers regarding their water use. Both the City and Sunnyslope use a tiered rate structure for single family residences, where efficient water use is billed at a low price and higher water use is billed at progressively higher prices. The rate structures are included in **Appendix K**.

Programs to assess and manage distribution system real loss. The City and Sunnyslope generally have small water losses for the overall system. Each retailer regularly inspects the distribution system, to check for leaks. In addition, customers are contacted if water bill increases suggest leaks.

PUBLIC EDUCATION AND OUTREACH – BMP 2

WRA, through its Water Conservation Coordinator and other staff, supports a variety of public education and outreach efforts. This includes bill inserts, flyers, Water Awareness Month, school presentations, and more. Water Awareness Month (WAM) is in May at the start of the irrigation season. The timing is optimal to remind water customers about irrigation programs and water efficiency. In addition, Proclamations are read at the Member Agencies board and council meetings as well as the Board of Supervisors meeting in proclaiming May as Water Awareness Month. During WAM, a banner is strung across San Benito Street to urge people to contact their water provider for water saving ideas, the WRA sets up a booth at the local Farmer's Market, and holds workshops or classes covering a variety of topics concerning water use reduction.

The WRA retains a Water Conservation Coordinator, who is a District employee, to serve the water conservation needs for the WRA members. This person's duties focus primarily on ongoing programs within the District to encourage wise water use among the agricultural community and within the Hollister Urban Area. The duties of this position (and any support staff, as necessary) are described in section 9.3.

RESIDENTIAL PROGRAMS – BMP 3

Residential Surveys. This survey is a free home water conservation checkup including identification of the need for plumbing retrofits, a water softener check, household leak checks and identification of other possible water conservation improvements.

Plumbing Retrofits. As a complement to the residential surveys, WRA offers plumbing retrofits that replace older shower heads, add aerators in faucets and free hose nozzles. While this program has been successful in the past, it is estimated that it has reached over 75 percent of customers and may not provide significant water demand reduction in the future.

High Efficiency Clothes Washers (HECW) Rebates. These HECW use half as much water as traditional top loading clothes washers. These machines also use less detergent and help protect the quality of groundwater supplies.

WaterSense Specification (WSS) Toilet Rebates. Rebates and giveaways are available for residential customers who replace existing toilets with high efficiency models.

Water Softener Rebate Program. Since 2007, a program has been in place to issue rebates to those water customers who remove a self-regenerating water softeners (SRWS) without replacement (\$300) or with transition to an off-site exchange service (\$250). In July 2014, the City of Hollister enacted an ordinance that prohibits the installation of SRWS that use sodium and/or potassium salts. In February 2015, Sunnyslope adopted a new District Code prohibiting the installation of SRWS that use sodium and/or potassium salts.

Residential Bill Comparison. In addition to public outreach information. The agencies revised their bills to reflect a comparison of 2013 water consumption and current consumption for customers to gauge their reduction efforts.

High-Bill Contact Programs This programs alerts residential users if the monthly bill is higher than a predetermined threshold. This will help the residential user identify leaks or changes in water use.

Notification of Leaks. If a leak is detected on a customer's property, they are alerted so they can repair the leak and avoid further water waste.

CII PROGRAMS – BMP 4

Commercial High - Efficiency Single Load Clothes Washers. Rebates are available for commercial customers who replace existing washers with high efficiency single load machines.

Commercial High - Efficiency Toilets. Rebates are available for commercial customers who replace existing toilets with high efficiency model.

Green Business Certification. The WRASBC is working together with the San Benito County Chamber of Commerce, San Benito County Integrated Waste Management and PG&E to assist, recognize and promote businesses and government agencies that volunteer to operate in a more environmentally responsible way.

Hotel Program. The WRASBC provides table cards to hotels and motels that allow guests to have linens washed only upon request.

LANDSCAPE PROGRAMS – BMP 5

Landscape Water Surveys. This survey is a free water conservation checkup for large urban irrigators including the identification of needs for plumbing retrofits and/or updated irrigation hardware, leak checks and identification of other possible water conservation improvements.

Landscape Irrigation Hardware Rebate Program. The WRA has rebates on hose timers, rain sensors and MP Rotator irrigation nozzles and sprinkler bodies with pressure regulators. A rebate is offered of 50 percent of the cost of qualifying products, up to \$100.

Turf Removal Program. In July 2014 the WRA added a Turf Removal Program to encourage customers to remove high water use turf areas from residential parcels. This program complements the irrigation hardware rebates and free water efficient landscape plans. In Fiscal Year 2015/16 the program expanded its offer from a \$1 per square of turf removed up to 500 square feet to 1,000 square feet. The only land cover allowed in the area where the turf is removed includes: drought tolerant or native plants, permeable hardscapes and/or a combination. As of November 2015, over 88,000 square feet of turf have been removed in the Hollister Urban Area. The turf removal program includes extensive public outreach in Spanish and English. As of August 2015, the WRASBC allocated all its' funding for this program. However, the WRASBC promotes the State-wide Turf Removal Program and any residents have taken advantage of this rebate.

Irrigation Education. The District, in collaboration with the WRA, has been offering a series of classes since 2009 on irrigation efficiency and other agriculture practices. These workshops provide concepts, tools, and examples for optimizing irrigation and nitrogen management efficiency in row, tree, and greenhouse crop production. The classes also focus on keeping records and acquiring data needed for water quality regulation and reporting. The WRA also offers classes to residential customers. These classes instruct customers on topics such as efficient irrigation practices, converting landscapes to be water wise, and composting.

Custom Sprinkler Schedule. A Water Conservation Specialist will design a watering schedule tailored to customer habits, sprinkler's output, and the seasonal water needs of the individual lawn and garden. The plan is free and includes a schedule for each season, and even programming of the automatic sprinkler timer upon request.

9.3 IMPLEMENTATION OVER THE PAST FIVE YEARS

Each DMM listed above is discussed below including the following details:

- Nature Description of the DMM program (e.g., the dollar value for individual toilet replacements, the process used to inform customers of a landscape water budget program, or the content of a school education program.)
- Extent Quantification of the implementation of the DMM (e.g., the number of customers who have used the toilet rebate program, the number of large landscape accounts that have been assigned a water budget, or the number of school presentations given by the WRA). In addition, extent includes a description of the methods used to estimate the expected water savings from DMMs, or the agency's implementation plan for a particular DMM.

A summary table on the following page shows the implementation from 2011 to 2015 along with current budget allocations.

			TOTAL
CUWCC BMP	Program	Unit	2011-2015
1	Water Waste Ordinances	In Effect	
1	Metering	No unmetered	
1	Conservation Pricing	Tier Rates - Single Family	
1	Water Conservation Coordinator		
2.1	Newsletter and Articles	# of articles published	38
2.1	Flyers/ Bill Inserts	# reached	161,900
2.1	Website	# reached	2,600
2.1	Booths at Festivals	# of attendees	6,200
2.1	Email	email sent	675
2.2	School classroom presentations	# students reached	700
2.2	Large School Assemblies	# students reached	3600
2.2	Field Trips to WTP and WWTP	# students reached	350
2.2	Focus on Water Career Education	# students reached	425
3	Surveys- Residential Single Family	# surveys	1,547
3	Surveys- Residential Multi Family	# surveys	184
	Plumbing Retrofits Single Family		
3	(showerhead/faucet aerators)	# replaced	1,642
	Plumbing Retrofits Multi Family		
3	(showerheads/faucet aerators)	# replaced	161
	High Efficiency Clothes Washers HECW		
3	Rebates (\$100)	# replaced	280
	Water Sense Specification (WSS) Toilets		
3	Rebates	# replaced	995
3	Water Softener Replacement Program	# replaced	319
3	Residential Bill Comparison	total hh reached	3,050
3	High Bill Contact Programs	total hh reached	3,950
3	Notification of Leaks	total hh reached	1,150
4	Commercial High-Efficiency Toilets	# replaced	50
	Commercial High - Efficiency Single Load		
4	Clothes Washers	# replaced	2
4	Green Business Certification	# of businesses	11
4	The Hotel Program	# of hotels	2
	Landscape Irrigation Hardware Rebate		
5	Program	# of rebates	89
5	Turf Removal Program	sq ft removed	88,000
5	Landscape Water Surveys	# of surveys	6
5	Custom Sprinkler Schedule	# reached	6
5	Landscape Classes	# of attendees	400
5	Landscape Plans	# downloads	UNK

WATER WASTE PREVENTION ORDINANCES

The ordinances were originally created as a response to the multiple dry years of the early 1990's but have continued to support sustainable water supply by prohibiting water wasting activities, which include:

- Indiscriminate or excessive water use, which results in water waste.
- Washing of cars, buildings, or exterior surfaces without the use of a quick-acting, positive shutoff nozzle.
- Use of potable water to irrigate turf, lawns, gardens, or ornamental landscaping between 9:00 a.m. and 5:00 p.m. by means other than drip irrigation or hand watering with a quick-acting, positive shut-off nozzle.
- Use of potable water to wash sidewalks or roadways when the use of airblowers or sweeping would provide a reasonable alternative.
- Allowing water waste caused by easily correctable leaks, breaks, or malfunctions, after a reasonable time within which to correct the problem.
- Operation of decorative fountains, even if they use recirculating systems.
- Use of water for construction purposes, such as consolidation of backfill, except when no other method can be used.
- Restaurant water service unless upon customer request.
- Hydrant flushing, except where required for public health and safety.
- Refilling existing private pools, except to maintain water levels.

Hollister, Sunnyslope, the District, and San Benito County have all established "No-Waste" ordinances, policies, and resolutions for their respective jurisdictions. The District has a Water Users Handbook that explains how each water user must take steps to control tailwater. If these policies are not followed, the District has the authority to discontinue service.

In addition to these existing ordinances, Emergency Water Conservation Regulations were passed in 2015 that added outdoor water restrictions. The Emergency regulations also added penalties for violating these restrictions including fines for repeated violations. The Regulations are included in **Appendix I**.

The water waste ordinances are enforceable for retailer customers in the City of Hollister and Sunnyslope. Enforcement costs are a part of each agency's overhead.

The WRA handles complaints of water waste or pursues water waste violations if observed by staff. The WRA issues 'Water Waste' violation cards and follows up with letters to the violators and offers assistance to correct the problem.

In 2015, due to drought awareness and the Emergency Water Conservation Regulations imposed by the state, the response from the public was increased. The WRA fielded approximately 75 phone calls from April through December 2015 relating to water waste. In the past, there have been an average of four calls per year.

METERING

Both Hollister and Sunnyslope meter all customers within their service areas and both retailers have a meter replacement program.

Hollister has been replacing approximately 700 to 800 meters annually, about 10 percent of total connections. As of early 2008, nearly half of the City's old meters have been replaced with new meters that allow reading through a radio. Hollister is making continuous efforts to identify the number of accounts by specific customer type, including installation of dedicated landscape meters for customers who had mixed-use meters. Meter installation costs are part of new service connection fees.

Sunnyslope began the meter replacement program about 10 years ago, replacing up to 600 meters annually, 11 percent of total connections. Sunnyslope's goal is to replace any meter older than 15 years to ensure meter accuracy. In Fiscal year 14/15, approximately 350 water meters were replaced; Sunnyslope added staff to assist with this maintenance task in January 2015.

CONSERVATION PRICING

Both the City and Sunnyslope use a tiered rate structure for single family residences, where efficient water use is billed at a low price and higher water use billed at progressively higher prices. Both entities assess a monthly service charge based on water meter size, plus a monthly consumption rate based on the amount of water consumed.

The monthly consumption rates for single-family residential customers are an inclining block with three tiers, while non-single-family customers are charged one rate for all water consumption. The City and Sunnyslope tiers and rates are included in **Appendix K**.

The current Sunnyslope water rates were approved by the Board of Directors on August 6, 2013 by Ordinance No. 73 and took effect on December 21, 2015.

Comparison with previous average usage rates might provide some information regarding the effectiveness of changing from non-conserving to conservation pricing. It is assumed that the economic incentive to customers to conserve water under conservation pricing structures is sufficient to make this program efficient.

It is expected that most of the conservation savings will occur with the largest water users, who will see larger benefits for conserving water. The expected annual water savings is 100 AFY, compared to the scenario where non-conserving pricing is used.

PUBLIC EDUCATION AND OUTREACH

Public outreach is central to the HUA water conservation efforts. These ongoing activities were ramped up in response to the State mandated water conservation. Specific activities include:

• Newsletter articles on conservation - These articles are included as Appendix L.

- Flyers and/or brochures, bill stuffers, messages printed on bill, information packets. The flyers are included as **Appendix L**.
- Development and update of a website with resources for water conservation: <u>www.wrasbc.org</u>. The website provides details about ongoing water conservation programs and has three different water wise landscape plans available for download.
- Booths at Children's Festivals
- Engagement with the community through responsiveness to emailed questions and concerns
- Water Awareness Festival in May

The total budget approved for the fiscal year 2014/15 was \$28,600, for meeting coordination and materials. Three agencies (Hollister, Sunnyslope, and the District) split the costs. During the recent drought, the budget was expanded by \$45,000 in response to the state mandated reductions. Much of the increased spending focused on informing customers of the state mandatory water conservation rules.

The full time water conservation coordinator records the number and type of outreach activities. Newsletters are sent with water bills and are estimated to reach 40,000 people per year. Booths at festivals reached over 1,400 people in 2015. Other outreach includes the website and email communication which reached about 900 people in 2015.

While there is no direct way to quantify public outreach, it is the foundation for all other programs. With methods to advertise and connect customers to other programs and information, all other demand management measures would be less effective. In addition, the expanded public outreach in response to the drought shows a direct connect between increased public outreach and decreased water use.

SCHOOL EDUCATION AND OUTREACH

The WRA also provides specific school focus outreach including:

- Presentations to school groups (both classroom and large assemblies
 - Water Cycle presentation to 4 and 5th graders
 - Water and Your World presentation to elementary students
- Field trips to the Water Treatment Plant and Wastewater Treatment Plant

In May 2015, the WRA was awarded a grant of \$17,000 for the California Board of Education to focus on education of careers in water resources. The purpose of the grant is to provide ways to expose high school students to the field through additional courses at Gavilan community college and field trips to the WTP and WWTP.

The fiscal year 2014/15 budget allocated \$3,980 to school education. The grant for water resources careers brings the total school outreach budget to \$20,980. The number of students who have participated in these school programs totaled 1,075 in 2015. The school career grant reached 150 students in 2015 and the program is increasing its reach in 2016.

WRA will continue to reach out to students at all grade levels. Before the start of each school year, the Water Conservation Coordinator visits every school in the Hollister Urban Area along with those in San Juan Bautista to alert them of the School Education Program offered through the WRA. The direct effect on water demand is not quantifiable, but there is long-term benefit to educating students on the science and impacts of water supply and conservation.

PROGRAMS TO ASSESS AND MANAGE DISTRIBUTION SYSTEM REAL LOSS

As all connections in Sunnyslope and Hollister are metered, water loss in the HUA is due to leaks, flushing fire hydrants, maintenance of water tanks, metering accuracy, and other small unmetered releases due to maintenance procedures. No additional programs are planned to further manage water distribution system losses.

WATER CONSERVATION PROGRAM COORDINATION AND STAFFING SUPPORT

The WRA conservation coordinator's duties focus primarily on ongoing programs within the District to encourage wise water use among the agricultural community and within the Hollister Urban Area. The duties of this position (and any support staff, as necessary) include the following:

- Coordination and oversight of conservation programs and BMP implementation
- Preparation and submittal of the CUWCC BMP Implementation reports
- Communication and promotion of water conservation issues to agency senior management
- Coordination of agencies' conservation programs with operations and planning staff
- Preparation of annual conservation budget
- Attendance at Bay Area Water Conservation Coordinator Meetings with representatives from the CUWCC
- Reporting to the governing bodies of the participatory agencies on the progress of the Water Conservation Program.

As required by USBR, the WRA coordinator also enters water conservation data to the CUWCC database for Sunnyslope, the District, and San Juan Bautista. Hollister's Utility Technician, a certified and functional Conservation Practitioner, enters this information into the CUWCC's database on behalf of the City.

The total budget for the fiscal year 2014/15 is \$95,000 for water conservation staff costs. The water conservation coordinator works on behalf of the WRA which included Hollister, Sunnyslope, San Juan Bautista and the District. Like public outreach, this demand management measure provides a foundation for all other programs. Having key personnel to coordinate ongoing programs and begin new initiatives is critical for continued water use efficiency. The Conservation Coordinator will continue to oversee water conservation activities for the HUA. To gauge the effectiveness of this DMM, the conservation coordinator and Hollister staff will continue to document the number of programs, materials and attendance at water conservation activities. The benefits of a coordinator are indirect and the water savings due to this DMM cannot be quantified.

Residential Surveys

This DMM involves assisting customers with leak detection and minimization. This may include, but is not limited to: a water conservation survey, water efficiency suggestions and/or inspection, and provision of showerheads and faucet aerators that meet current Water Sense specifications. The primary focus is older neighborhoods with pre-1980 plumbing and the second priority is other pre-1992 housing. Houses constructed after 1992 were required by state building codes to utilize water conserving plumbing fixtures. The program is marketed through advertising in bill inserts, bill messages, and newsletters. During the water survey, water conservation staff performs the following:

- Check for leaks, including toilets, faucets, and meter check
- Check showerhead flow rates, aerator flow rates, and offer to replace or recommend replacement, as necessary
- Check toilet flow rates and direct customer to ultra low flush toilet (ULFT) replacement programs, as necessary, and replace leaking toilet flappers and floats if applicable
- Check irrigation system and timers
- Review or develop customer irrigation schedule
- Evaluate water softener operations and test water hardness to ensure proper settings
- Promote the retrofit program and provide other information on local water resource topics

Surveys require between 30 and 90 minutes. For each dwelling unit, a Water Conservation Assistant completes a customer data form (including number of people per household, number of bathrooms, age of clothes washer and water softener, and approximate landscaped area square footage). These data are used to analyze the customer's water use for both pre- and post-audit conditions, and to refine the program. The results of the residential water survey are provided to the customer with water saving recommendations and specific local information packets prepared as part of the public information program described for DMM 7. The individual contacts made during the survey are used to actively promote the other programs and services offered by the Water Conservation Program, including retrofit and rebate programs offered under other BMPs. Both English and Spanish speaking persons conduct the surveys, and both English and Spanish language materials are available. The form used in the survey is shown in **Appendix L**.

The annual budget for both residential surveys and retrofits is \$40,500. This budget amount assumes \$72.00 per residence is available for the program. From 2011-2015, over 1,700 residences participated.

Based on available information, the potential water savings from this BMP are estimated to be 20 to 30 gpd and 18 to 28 gpd for single family and multi-family residences, respectively. Based on the surveys completed, approximately 38 to 58 AF have been saved since 2011. It is expected that the number of surveys per year will decline with the decrease in older residences that have not completed these surveys.

REBATES AND RETROFITS

The WRA provides several rebates and plumbing retrofits for residential customers, including:

- Plumbing retrofits (shower heads, aerators in faucets and free hose nozzles)
- High Efficiency Clothes Washers (HECW) Rebates
- Water Sense Specification (WSS) toilets
- Water Softeners (demolishing)

The rebate programs have been very active and successful. The total annual 2015 budget is \$15,800. The three major programs (HECW, low flow toilets, and water softeners) have all seen great success in the past but the number of rebates issued has dwindled from 2011 to 2015. Water savings from these programs has totaled 130 AFY (2.5 percent of total demand).

The HECW rebate is \$100 per washer, and the budget in 2015 was \$8,000. Since 2011, 280 rebates for HECW have been issued. The CUWCC reports a water savings estimate of 5,250 gallons per year (0.2 AFY) per high efficiency washing machine, for a total savings of 56 AFY since 2011 (Todd 2011). The number of washers replaced from 2007-2010 was significantly higher, 729 units. The slowdown of rebates for HECW may be an indication that the market is becoming saturated.

For WSS toilets, the financial incentive currently is \$75 per toilet, and an additional \$10 is given when residents deliver their old toilet to the District, as administrator of the program. In addition, the WRA provides a free toilets by appointment, limited to two free toilets per residence, unless a WRA representative inspects the property to confirm more than two toilets are required. In the past, this program has been extremely successful, with over 6,000 ULFTs installed from 2001 to 2010. From 2011 to 2015, only 995 toilets rebates were issued. Projected total annual water savings from toilet retrofits at full implementation are 20 gpcd each or 66.87 AFY for rebates issued (2011-2015), both in water demand and wastewater generation. The fiscal year 2014/15 budget for the WRA is \$ \$25,000for materials, rebates, and advertising costs. The decrease in rebates and budget are another indication that the area already has many water saving devices with limited additional water savings potential.

Since 2007, WRA has conducted a water softener rebate program that encourages people to upgrade from their timer-based models (pre-1999) to demand-initiated regenerating (DIR) models or to demolish these older softeners with no replacement. A shared goal of the District, City and Sunnyslope is to reduce salt loading to wastewater and thereby help maintain groundwater quality and support water recycling. The program includes water softener checks as part of the home water audit programs. It also provides the public with information about DIR and exchange-type water softeners, encouraging replacement of less efficient timer models. Currently, the rebate offer is \$150 (per household) for a water softener replacement, \$250 for a water softener replacement with offsite service, and \$300 for a water softener demolition. The water softener rebates are funded by a grant. It is estimated these rebates save 600 gallons per month per household. From 2011-2015, 319 rebates were issued, for an estimated total savings of 7 AFY.

Participation from the public in various residential rebate programs has declined in recent years and may indicate saturation. The WRA and Hollister estimate that 70 percent of toilets in the HUA are low flow toilets.

This DMM was budgeted for 200 rebates for the current fiscal year. The fiscal year budget approved by the WRA is \$20,000 for high efficiency washing machine rebate program, including a separate budget of approximately \$6,500 for Hollister and Sunnyslope, and a budget of \$6,800 for the District.

OTHER RESIDENTIAL PROGRAMS

In addition to rebate and retrofit programs, there are demand management measures aimed at residential customer education and outreach. The agencies revised their bills to reflect a comparison of 2013 water consumption and current consumption for customers to gauge their reduction efforts. The WRA also alerts residential users if the monthly bill is higher than a pre-determined threshold. This helps the residential user identify leaks or changes in water use. If a leak is detected on a customer's property, they are alerted so they can repair the leak and avoid further water waste.

The WRA included water use comparisons for over 3,000 customers over the last five years. The WRA also contacted 3,950 customers directly over this time to alert them of their high water use. This program has greatly expanded in the last few years from 500 customers in 2011 to 1,500 customers in 2015. As part of this program and others, 1,150 customers were notified of identified leaks.

There is no single budget amount for these programs which are administered by the water conservation coordinator and agency staff.

The direct water savings cannot be calculated but it is assumed these program reduces water waste and system water loss significantly.

COMMERCIAL, INDUSTRIAL, AND INSTITUTIONAL PROGRAMS

The WRA works with businesses to encourage water conservation. The two main programs include the Green Business Certification which recognizes and promotes businesses and government agencies that volunteer to operate in a more environmentally responsible way. The other program serves hotels and provides table cards to hotels and motels that allow guests to have linens washed only upon request.

These programs are conducted jointly with SBC Chamber of Commerce. The WRA works closely with their partners to establish policies that are both business friendly and promote environmental stewardship. As part of this partnership, they produce the TV show "Going Green" which is aired on the Community Media Access Partnership through the local cable provider (Charter). This show discusses "green" topics including water conservation both locally and worldwide.

There is no single budget amount for these programs administered by the water conservation coordinator.

LANDSCAPE WATER SURVEYS

A landscape water survey includes a check of an irrigation system and timers for maintenance and repairs needs, development of a customer irrigation schedule, reviewing scheduling with the customer, and providing the customer with an evaluation.

During a survey, the WRA checks irrigation schedules to see if they are adjusted for the season, checks/adjust sprinkler heads to make sure landscape is being irrigated and not fences or walkways, etc., develops an irrigation schedule to follow for the year, and makes recommendations to upgrade or repair equipment.

Hollister has a landscape ordinance that pertains to new and existing single family homes, and has adopted the model water efficiency landscape ordinance (MWELO) to promote landscape irrigation efficiency. The City is also considering a financial incentive program to help homeowners to convert landscaping toward more water efficiency (e.g., landscape materials, irrigation conversions, automatic controllers, etc.)

The WRA water conservation coordinator offers water use surveys and audits to single family residences, which are modified versions of audits offered to large landscape customers. The WRA also publishes a newsletter biannually entitled, "Water Conservation Update", included in **Appendix L.** The newsletter provides landscape water conservation information, and suggests seasonal water conservation measures such as turning off irrigation systems in the fall. WRA also offers free irrigation inspections in the spring and irrigation controller assistance in the fall. The WRA website provides useful tips for outside water conservation, a Watering Index to guide irrigation, and a Residential Lawn Watering Guide. The website also promotes a free custom sprinkler schedule.

From 2011 to 2015, six surveys were performed. The proposed annual budget for all residential surveys is \$6,500. The water savings of this measure would depend on the existing volume of irrigation and the implemented reduction of irrigation. The 2010 UWMP estimated 25-50 AFY savings for this program.

The City of Hollister and the County have adopted Large Landscape Conservation Requirements, including the MWELO. The HUA entities will continue to implement this DMM through annual review of customers' water use, and by offering on-site follow-up evaluations to customers whose total water use exceeds their total annual water budget. The overall target of providing large landscape audits is 3 percent of existing accounts each year.

Landscape Irrigation Hardware Rebate Program

The WRA has rebates on hose timers, rain sensors and MP Rotator irrigation nozzles. Information on how residents apply for this rebate and what models are available are included in **Appendix L**.

The rebate of 50 percent of the cost of qualifying products, up to \$100. A total 89 rebates have been granted from 2011 to 2015. The budget for Fiscal year 14/15 was \$9,000.

Turf Removal Program

In July 2014 the WRA added a Turf Removal Program to encourage customers to remove high water use turf areas from residential parcels. This program complements the irrigation hardware rebates and free water efficient landscape plans. The turf removal program includes extensive public outreach in both Spanish and English.

In Fiscal Year 2015/16 the program expanded from offering a \$1 per square of turf removed up to 500 square feet to 1,000 square feet. The only land cover allowed in the area where the turf is removed includes drought tolerant or native plants, permeable hardscapes and/or a combination. As of November 2015, over 88,000 square feet of turf have been removed in the Hollister Urban Area. The total budget for Fiscal year 2014/15 was \$28,000.

In fiscal year 2015/16, the WRA received another \$100K of funding to support the Turf Removal Program. It is anticipated that by the end of the Fiscal Year over 200,000 square feet of turf will be removed and either replaced with hardscape, drought tolerant plants or a combination of both. The WRA has had several customers apply for the state's turf removal rebate program. While the rate of turf removal requests may slow after the drought, the water savings effects of the removed drought will continue unless new turf is planted.

IRRIGATION EDUCATION

The District, in collaboration with the WRA, has been offering a series of classes since 2009 on irrigation efficiency and other agriculture practices. These workshops provide concepts, tools, and examples for optimizing irrigation and nitrogen management efficiency in row, tree, and greenhouse crop production. The classes also focus on keeping records and acquiring data needed for water quality regulation and reporting. The WRA also offers classes to residential customers. These classes instruct customers on topics such as composting, implementing efficient irrigation practices, and converting landscapes to be water wise. From 2011 to 2015, there were four classes per year, for a total of 16 classes.

Custom Sprinkler Schedule

A Water Conservation Specialist will design a watering schedule tailored to customer habits, sprinkler's output, and the seasonal water needs of the individual lawn and garden. The plan is free and includes a schedule for each season plus programming of the automatic sprinkler timer.

Six schedules have been developed for large landscapes customers from 2011 to 2015. It is estimated a custom sprinkler schedule could reduce irrigation by 20 to 30 gallons per day. This program can be expanded by reaching out directly to large landscape as well as residential customers. Schedules are created for residential customers through the water survey program.

9.4 PLANNED IMPLEMENTATION TO ACHIEVE WATER USE TARGETS (RETAIL AGENCIES ONLY)

Water conservation efforts over the past five years have resulted in numerous plumbing and hardware retrofits in older buildings. These existing efforts (combined with new plumbing codes that require new developments to have water saving fixtures) have resulted in a large percent of buildings (both residential and commercial) with water saving technology. While these improvements have resulted in decreased water demand, the future potential gains from the rebate and retrofit programs may be limited.

In response to the State mandated water reduction due to the drought, the WRA and agencies stepped up their public outreach. They increased bill inserts, contacted high water users, and increased the advertisement of existing programs in multiple languages. In addition, the WRA also used public outreach to alert users to the new Emergency Water Conservation Regulations. These regulations focused on implementing efficient irrigation and outdoor water use. The increased public outreach and the focus on reducing water waste outdoors had measurable results. The agencies were able to reduce water demand in 2015 by more than 25 percent.

The WRA plans to continue its focus on public outreach and education about irrigation efficiency. While these programs are difficult to account per unit water savings, the overall effect of reducing demand during the drought demonstrates the overall water savings.

9.5 MEMBERS OF THE CALIFORNIA URBAN WATER CONSERVATION COUNCIL

The City of Hollister is signatory to the CUWCC MOU for urban water conservation in California. Signatory agencies agree to follow guidelines for developing, implementing and evaluating water conservation BMPs included in their UWMP. As a signatory to the CUWCC MOU, Hollister reports implementation of BMPs directly to the CUWCC database (http://bmp.cuwcc.org/). Although the District and Sunnyslope have not signed the MOU, they also report BMP implementation to the CUWCC as requested by the USBR through the CVP contract agreement. Information on BMPs by the District and Sunnyslope is compiled by the WRA and entered into the CUWCC database by the WRA.

Signatories to the CUWCC MOU are required to report the status of each BMP implementation every two years. Reporting includes the status for two consecutive years. In addition to the CUWCC reporting requirements, the Water Conservation Coordinator reports to the WRA during the WRA meetings, providing the status of BMP implementation, ongoing activities, and scheduled events. The WRA funds water conservation activities through contributions from Hollister, Sunnyslope, the District, and to a lesser extent, the City of San Juan Bautista.

This Page Intentionally Blank

10. COMPLETED UWMP CHECKLIST

The UWMP checklist is found on the following pages.

This Page Intentionally Blank

Table 10-1 Retail:	ail: Notification to Cities and Counties		
City Name	60 Day Notice	Notice of Public Hearing	
A	dd additional rows as neec	led	
San Jaun Bautista			
County Name Drop Down List	60 Day Notice	Notice of Public Hearing	
A	dd additional rows as neec	led	
San Benito County	~		
NOTES:			

Table 10-1 Wholesale: Notification to Cities and Counties (select one)					
	Supplier has notified more than 10 cities or counties in accordance with CWC 10621 (b) and 10642. Completion of the table below is not required. Provide a separate list of the cities and counties that were notified.				
	Provide the page or loc	ation of this list in the UWMP.			
V	Supplier has notified 10 or fewer cities or counties. Complete the table below.				
City Name	60 Day Notice Notice of Public Hearing				
Add additional rows as needed					
San Jaun Bautista	\checkmark				
County Name Drop Down List	60 Day Notice	Notice of Public Hearing			
	Add additional rov	ws as needed			
San Benito County	\checkmark	\			
NOTES:	NOTES:				

Checklist Arranged by Water Code Section

CWC Section	UWMP Requirement	Subject	Guidebook Location	UWMP Location
10608.20(b)	Retail suppliers shall adopt a 2020 water use target using one of four methods.	Baselines and Targets	Section 5.7 and App E	Section 5.6
10608.20(e)	Retail suppliers shall provide baseline daily per capita water use, urban water use target, interim urban water use target, and compliance daily per capita water use, along with the bases for determining those estimates, including references to supporting data.	Baselines and Targets	Chapter 5 and App E	Section 5.7
10608.22	Retail suppliers' per capita daily water use reduction shall be no less than 5 percent of base daily per capita water use of the 5 year baseline. This does not apply is the suppliers base GPCD is at or below 100.	Baselines and Targets	Section 5.7.2	Section 5.5
10608.24(a)	Retail suppliers shall meet their interim target by December 31, 2015.	Baselines and Targets	Section 5.8 and App E	Section 5.7
1608.24(d)(2)	If the retail supplier adjusts its compliance GPCD using weather normalization, economic adjustment, or extraordinary events, it shall provide the basis for, and data supporting the adjustment.	Baselines and Targets	Section 5.8.2	Section 5.7
10608.26(a)	Retail suppliers shall conduct a public hearing to discuss adoption, implementation, and economic impact of water use targets.	Plan Adoption, Submittal, and Implementation	Section 10.3	Section 2.1
10608.36	Wholesale suppliers shall include an assessment of present and proposed future measures, programs, and policies to help their retail water suppliers achieve targeted water use reductions.	Baselines and Targets	Section 5.1	Section 5.7 and Section 9
10608.40	Retail suppliers shall report on their progress in meeting their water use targets. The data shall be reported using a standardized form.	Baselines and Targets	Section 5.8 and App E	Section 5.7 and Appendix E
10620(b)	Every person that becomes an urban water supplier shall adopt an urban water management plan within one year after it has become an urban water supplier.	Plan Preparation	Section 2.1	Section 2.1
10620(d)(2)	Coordinate the preparation of its plan with other appropriate agencies in the area, including other water suppliers that share a common source, water management agencies, and relevant public agencies, to the extent practicable.	Plan Preparation	Section 2.5.2	Section 2.2
10620(f)	Describe water management tools and options to maximize resources and minimize the need to import water from other regions.	Water Supply Reliability Assessment	Section 7.4	Section 7.4
10621(b)	Notify, at least 60 days prior to the public hearing, any city or county within which the supplier provides water that the urban water supplier will be reviewing the plan and considering amendments or changes to the plan.	Plan Adoption, Submittal, and Implementation	Section 10.2.1	
10621(d)	Each urban water supplier shall update and submit its 2015 plan to the department by July 1, 2016.	Plan Adoption, Submittal, and Implementation	Sections 10.3.1 and 10.4	Section 2.1
10631(a)	Describe the water supplier service area.	System Description	Section 3.1	Section 3.1
10631(a)	Describe the climate of the service area of the supplier.	System Description	Section 3.3	Section 3.3
10631(a)	Indicate the current population of the service area.	System Description and Baselines and Targets	Sections 3.4 and 5.4	Sections 3.4 and 5.3

CWC Section	UWMP Requirement	Subject	Guidebook Location	UWMP Location
10631(a)	Provide population projections for 2020, 2025, 2030, and 2035.	System Description	Section 3.4	Section 3.4
10631(a)	Describe other demographic factors affecting the supplier's water management planning.	System Description	Section 3.4	Section 3.4
10631(b)	Identify and quantify the existing and planned sources of water available for 2015, 2020, 2025, 2030, and 2035.	System Supplies	Chapter 6	Chapter 6
10631(b)	Indicate whether groundwater is an existing or planned source of water available to the supplier.	System Supplies	Section 6.2	Section 6.2
10631(b)(1)	Indicate whether a groundwater management plan has been adopted by the water supplier or if there is any other specific authorization for groundwater management. Include a copy of the plan or authorization.	System Supplies	Section 6.2.2	Section 6.2
10631(b)(2)	Describe the groundwater basin.	System Supplies	Section 6.2.1	Section 6.2
10631(b)(2)	Indicate if the basin has been adjudicated and include a copy of the court order or decree and a description of the amount of water the supplier has the legal right to pump.	System Supplies	Section 6.2.2	Section 6.2
10631(b)(2)	For unadjudicated basins, indicate whether or not the department has identified the basin as overdrafted, or projected to become overdrafted. Describe efforts by the supplier to eliminate the long-term overdraft condition.	System Supplies	Section 6.2.3	Section 6.2
10631(b)(3)	Provide a detailed description and analysis of the location, amount, and sufficiency of groundwater pumped by the urban water supplier for	System Supplies	Section 6.2.4	Section 6.2
	the past five years			
10631(b)(4)	Provide a detailed description and analysis of the amount and location of groundwater that is projected to be pumped.	System Supplies	Sections 6.2 and 6.9	Sections 6.2 and 6.9
10631(c)(1)	Describe the reliability of the water supply and vulnerability to seasonal or climatic shortage.	Water Supply Reliability Assessment	Section 7.1	Section 7.1
10631(c)(1)	Provide data for an average water year, a single dry water year, and multiple dry water years	Water Supply Reliability Assessment	Section 7.2	Section 7.2
10631(c)(2)	For any water source that may not be available at a consistent level of use, describe plans to supplement or replace that source.	Water Supply Reliability Assessment	Section 7.1	Section 7.1
10631(d)	Describe the opportunities for exchanges or transfers of water on a short-term or long- term basis.	System Supplies	Section 6.7	Section 6.7
10631(e)(1)	Quantify past, current, and projected water use, identifying the uses among water use sectors.	System Water Use	Section 4.2	Section 4.1 and 4.2
10631(e)(3)(A)	Report the distribution system water loss for the most recent 12-month period available.	System Water Use	Section 4.3	Section 4.4
10631(f)(1)	Retail suppliers shall provide a description of the nature and extent of each demand management measure implemented over the past five years. The description will address specific measures listed in code.	Demand Management Measures	Sections 9.2 and 9.3	Sections 9.2 and 9.3
10631(f)(2)	Wholesale suppliers shall describe specific demand management measures listed in code, their distribution system asset management program, and supplier assistance program.	Demand Management Measures	Sections 9.1 and 9.3	Sections 9.1 and 9.3

CWC Section	UWMP Requirement	Subject	Guidebook Location	UWMP Location
10631(g)	Describe the expected future water supply projects and programs that may be undertaken by the water supplier to address water supply reliability in average, single- dry, and multiple-dry years.		Section 6.8	Section 6.8
10631(i)	Describe desalinated water project opportunities for long-term supply.	System Supplies	Section 6.6	Section 6.6
10631(j)	CUWCC members may submit their 2013- 2014 CUWCC BMP annual reports in lieu of, or in addition to, describing the DMM implementation in their UWMPs. This option is only allowable if the supplier has been found to be in full compliance with the CUWCC MOU.	Demand Management Measures	Section 9.5	NA
10631(j)	Retail suppliers will include documentation that they have provided their wholesale supplier(s) – if any - with water use projections from that source.	System Supplies	Section 2.5.1	NA
10631(j)	Wholesale suppliers will include documentation that they have provided their urban water suppliers with identification and quantification of the existing and planned sources of water available from the wholesale to the urban supplier during various water year types.	System Supplies	Section 2.5.1	NA
10631.1(a)	Include projected water use needed for lower income housing projected in the service area of the supplier.	System Water Use	Section 4.5	Section 4.5
10632(a) and 10632(a)(1)	Provide an urban water shortage contingency analysis that specifies stages of action and an outline of specific water supply conditions at each stage.	Water Shortage Contingency Planning	Section 8.1	Section 8.1
10632(a)(2)	Provide an estimate of the minimum water supply available during each of the next three water years based on the driest three- year historic sequence for the agency.	Water Shortage Contingency Planning	Section 8.9	Section 8.9
10632(a)(3)	Identify actions to be undertaken by the urban water supplier in case of a catastrophic interruption of water supplies.	Water Shortage Contingency Planning	Section 8.8	Section 8.8
10632(a)(4)	Identify mandatory prohibitions against specific water use practices during water shortages.	Water Shortage Contingency Planning	Section 8.2	Section 8.2
10632(a)(5)	Specify consumption reduction methods in the most restrictive stages.	Water Shortage Contingency Planning	Section 8.4	Section 8.2 and 8.4
10632(a)(6)	Indicated penalties or charges for excessive use, where applicable.	Water Shortage Contingency Planning	Section 8.3	Section 8.3
10632(a)(7)	Provide an analysis of the impacts of each of the actions and conditions in the water shortage contingency analysis on the revenues and expenditures of the urban water supplier, and proposed measures to overcome those impacts.	Water Shortage Contingency Planning	Section 8.6	Section 8.6
10632(a)(8)	Provide a draft water shortage contingency resolution or ordinance.	Water Shortage Contingency Planning	Section 8.7	Section 8.7
10632(a)(9)	Indicate a mechanism for determining actual reductions in water use pursuant to the water shortage contingency analysis.		Section 8.5	Section 8.5
10633	For wastewater and recycled water, coordinate with local water, wastewater, groundwater, and planning agencies that operate within the supplier's service area.	System Supplies (Recycled Water)	Section 6.5.1	Section 6.5

CWC Section	UWMP Requirement	Subject	Guidebook Location	UWMP Location
10633(a)	Describe the wastewater collection and treatment systems in the supplier's service area. Include quantification of the amount of wastewater collected and treated and the methods of	System Supplies (Recycled Water)	Section 6.5.2	Section 6.5
10633(b)	wastewater disposal. Describe the quantity of treated wastewater that meets recycled water standards, is being discharged, and is otherwise available for use in a recycled water project.	System Supplies (Recycled Water)	Section 6.5.2.2	Section 6.5
10633(c)	Describe the recycled water currently being used in the supplier's service area.	System Supplies (Recycled Water)	Section 6.5.3 and 6.5.4	Section 6.5
10633(d)	Describe and quantify the potential uses of recycled water and provide a determination of the technical and economic feasibility of those uses.	System Supplies (Recycled Water)	Section 6.5.4	Section 6.5
10633(e)	Describe the projected use of recycled water within the supplier's service area at the end of 5, 10, 15, and 20 years, and a description of the actual use of recycled water in comparison to uses previously projected.	System Supplies (Recycled Water)	Section 6.5.4	Section 6.5
10633(f)	Describe the actions which may be taken to encourage the use of recycled water and the projected results of these actions in terms of acre-feet of recycled water used per year.	System Supplies (Recycled Water)	Section 6.5.5	Section 6.5
10633(g)	Provide a plan for optimizing the use of recycled water in the supplier's service area.	System Supplies (Recycled Water)	Section 6.5.5	Section 6.5
10634	Provide information on the quality of existing sources of water available to the supplier and the manner in which water quality affects water management strategies and supply reliability		Section 7.1	Section 7.1
10635(a)	Assess the water supply reliability during normal, dry, and multiple dry water years by comparing the total water supply sources available to the water supplier with the total projected water use over the next 20	Water Supply Reliability Assessment	Section 7.3	Section 7.3
10635(b)	Vears. Provide supporting documentation that Water Shortage Contingency Plan has been, or will be, provided to any city or county within which it provides water, no later than 60 days after the submission of the plan to DWR.		Section 10.4.4	Section 2.1 and Section 8.1
10642	Provide supporting documentation that the water supplier has encouraged active involvement of diverse social, cultural, and economic elements of the population within the service area prior to and during the preparation of the plan.	Plan Preparation	Section 2.5.2	Section 2
10642	Provide supporting documentation that the urban water supplier made the plan available for public inspection, published notice of the public hearing, and held a public hearing about the plan.	Plan Adoption, Submittal, and Implementation	Sections 10.2.2, 10.3, and 10.5	Section 2.1
10642	The water supplier is to provide the time and place of the hearing to any city or county within which the supplier provides water.	Plan Adoption, Submittal, and Implementation	Sections 10.2.1	Section 2 And Appendix A
10642	Provide supporting documentation that the plan has been adopted as prepared or modified.	Plan Adoption, Submittal, and Implementation	Section 10.3.1	Section 2 And Appendix A
10644(a)	Provide supporting documentation that the urban water supplier has submitted this UWMP to the California State Library.	Plan Adoption, Submittal, and Implementation	Section 10.4.3	Section 2 And Appendix A

CWC Section	UWMP Requirement	Subject	Guidebook Location	UWMP Location
10644(a)(1)	Provide supporting documentation that the urban water supplier has submitted this UWMP to any city or county within which the supplier provides water no later than 30 days after adoption.		Section 10.4.4	Section 2 And Appendix A
10644(a)(2)	The plan, or amendments to the plan, submitted to the department shall be submitted electronically.	Plan Adoption, Submittal, and Implementation	Sections 10.4.1 and 10.4.2	Section 2 And Appendix A
10645	Provide supporting documentation that, not later than 30 days after filing a copy of its plan with the department, the supplier has or will make the plan available for public review during normal business hours.	Plan Adoption, Submittal, and Implementation	Section 10.5	Section 2 And Appendix A
10620(b)	Every person that becomes an urban water supplier shall adopt an urban water management plan within one year after it has become an urban water supplier.	Plan Preparation	Section 2.1	Section 2
10620(d)(2)	Coordinate the preparation of its plan with other appropriate agencies in the area, including other water suppliers that share a common source, water management agencies, and relevant public agencies, to the extent practicable.	Plan Preparation	Section 2.5.2	Section 2
10642	Provide supporting documentation that the water supplier has encouraged active involvement of diverse social, cultural, and economic elements of the population within the service area prior to and during the preparation of the plan.	Plan Preparation	Section 2.5.2	Section 2
10631(a)	Describe the water supplier service area.	System Description	Section 3.1	Section 3.1
10631(a)	Describe the climate of the service area of the supplier.	System Description	Section 3.3	Section 3.3
10631(a)	Provide population projections for 2020, 2025, 2030, and 2035.	System Description	Section 3.4	Section 3.4
10631(a)	Describe other demographic factors affecting the supplier's water management planning.	System Description	Section 3.4	Section 3.4
10631(a)	Indicate the current population of the service area.	System Description and Baselines and Targets	Sections 3.4 and 5.4	Sections 3.4 and 5.4
10631(e)(1)	Quantify past, current, and projected water use, identifying the uses among water use sectors.	System Water Use	Section 4.2	Section 4.2
10631(e)(3)(A)	Report the distribution system water loss for the most recent 12-month period available.	System Water Use	Section 4.3	Section 4.3
10631.1(a)	Include projected water use needed for lower income housing projected in the service area of the supplier.	System Water Use	Section 4.5	Section 4.5
10608.20(b)	Retail suppliers shall adopt a 2020 water use target using one of four methods.	Baselines and Targets	Section 5.7 and App E	Section 5.7 and App F
10608.20(e)	Retail suppliers shall provide baseline daily per capita water use, urban water use target, interim urban water use target, and compliance daily per capita water use, along with the bases for determining those estimates, including references to supporting data.	Baselines and Targets	Chapter 5 and App E	Chapter 5 and App F

CWC Section	UWMP Requirement	Subject	Guidebook Location	UWMP Location
10608.22	Retail suppliers' per capita daily water use reduction shall be no less than 5 percent of base daily per capita water use of the 5 year baseline. This does not apply is the suppliers base GPCD is at or below 100.	Baselines and Targets	Section 5.7.2	Section 5.7.2
10608.24(a)	Retail suppliers shall meet their interim target by December 31, 2015.	Baselines and Targets	Section 5.8 and App E	Section 5 and App F
1608.24(d)(2)	If the retail supplier adjusts its compliance GPCD using weather normalization, economic adjustment, or extraordinary events, it shall provide the basis for, and data supporting the adjustment.	Baselines and Targets	Section 5.8.2	Section 5.8.2
10608.36	Wholesale suppliers shall include an assessment of present and proposed future measures, programs, and policies to help their retail water suppliers achieve targeted	Baselines and Targets	Section 5.1	Section 5.1
10608.40	water use reductions. Retail suppliers shall report on their progress in meeting their water use targets. The data shall be reported using a standardized form.	Baselines and Targets	Section 5.8 and App E	Section 5 and App F
10631(b)	Identify and quantify the existing and planned sources of water available for 2015, 2020, 2025, 2030, and 2035.	System Supplies	Chapter 6	Chapter 6
10631(b)	Indicate whether groundwater is an existing or planned source of water available to the supplier.	System Supplies	Section 6.2	Section 6.2
10631(b)(1)	Indicate whether a groundwater management plan has been adopted by the water supplier or if there is any other specific authorization for groundwater management. Include a copy of the plan or	System Supplies	Section 6.2.2	Section 6.2.2
10631(b)(2)	authorization. Describe the groundwater basin.	System Supplies	Section 6.2.1	Section 6.2
10631(b)(2)	Indicate if the basin has been adjudicated and include a copy of the court order or decree and a description of the amount of water the supplier has the legal right to pump.	System Supplies	Section 6.2.2	Section 6.2
10631(b)(2)	For unadjudicated basins, indicate whether or not the department has identified the basin as overdrafted, or projected to become overdrafted. Describe efforts by the supplier to eliminate the long-term overdraft condition.	System Supplies	Section 6.2.3	Section 6.2
10631(b)(3)	Provide a detailed description and analysis of the location, amount, and sufficiency of groundwater pumped by the urban water supplier for the past five years	System Supplies	Section 6.2.4	Section 6.2
10631(b)(4)	Provide a detailed description and analysis of the amount and location of groundwater that is projected to be pumped.	System Supplies	Sections 6.2 and 6.9	Sections 6.2 and 6.9
10631(d)	Describe the opportunities for exchanges or transfers of water on a short-term or long- term basis.	System Supplies	Section 6.7	Section 6.7
10631(g)	Describe the expected future water supply projects and programs that may be undertaken by the water supplier to address water supply reliability in average, single- dry, and multiple-dry years.		Section 6.8	Section 6.8
10631(i)	Describe desalinated water project opportunities for long-term supply.	System Supplies	Section 6.6	Section 6.6

CWC Section	UWMP Requirement	Subject	Guidebook Location	UWMP Location
10631(j)	Retail suppliers will include documentation that they have provided their wholesale supplier(s) – if any - with water use projections from that source.	System Supplies	Section 2.5.1	Section 2.5.1
10631(j)	Wholesale suppliers will include documentation that they have provided their urban water suppliers with identification and quantification of the existing and planned sources of water available from the wholesale to the urban supplier during various water year types.	System Supplies	Section 2.5.1	Section 2
10633	For wastewater and recycled water, coordinate with local water, wastewater, groundwater, and planning agencies that operate within the supplier's service area.	System Supplies (Recycled Water)	Section 6.5.1	Section 6.5
10633(a)	Describe the wastewater collection and treatment systems in the supplier's service area. Include quantification of the amount of wastewater collected and treated and the methods of wastewater disposal.	System Supplies (Recycled Water)	Section 6.5.2	Section 6.5
10633(b)	Describe the quantity of treated wastewater that meets recycled water standards, is being discharged, and is otherwise available for use in a recycled water project.	System Supplies (Recycled Water)	Section 6.5.2.2	Section 6.5
10633(c)	Describe the recycled water currently being used in the supplier's service area.	System Supplies (Recycled Water)	Section 6.5.3 and 6.5.4	Section 6.5
10633(d)	Describe and quantify the potential uses of recycled water and provide a determination of the technical and economic feasibility of those uses.	System Supplies (Recycled Water)	Section 6.5.4	Section 6.5
10633(e)	Describe the projected use of recycled water within the supplier's service area at the end of 5, 10, 15, and 20 years, and a description of the actual use of recycled water in comparison to uses previously projected.	System Supplies (Recycled Water)	Section 6.5.4	Section 6.5
10633(f)	Describe the actions which may be taken to encourage the use of recycled water and the projected results of these actions in terms of acre-feet of recycled water used per year.	System Supplies (Recycled Water)	Section 6.5.5	Section 6.5
10633(g)	Provide a plan for optimizing the use of recycled water in the supplier's service area.	System Supplies (Recycled Water)	Section 6.5.5	Section 6.5
10620(f)	Describe water management tools and options to maximize resources and minimize the need to import water from other regions.	Water Supply Reliability Assessment	Section 7.4	Section 7.4
10631(c)(1)	Describe the reliability of the water supply and vulnerability to seasonal or climatic shortage.	Water Supply Reliability Assessment	Section 7.1	Section 7.1
10631(c)(1)	Provide data for an average water year, a single dry water year, and multiple dry water years	Water Supply Reliability Assessment	Section 7.2	Section 7.2
10631(c)(2)	For any water source that may not be available at a consistent level of use, describe plans to supplement or replace that	Water Supply Reliability Assessment	Section 7.1	Section 7.1
10634	Source. Provide information on the quality of existing sources of water available to the supplier and the manner in which water quality affects water management strategies and supply reliability		Section 7.1	Section 7.1

CWC Section	UWMP Requirement	Subject	Guidebook Location	UWMP Location
10635(a)	Assess the water supply reliability during normal, dry, and multiple dry water years by comparing the total water supply sources available to the water supplier with the total projected water use over the next 20 years.	Water Supply Reliability Assessment	Section 7.3	Section 7.3
10632(a) and 10632(a)(1)	Provide an urban water shortage contingency analysis that specifies stages of action and an outline of specific water supply conditions at each stage.	Water Shortage Contingency Planning	Section 8.1	Section 8.1
10632(a)(2)	Provide an estimate of the minimum water supply available during each of the next three water years based on the driest three- year historic sequence for the agency.	Water Shortage Contingency Planning	Section 8.9	Section 8.9
10632(a)(3)	Identify actions to be undertaken by the urban water supplier in case of a catastrophic interruption of water supplies.	Water Shortage Contingency Planning	Section 8.8	Section 8.8
10632(a)(4)	Identify mandatory prohibitions against specific water use practices during water shortages.	Water Shortage Contingency Planning	Section 8.2	Section 8.2
10632(a)(5)	Specify consumption reduction methods in the most restrictive stages.	Water Shortage Contingency Planning	Section 8.4	Section 8.4
10632(a)(6)	Indicated penalties or charges for excessive use, where applicable.	Water Shortage Contingency Planning	Section 8.3	Section 8.3
10632(a)(7)	Provide an analysis of the impacts of each of the actions and conditions in the water shortage contingency analysis on the revenues and expenditures of the urban water supplier, and proposed measures to overcome those impacts.	Water Shortage Contingency Planning	Section 8.6	Section 8.6
10632(a)(8)	Provide a draft water shortage contingency resolution or ordinance.	Water Shortage Contingency Planning	Section 8.7	Section 8.7
10632(a)(9)	Indicate a mechanism for determining actual reductions in water use pursuant to the water shortage contingency analysis.		Section 8.5	Section 8.5
10631(f)(1)	Retail suppliers shall provide a description of the nature and extent of each demand management measure implemented over the past five years. The description will address specific measures listed in code.	Demand Management Measures	Sections 9.2 and 9.3	Sections 9.2 and 9.3
10631(f)(2)	Wholesale suppliers shall describe specific demand management measures listed in code, their distribution system asset management program, and supplier assistance program.	Demand Management Measures	Sections 9.1 and 9.3	Sections 9.1 and 9.3
10631(j)	CUWCC members may submit their 2013- 2014 CUWCC BMP annual reports in lieu of, or in addition to, describing the DMM implementation in their UWMPs. This option is only allowable if the supplier has been found to be in full compliance with the CUWCC MOU.	Demand Management Measures	Section 9.5	NA
10608.26(a)	Retail suppliers shall conduct a public hearing to discuss adoption, implementation, and economic impact of water use targets.	Plan Adoption, Submittal, and Implementation	Section 10.3	Section 2
10621(b)	Notify, at least 60 days prior to the public hearing, any city or county within which the supplier provides water that the urban water supplier will be reviewing the plan and considering amendments or changes to the plan.	Plan Adoption, Submittal, and Implementation	Section 10.2.1	Section 2

CWC Section	UWMP Requirement	Subject	Guidebook Location	UWMP Location
10621(d)	Each urban water supplier shall update and submit its 2015 plan to the department by July 1, 2016.	Plan Adoption, Submittal, and Implementation	Sections 10.3.1 and 10.4	Section 2
10635(b)	Provide supporting documentation that Water Shortage Contingency Plan has been, or will be, provided to any city or county within which it provides water, no later than 60 days after the submission of the plan to DWR.	Plan Adoption, Submittal, and Implementation	Section 10.4.4	Section 2
10642	Provide supporting documentation that the urban water supplier made the plan available for public inspection, published notice of the public hearing, and held a public hearing about the plan.	Plan Adoption, Submittal, and Implementation	Sections 10.2.2, 10.3, and 10.5	Section 2
10642	The water supplier is to provide the time and place of the hearing to any city or county within which the supplier provides water.	Plan Adoption, Submittal, and Implementation	Sections 10.2.1	Section 2
10642	Provide supporting documentation that the plan has been adopted as prepared or modified.	Plan Adoption, Submittal, and Implementation	Section 10.3.1	Section 2
10644(a)	Provide supporting documentation that the urban water supplier has submitted this UWMP to the California State Library.	Plan Adoption, Submittal, and Implementation	Section 10.4.3	Section 2
10644(a)(1)	Provide supporting documentation that the urban water supplier has submitted this UWMP to any city or county within which the supplier provides water no later than 30 days after adoption.		Section 10.4.4	Section 2
10644(a)(2)	The plan, or amendments to the plan, submitted to the department shall be submitted electronically.	Plan Adoption, Submittal, and Implementation	Sections 10.4.1 and 10.4.2	Section 2
10645	Provide supporting documentation that, not later than 30 days after filing a copy of its plan with the department, the supplier has or will make the plan available for public review during normal business hours.	Plan Adoption, Submittal, and Implementation	Section 10.5	Section 2

This Page Intentionally Blank

11. REFERENCES

AECOM, Final Program Environmental Impact Report Hollister Urban Area Water and Wastewater, Master Plan and Coordinated Water Supply and Treatment Plan, January 2011.

California Department of Water Resources (DWR), California's Groundwater, Bulletin 118, http://www.water.ca.gov/groundwater/ Last Accessed January 2016a.

California Department of Water Resources (DWR), Climate Change, <u>http://www.water.ca.gov/climatechange/</u>, Last Accessed January 2016b.

California Department of Water Resources (DWR), Climate of Change Fact Sheet, <u>http://www.water.ca.gov/climatechange/docs/062807factsheet.pdf</u>, February 2007, Last Accessed August 2009.

California Department of Water Resources (DWR), Delta Initiatives, <u>http://www.water.ca.gov/deltainit/</u>, Last Accessed January 2016c.

California Department of Water Resources, California Water Plan Update 2013, <u>http://www.waterplan.water.ca.gov/cwpu2013/final/index.cfm</u>, September 2014.

California Department of Water Resources, Guidebook to Assist Urban Water Suppliers to Prepare an Urban Water Management Plan, March 2016d.

California Emergency Management Agency, *Emergency Planning Guidance for Public and Private Water Utilities*,

ttp://www.calema.ca.gov/WebPage/oeswebsite.nsf/0/22933e652ad231b7882574100066cece/\$FILE/H2 o_.pdf,

California Geological Survey (formerly California Division of Mines and Geology), Geologic Map of Monterey 30' x 60' Quadrangle and Adjacent Areas, California: A Digital Database, Publication No. CD 2002-04, 2002.

California State Water Resources Control Board (SWRCB), 2015, Drinking Water MCL: <u>www.waterboards.ca.gov/drinking water/certlic/drinkingwater/MCLsandPHGs.shtml</u>, last updated February 27, 2015, last accessed June 17, 2015.

Cattaneo, Jeff, General Manager San Benito County Water District, personal communication, March 22, 2016.

Clark, William O., Ground Water in Santa Clara Valley California, USGS Water-Supply Paper 519, 1924.

Creegan & D'Angelo, Groundwater Report 1990, prepared for San Benito County Water District, March 12, 1990.

Farrar, C.D., Ground-Water-Level Monitoring Network, Hollister and San Juan Valleys, San Benito County, California, USGS Water Resources Investigations Open-File Report 81-66, prepared in cooperation with the San Benito County Water Conservation and Flood Control District, March 1981.

Faye, Robert E., Mathematical Model of the San Juan Valley Ground-Water Basin, San Benito, California, USGS Water Resources Investigation 58-73, August 1974.

Faye, Robert E., Mathematical Model of the West Bolsa Ground-Water Basin, San Benito County, California, USGS Water-Resources Investigations 76-71, December 1976.

HDR, Hollister Urban Area Water and Wastewater Management Plan, Prepared for City of Hollister, San Benito County, San Benito County Water District, and Sunnyslope County Water District, November 2008.

HDR, San Benito County Water District and City of Hollister Recycled Water Feasibility Update, Prepared for San Benito County Water District and City of Hollister, November 2008b.

Jones & Stokes Associates, Inc., and CH2M Hill, Groundwater Management Plan for the San Benito County Part of the Gilroy-Hollister Groundwater Basin, Final, Prepared for Agency Advisory Group, Hollister, California, April 1998.

Jones & Stokes Associates, Inc., Final Annual Groundwater Report for the 1998-1999 Water Year, prepared for San Benito County Water District, December 20, 1999.

Kennedy/Jenks Consultants, Engineers & Scientists, Groundwater Management Plan Update for the San Benito County Part of the Gilroy-Hollister Groundwater Basin, Prepared for Water Resources Association of San Benito County, July 2003.

Kennedy/Jenks Consultants, Engineers & Scientists, Hollister Area 2008 Urban Area Water Management Plan, Prepared for Sunnyslope County Water District and the City of Hollister, January 2009.

Kilburn, C., Ground-Water Hydrology of the Hollister and San Juan Valleys, San Benito County, California, 1913-1968, United States Geological Survey Open File Report 73-144, 1972.

L.A. Times – Boxtall, Bettina, Federal Appeals Court Backs Restrictions on Delta Water Deliveries, <u>http://www.latimes.com/science/la-me-delta-salmon-20141223-story.html</u>, December 22, 2014.

Luhdorff & Scalmanini Consulting Engineers, San Benito County Ground-Water Investigation, prepared for San Benito County, October 1991.

Mintier Harnish Planning Consultants, San Joaquin County General Plan Background Report, July 2, 2009.

Pajaro River Watershed Integrated Regional Water Management Plan (IRWMP), June 2006.

RMC Water and Environment, San Benito County Regional Recycled Water Project Draft Feasibility Study Report, Prepared for San Benito County Water District and City of Hollister, May 2005.

San Benito County Water District, Website http://www.sbcwd.com/, Last accessed: February 2016.

Schaaf & Wheeler and Jones & Stokes, Hollister Area Urban Water Management Plan 2000, Prepared for Sunnyslope County Water District, City of Hollister, and San Benito County Water District, July 1999.

Semitropic Water Storage District, Homepage <u>http://www.semitropic.com/</u>, Last accessed January 2016.

Sweigert, Jan, State Water Resources Control Board, Letter to Danny Hillstock, City of Hollister, January 2016.

Todd Groundwater, Annual Groundwater Report for Water Years 2006-2015, Prepared for San Benito County Water District, December 2006-2015.

Todd Groundwater, 2015a, Annual Groundwater Report for Water Years 2015, Prepared for San Benito County Water District, December 2015.

Todd Groundwater, 2015b, Well Modification Investigation, Task 1, City of Hollister, San Benito County, February 13, 2015.

Todd Groundwater, 2015c, Vertical Flow and Hexavalent Chromium Profiling of Well No. 4, City of Hollister, San Benito County, June 26, 2015.

US Bureau of Reclamation, Safety of Dams, <u>http://www.usbr.gov/mp/sod/</u>, Last Accessed: Jan 2016

US Bureau of Reclamation, Municipal and Industrial Water Shortage Policy Environmental Impact Statement, August 2015.

Yates, Gus, Consulting Hydrogeologist, Coordinated Master Plan: Groundwater Model Improvements and Simulation of North County Project Wells, Memorandum to Jeff Cattaneo and Harry Blohm, San Benito County Water District and Bob Ellis and Holly Kennedy, HDR, Inc., February 10, 2011.

2015 Hollister Urban Area Urban Water Management Plan

July 2016

APPENDICES







Sunnyslope 👌 County Water District

APPENDIX A - NOTICE TO ADOPT

NOTICE 2015 Hollister Urban Area Urban Water Management Plan Update

Date: March 31, 2016

To: City of Hollister, City Clerk County of San Benito, Clerk of the Board

From: Shawn Novack, Water Conservation Program Manager San Benito County Water District

Re: 2015 Urban Water Management Plan Update

The Urban Water Management Planning Act requires every urban water supplier to prepare and adopt an Urban Water Management Plan (UWMP) and to update the plan at least once every five years. The Hollister Urban Area UWMP, a collaborative endeavor of the City of Hollister, Sunnyslope County Water District, and San Benito County Water District, is now being reviewed and changes are being considered.

In accordance with Water Code Section 10621, this notice is provided to the City and County at least 60 days prior to the public hearings on the plan, which are being scheduled for late June. Consistent with the Water Code, the plan will be adopted by the Hollister Urban Area agencies by July 1, 2016.

If you have any questions or comments regarding the UWMP update, please contact:

Shawn Novack Water Conservation Program Manager San Benito County Water District snovack@sbcwd.com (831) 637.4378 Direct

APPENDIX B - POPULATION TOOL

			Hollister - Popu	lation Using Po	ersons-per-Cor	nection		
				Persons Per	Persons Per			
		# SF	# MF/GQ	SF	MF/GQ		MF/GQ	Total
	Year	Connections	Connections	Connection	Connection	SF Population	Population	Population
10 to 15 Ye	ear Baseline	Population Ca	lculations					
Year 1	1996	4,267	153	3.74	21.02	15,966	3,216	19,182
Year 2	1997	4,469	174	3.72	20.91	16,640	3,638	20,277
Year 3	1998	4,630	186	3.7	20.8	17,154	3,868	21,022
Year 4	1999	4,905	210	3.69	20.69	18,082	4,344	22,427
Year 5	2000	5,014	215	3.67	20.58	18,392	4,424	22,816
Year 6	2001	5,199	218	3.65	20.47	18,982	4,462	23,444
Year 7	2002	5,289	219	3.63	20.36	19,210	4,459	23,668
Year 8	2003	5,227	223	3.61	20.25	18,885	4,516	23,401
Year 9	2004	5,204	222	3.59	20.14	18,703	4,471	23,174
Year 10	2005	5,190	221	3.58	20.03	18,554	4,427	22,981
5 Year Bas	eline Popula	ation Calculatio	ons					
Year 1	2003	5,227	223	3.61	20.25	18,885	4,516	23,401
Year 2	2004	5,204	222	3.59	20.14	18,703	4,471	23,174
Year 3	2005	5,190	221	3.58	20.03	18,554	4,427	22,981
Year 4	2006	5,158	238	3.56	19.92	18,342	4,741	23,083
Year 5	2007	5,175	229	3.54	19.81	18,304	4,536	22,840
2015 Com	oliance Year	Population Ca	lculations					
	2015	5410	260	3.39	18.93	18,340	4,922	23,262

		Sunny	vslope - Popula	tion Using Per	sons-per-Conr	nection		
				Persons Per	Persons Per			
		# SF	# MF/GQ	SF	MF/GQ	SF	MF/GQ	Total
	Year	Connections	Connections	Connection	Connection	Population	Population	Population
10 to 15 Yea	ar Baseline Po	pulation Calcu	lations					
Year 1	1996	3,332	352	2.79	11.66	9,312	4,103	13,415
Year 2	1997	4,418	205	2.82	11.59	12,468	2,375	14,843
Year 3	1998	4,418	205	2.85	11.52	12,588	2,362	14,950
Year 4	1999	4,695	198	2.88	11.45	13,506	2,267	15,773
Year 5	2000	4,843	198	2.9	11.38	14,064	2,254	16,318
Year 6	2001	4,938	200	2.93	11.31	14,458	2,262	16,721
Year 7	2002	4,986	200	2.96	11.24	14,739	2,249	16,987
Year 8	2003	4,977	200	2.98	11.18	14,851	2,235	17,087
Year 9	2004	4,985	199	3.01	11.11	15,015	2,210	17,225
Year 10	2005	4,985	200	3.04	11.04	15,154	2,208	17,362
5 Year Base	line Populatio	on Calculations						
Year 1	2003	4,977	200	2.98	11.18	14,851	2,235	17,087
Year 2	2004	4,985	199	3.01	11.11	15,015	2,210	17,225
Year 3	2005	4,985	200	3.04	11.04	15,154	2,208	17,362
Year 4	2006	4,985	198	3.07	10.97	15,294	2,172	17,466
Year 5	2007	4,937	198	3.1	10.9	15,285	2,159	17,444
2015 Compl	iance Year Po	pulation Calcu	lations					
	2015	5181	213	3.31	10.37	17,171	2,209	19,380

		HU	A - Populatior	n Using Perso	ns-per-Conne	ection		
				Persons Per	Persons Per			
		# SF	# MF/GQ	SF	MF/GQ	SF	MF/GQ	Total
	Year	Connections	Connections	Connection	Connection	Population	Population	Population
10 to 15 Ye	ear Baseline	Population Ca	lculations					
Year 1	1996	7,599	505	3.265	16.34	25,278	7,319	32,597
Year 2	1997	8,887	379	3.27	16.25	29,108	6,013	35,120
Year 3	1998	9,048	391	3.275	16.16	29,742	6,230	35,972
Year 4	1999	9,600	408	3.285	16.07	31,588	6,611	38,200
Year 5	2000	9,857	413	3.285	15.98	32,456	6,678	39,134
Year 6	2001	10,137	418	3.29	15.89	33,440	6,724	40,165
Year 7	2002	10,275	419	3.295	15.8	33,949	6,708	40,655
Year 8	2003	10,204	423	3.295	15.715	33,736	6,751	40,488
Year 9	2004	10,189	421	3.3	15.625	33,718	6,681	40,399
Year 10	2005	10,175	421	3.31	15.535	33,708	6,635	40,343
5 Year Base	eline Popula	ation Calculatio	ons					
Year 1	2003	10,204	423	3.295	15.715	33,736	6,751	40,488
Year 2	2004	10,189	421	3.3	15.625	33,718	6,681	40,399
Year 3	2005	10,175	421	3.31	15.535	33,708	6,635	40,343
Year 4	2006	10,143	436	3.315	15.445	33,636	6,913	40,549
Year 5	2007	10,112	427	3.32	15.355	33,589	6,695	40,284
2015 Comp	oliance Year	r Population Ca	lculations					
	2015	10591	473	3.35	14.65	35,511	7,131	42,642

APPENDIX C - FUTURE WATER DEMANDS MEMO

Water Demand and Wastewater Flow Projections Technical Memorandum Master Plan Update

City of Hollister, San Benito County Water District, and Sunnyslope County Water District

July 1, 2016





Table of Contents

Summa	ary	.1
1.0	Previous Projections	.2
1.1.	2008 Master Plan	.2
1.2.	2010 UWMP	.3
2.0	Changed Conditions since Prior Projections	.3
2.1.	Economic Downturn	.3
2.2.	Ongoing Drought	.3
2.3.	Conservation	.3
2.4.	County Master Plan Update	.4
3.0	Methodology	.4
4.0	Analysis of Recent Historical Data	.4
4.1.	Connections	.5
4.2.	Water Consumption	.5
4.3.	Unit Factors	.6
4.4.	Conservation	.7
4.5.	Unaccounted for Water	.8
5.0	Population Projections	.8
6.0	Water Demands1	10
7.0	Wastewater Flows1	11
7.1.	City WRF Wastewater Flows	12
7.2.	Ridgemark WWTP Flows	14



List of Tables

Table 1. Historical Connections (Number of Connections)	5
Table 2. Historical Water Consumption (AFY)	5
Table 3. City Unit Demands (AFY / Connection)	6
Table 4. SSCWD Unit Demands for 2011 (AFY / Connection)	6
Table 5. Water Conservation Activities	7
Table 6. Unaccounted for Water	8
Table 7. Projected Population Growth	9
Table 8. Projected New Connections	9
Table 9. New Water Demand by Customer Class (AFY)	10
Table 10. Projected Water Demand (AFY)	10
Table 11. Historical Influent Flow to City's WRF	12
Table 12. Projected ADWF Flows to City's WRF (mgd)	13

List of Figures

.

Figure 1. Existing and Projected Water Demands	1
Figure 2. 2008 Master Plan Water Demand Projection	2
Figure 3. Projected New Connections	9
Figure 4. Projected Water Demand	11
Figure 5. Historical Influent Flow to City's WRF	12
Figure 6. Projected ADWF at City's WRF	13
Figure 7. Projected ADWF at Ridgemark WWTP	14

Summary

Demand projections are required for the Hollister Urban Area Water and Wastewater Master Plan Update to identify future urban water supply needs and wastewater flows for the planning horizon of 2035. The demand projections presented in this technical memorandum are based on historical water demand data and patterns for the period between 2010 and 2015, projected population growth within the service areas, unit demands, estimated system losses, and consideration for water conservation as well as the ongoing drought.

Annual water demands for the Hollister Urban Area (HUA) are approximately 5,830 acre-feet per year (AFY) based on the average demand for 2011 through 2014. The annual water demand is projected to increase to approximately 6,820 AFY by 2020 and to approximately 8,840 AFY by 2030, as summarized in Figure 1. By comparison, the previous master plan, completed in 2008, projected the annual water demand would be 11,840 AFY in 2023. The significant decrease in projected future demands is attributed to increased water conservation, changes in behavior due to the ongoing drought, and delayed development due to the "Great Recession."





Figure 1. Existing and Projected Water Demands

Based on the anticipated new connections to the service areas, projected wastewater flows were also evaluated for the respective water reclamation facilities (WRF) operated by the City and SSCWD. The existing average dry weather flow (ADWF) is approximately 2.1 million gallons per day (mgd) at the City's WRF and is expected to increase to 2.7 mgd by 2020 and



The increase in influent flows to the respective WRFs will also increase the production of recycled water. Currently, only the City's WRF produces Title 22 recycled water, estimated at approximately 2,500 AFY. Based on the projected increase in wastewater flow, the production of recycled water at the City's WRF is expected to increase to approximately 3,000 AFY in 2020 and to 4,300 AFY by 2030.


1.0 Previous Projections

Demand projections are required for the Hollister Urban Area Water and Wastewater Master Plan Update to identify future urban water supply needs and wastewater flows for the planning horizon of 2030. The following subsections present a summary of past projections that have been prepared for the 2008 Master Plan and the 2010 Urban Water Management Plan.

1.1. 2008 Master Plan

The 2008 Hollister Urban Area Water and Wastewater Master Plan (2008 Master Plan) included a detailed analysis of historical water use and future water projections. The analysis incorporated land use planning data from the adopted General Plans for the City of Hollister and San Benito County, respectively, and evaluation of unit demands, system losses, and water conservation projections.

At the time of the 2008 Master Plan, the average annual water demand was estimated to be approximately 7,965 AFY and was projected to increase to 11,840 AFY 2023 and to 20,150 AFY by buildout of the HUA.



The growth in demands presented in the 2008 Master Plan is presented in Figure 2.

Figure 2. 2008 Master Plan Water Demand Projection

The 2008 Master Plan also considered wastewater flows to the WRFs. The total ADWF was estimated to be approximately 3.0 mgd, increasing to 4.5 mgd by 2023. The City's WRF was expected to increase from 2.7 mgd to 4.4 mgd, while SSCWD's Ridgemark WRF was expected to increase from 0.3 mgd to 0.46 mgd.

1.2. 2010 UWMP

The 2010 Urban Water Management Plan (UWMP) included an analysis of past and projected water demands, as required by the State and prescribed in the 2010 UWMP Guidebook. As presented in the 2010 UWMP, the total water use from 2005 to 2010 decreased from approximately 6,791 AFY to 5,856 AFY, despite a relatively consistent population in the HUA. The factors believed to contribute to this decrease are described in the following section.

Water demand was projected to increase to 8,624 AFY in 2020 and to 11,583 by 2030, which included estimated system losses at approximately 7 percent of demand.

2.0 Changed Conditions since Prior Projections

Since the Master Plan was completed in 2008, several key conditions changed, including the following.

2.1. Economic Downturn

The "Great Recession," which marked the country's largest downturn in economic activity since the Great Depression, officially lasted from December 2007 to June 2009. During that period and the ensuing years, growth in development, including the residential housing market, stagnated and there was a sharp cutback in consumer spending. As a result, much of the growth that was anticipated to occur following the lifting of the City's building moratorium in 2008, has been delayed. After several years of limited or no growth, there now appears to be a renewed interest in residential housing construction in the HUA as builders are anticipating a rebound of housing demand.

2.2. Ongoing Drought

San Benito County, like all of California, has experienced severe drought conditions. Since 2008, six of the seven subsequent years have been drought years and the period between 2012 and today represents perhaps the worst prolonged drought in the State's historical record.

On January 17, 2014, Governor Jerry Brown proclaimed a State of Emergency recognizing that the state was facing water shortfalls in the driest year in recorded state history. Then, on April 1, 2015, following the lowest snowpack ever recorded in California, Governor Brown announced a mandatory 25 percent reduction in water consumption throughout the state.

The prolonged drought conditions have had significant impact on the water demands.

2.3. Conservation

In addition to the drought, the Water Conservation Bill of 2009, Senate Bill x7-7, required a 20 percent reduction in per-capita urban consumption by 2020 (often referred to as 20 by 2020).

SBX7-7 requires that urban water purveyors make incremental progress toward the conservation goal by reducing per-capita water use by at least 10 percent by the end of 2015. To enforce this requirement, SBx7-7 further requires that urban water purveyors are not eligible for state water grants or loans unless they comply with their water conservation requirements.

The effect of SBx7-7 has been a heightened awareness and implementation of conservation measures in the HUA. The Water Resource Association of San Benito County (WRA) is responsible for managing the conservation efforts in the HUA, including providing incentives for new plumbing fixtures (e.g., low flush toilets, etc.), and providing information and education on conservation measures for the public. As described later in this memorandum, the WRA has been very successful in its efforts to provide incentives for new plumbing fixtures.

2.4. County Master Plan Update

San Benito County is in the process of updating its General Plan which has the potential to change land use designations within the HUA study area (outside the City's sphere of influence). These changes could allow more urbanization/densification of existing agricultural, low density and/or vacant parcels which would result in an increase in the potable water demand. Since the County's General Plan is not yet complete and adopted, any potential changes in land use designations have not been accounted for in this update.

3.0 Methodology

As previously described, the approach used to the project the water demands presented in the 2008 Master Plan was based on planned future land uses and the application of water use factors to those respective lands. The land use designations and densities were identified in the City and County General Plans for vacant lands within the HUA Study Area. The future demands were then added to the existing demand to determine a total forecasted demand for 2023 and beyond.

The forecasts presented in this memorandum rely on earlier projections to understand total potential demand in the HUA. However, the near term demand projections presented herein (through 2025) rely on the current understanding of population growth within the HUA based on input from the City's Planning Department and SSCWD.

In addition, an analysis of recent residential water demand and wastewater flows from 2010 through 2014 was conducted to understand changes and trends in residential unit consumption and production that may have arisen due to the ongoing drought, water conservation, and changes in typical residential lot size. The unit factors resulting from this analysis were then applied to the anticipated population growth and associated new developments to project future potable water demand and wastewater flows.

4.0 Analysis of Recent Historical Data

The following subsections present an analysis of recent historical connections, water consumption, unit factors, conservation and unaccounted for water.

4.1. Connections

During the period between 2010 and 2014, the City's potable water system grew from approximately 5,830 total connections to over 6,000, which is an average of approximately 50 new connections per year or slightly less than one percent annual growth on average. Of the nearly 200 new connections added during the period, over 80 percent were single family residential (SFR) connections.

Similarly, SSCWD's system grew from approximately 5,300 in 2010 to nearly 5,500 connections in early 2015. On average, approximately 40 new connections were added per year during the period, reflecting slightly less than one percent annual growth on average.

The addition of new connections during the period from 2010 to 2014 is presented in Table 1

	2010	2011	2012	2013	2014
City	5,831	5,860	5,893	5,962	6,026
SSCWD	5,304	5,351	5,373	5,418	5,470
Total	11,135	11,211	11,266	11,380	11,496
New Connections		76	55	114	116

 Table 1. Historical Connections (Number of Connections)

4.2. Water Consumption

As expected with an increase in connections, the City's water consumption also increased. During the period, consumption increased from a total of 2,750 acre-feet per year (AFY) reported in 2010 to 3,010 AFY in 2014, reflecting a nearly 10 percent growth. However, despite an increase in the number of connections, SSCWD's total water consumption, as reported in the volume of water billed to its customers, decreased from 2,960 AFY in 2010 to 2,558 AFY in 2014. That decrease reflects a nearly 14 percent decrease in total water consumption for SSCWD.

As shown in Table 2, the total water consumption for the combined system declined from 5,710 AFY in 2010 to 5,568 AFY in 2014.

	2010	2011	2012	2013	2014			
City	2,750	2,827	2,864	2,986	3,010			
SSCWD	2,960	2,440	2,653	2,810	2,558			
Total	5,710	5,267	5,517	5,796	5,568			
Annual Increase		(443)	250	279	(228)			

Table 2. Historical Water Consumption (AFY)

4.3. Unit Factors

Water consumption was evaluated to better understand the variation in water use by customer types, including SFR, multi-family residential (MFR), commercial, industrial, and landscape irrigation. The unit demand by customer type for the City connections is presented in Table 3.

Customer Type	2010	2011	2012	2013	2014	Average
SFR	0.33	0.33	0.34	0.35	0.32	0.33
MFR	1.28	1.32	1.29	1.27	1.20	1.27
Commercial	0.86	0.86	0.83	0.87	0.79	0.84
Institutional	1.20	1.20	1.19	1.37	1.38	1.27
Landscape	2.49	2.87	2.57	2.52	4.51	2.99
Total	0.47	0.48	0.48	0.50	0.50	0.48

Table 3. City Unit Demands (AFY / Connection)

With the exception of the Landscape category, the unit demands are relatively stable for the period. The residential and commercial customer types demonstrate a slight decline during the period, which is likely attributed to increased water conservation, particularly in light of the ongoing drought. The Institutional and Landscape unit demands have increased during the period; there appears to be an anomaly in the 2014 Landscape data.

Typical lot sizes for new residential units have decreased from a historical size of approximately 8,000 square feet per lot to 6,000 square feet per lot. Smaller lots require less water for outdoor irrigation. This transition to smaller lot sizes has occurred over a long period of time. As a result, the unit demands shown in Table 3 do include consideration of smaller lot sizes.

Unit demands for SSCWD were evaluated in aggregate for the period and by customer type for 2011. The former analysis revealed that 2011 had the lowest unit demands for the period, with an average annual water use of 0.46 AFY per connection, compared to a high of 0.56 AFY per connection in 2010 and an overall average of 0.48 AFY per connection for the period.

The SSCWD unit demands by customer account type, based on the water consumption in 2011, are presented in Table 4.

Customer Type	2011
SFR	0.40
MFR	1.08
Commercial	0.78
Institutional	1.04
Landscape	2.51
Total	0.46

Table 4. SSCWD Unit Demands for 2011 (AFY / Connection)

4.4. Conservation

The Water Resource Association of San Benito County (WRA) began tracking water conservation activities in 2003. Since that time, significant strides in conservation have occurred, as demonstrated in Table 5.


		Water Fixture Replacements						
-	Toilets	Showerheads	Faucet Aerators	High Efficiency Washing Machines				
2003	1,794	612	510	170				
2004	783	654	545	168				
2005	604	657	548	261				
2006	513	866	721	259				
2007	497	497	414	240				
2008	530	642	535	187				
2009	560	564	470	163				
2010	310	438	365	139				
2011	279	512	426	81				
2012	181	549	458	59				
2013	223	531	443	51				
Total Fixtures	6,274	6,521	5,434	1,778				
Estimated Water Savings (AFY)	1,700 AFY	402 AFY	91 AFY	429 AFY				
Total Estimated Water Savings		2,62	3 AFY					

Table 5. Water Conservation Activities

In addition to the indoor plumbing retrofits identified in Table 5, approximately 74,500 square feet of turf has been removed and/or replaced with drought tolerant landscaping since early 2014. Based on a typical evapotranspiration rate of 3 AFY/acre for the region, which equates to approximately 5 AFY of water conservation savings due to turf removal. As a result, the total estimated conservation savings are estimated to be approximately 2,630 AFY.

Based on discussions with staff at the WRA, many of the quantifiable indoor conservation retrofits are reaching saturation in the existing system. Furthermore, while the current ongoing drought has led some customers to remove their turf in the last two years, this method of conservation is not expected to continue, particularly when drought conditions dissipate and mandatory rationing is discontinued.

As demonstrated in Table 5, the majority of the indoor plumbing retrofits occurred prior to the period of analysis (2010 - 2014). Given the ongoing drought conditions, it is expected that water consumption has been depressed in recent years. Taken together, it is difficult to predict any further decline in unit water demand due to conservation when considering the elasticity in behavior that may occur once the drought subsides. As a result, for the purposes of projecting



4.5. Unaccounted for Water

In order to estimate the total water demand, unaccounted for water (e.g., system losses, other non-metered water) must also be estimated. To do so, the total water production, including the water produced at the City's wells, SSCWD's wells, and the Lessalt Water Treatment Plant (LWTP), was compared to the total metered water in the combined system. A summary of the unaccounted for water analysis is presented in Table 6.

		Production (AFY)	Consumption (AFY)			Unaccounted for Water		
Year	City Wells	Lessalt + SSCWD Wells	Total	City	SSCWD	Total	Total (AFY)	Total (%)
2010	2,056	3,458	5,514	2,750	2,457	5,207	307	6%
2011	1,607	3,996	5,602	2,827	2,483	5,310	293	6%
2012	2,120	3,815	5,934	2,864	2,153	5,017	917	18%
2013	2,951	3,210	6,162	2,986	3,176	6,162	0	0%
2014	2,755	2,864	5,619	3,010	2,440	5,450	169	3%
							Average	7%

Table 6. Unaccounted for Water

As shown in Table 6, the unaccounted for water averages approximately 7 percent of the total annual consumption, which is consistent with past estimates from the 2008 Master Plan as well as typical industry averages which range between 5 and 10 percent.

Two years, 2012 and 2013, seem to be outliers. There appears to be a significant drop in the SSCWD metered consumption for July through October of 2012, which led to the large discrepancy between production and consumption. It also seems unlikely that production would perfectly match consumption, as was the case in 2013.

5.0 Population Projections

As previously described, population growth was used as the basis to update the water demand and wastewater flow projections.

In collaboration with City, SBCWD and SSCWD staff, the population projections summarized in Table 7 were developed. These projections are based on a representative period from 1990's census data, which reflects an approximately 4 percent annual growth rate. However, population growth was limited to 1,500 people per year through 2020 due to the current development landscape in the HUA as well as recognition of existing infrastructure limitations (e.g., Highway 101 capacity limitations).



	2015	2016-2020	2021-2025	2026- 2030	2031 -2035
New	1,500	7,500	8,450	10,280	12,500
Cumulative New	1,500	9,000	17,450	27,730	40,230

Table 7. Projected Population Growth

A summary of the projected new connections associated with the population growth is presented in Table 8. As shown, there will be an estimated 10,500 new connections during the planning period.

Table 8. Pro	jected New	Connections

	2015	2016 - 2020	2021 - 2025	2026 - 2030	2031 - 2035	Total
SFR ^(a)	379	1,894	2,134	2,596	3,158	10,161
MFR ^(b)	13	63	71	87	105	339
Total	392	1,957	2,205	2,683	3,263	10,500
Cumulative	392	2,349	4,554	7,237	10,500	

(a) Number of SFR connections is based upon 3.3 persons per household.

(b) 6 units per MFR connection were assumed.

Figure 3 illustrates the number of connections in the City and SSCWD water service areas since 2010 as well as the projected number of new connections described above. As shown, it is anticipated that the system will see an increase from approximately 11,510 existing connections to approximately 22,010 connections in 2035.




Figure 3. Projected New Connections

6.0 Water Demands

Based on the unit demands presented in Section 4 and the new connections presented in Section 5, the projected water demands are summarized in Table 9, Table 10, and Figure 4.

	2015 - 2020	2021 - 2025	2026 - 2030	2031 - 2035	Total
SFR ^(a)	756	710	863	1,050	3,380
MFR ^(b)	96	90	110	134	430
Commercial/Industrial ^(c)	75	63	63	63	264
Losses ^(d)	60	56	68	83	267
Total	987	919	1,104	1,330	4,340

Table 9. New Water Demand by Customer Class (AFY)

(a) SFR demand is based on a unit demand of 0.33 AFY.

(b) MFR demand is based on a unit demand of 1.27 AFY.

(c) Commercial / Industrial demands were estimated based on 12.5 AFY of new demand per year.

(d) Losses were estimated based as 7 percent of residential demand.

The projected demand presented in Table 9 reflects the projected new connections presented in Section 5 as well as an allowance for new commercial and industrial demands, estimated at 12.5 AFY. The projected demands also include system losses estimated at 7 percent of residential demand.

Table 10 presents the total estimated potable water demand for the combined systems as well as the demands for the City and SSCWD. As shown, the total system demand is expected to increase from approximately 5,830 AFY in recent years to over 10,000 AFY in 2035.

	Existing	2020	2025	2030	2035
City	3,150	3,580	3,980	4,460	5,040
SSCWD	2,680	3,240	3,760	4,380	5,130
Total	5,830	6,820	7,740	8,840	10,170

Table 10. Projected Water Demand (AFY)




Figure 4. Projected Water Demand

Due to the inherent uncertainty in projecting future conditions, a range is presented in Figure 4. The upper band of the range is based on a 10 percent increase over the projected flows. The lower band reflects both a slower growth rate (reduced from 4 percent to 2 percent) and a reduction in unit consumption by 10 percent. Due to this uncertainty, it will be important to identify triggers in the Master Plan Update such that the implementation of new water supply infrastructure needed to serve the future demand is complete in a timely manner.

As described in Section 1, the 2008 Master Plan projected the demand for 2023 to be approximately 11,840 AFY. As shown in Figure 5, the projected demand for the same period is only 7,350, reflecting a decrease of approximately 4,490 AFY. That decrease is attributed to the changed conditions described in Section 2. Namely, there has been an extended drought that has impacted water use behaviors, increased awareness and implementation of water conservation, and finally, there was a significant delay in the expected growth in the region due to the "Great Recession."

7.0 Wastewater Flows

The following subsections describe the projected wastewater flows for the City's WRF and SSCWD, respectively.

ト)く

7.1. City WRF Wastewater Flows

The historical influent flows to the City's WRF are illustrated in Figure 5 and summarized in Table 11. As shown, there appears to be a downward trend for the period between January 2010 and mid-2013, with some recovery in 2014. The average dry weather flow (ADWF) during the period was approximately 2.1 mgd while the average annual (AA) flow was only slightly higher at 2.2 mgd.




Figure 5. Historical Influent Flow to City's WRF

As shown in Figure 6, the unit discharge per connection decreased from approximately 240 gallons per connection per day (gal/con-day) in 2010 to a low of 224 gal/con-day in 2013, before rebounding to 232 gal/con-day. The overall average contribution per connection was approximately 231 gal/con-day.

	2010	2011	2012	2013	2014	Average
ADWF (mgd)	2.14	2.13	2.09	2.07	2.17	2.12
AA (mgd)	2.23	2.15	2.12	2.14	2.20	2.16
Connections (No.)	5,831	5,860	5,893	5,962	6,026	
ADWF / Connection	238	235	229	224	232	231

Table 11.	Historical	Influent Flow	to Cit	v's WRF
	Instoriour	minucine i iow		.y 3 WIN

トノく

The average contribution per connection was used to project the future growth in influent flow to the City's WRF. Similar to the projections for the water demand, an upper and lower bound were also projected to reflect the uncertainty associated with the projections. The upper bound is based on a 10 percent increase in flows, similar to the water demand projections. Similarly, the lower bound was based on a 10 percent reduction of the flows.

Based on the contribution per connection described above and the new connections presented in Section 5, the projected wastewater flows to the City's WRF are summarized in Table 12 and Figure 6.

	2020	2025	2030	2035
Projected ADWF	2.7	3.2	3.8	4.6
Upper Range	3.0	3.5	4.2	5.1
Lower Range	2.4	2.9	3.5	4.1

Table 12. Projected ADWF Flows to City's WRF (mgd)




Figure 6. Projected ADWF at City's WRF

トノく

7.2. Ridgemark WWTP Flows

The service area for the Ridgemark wastewater treatment plant (WWTP) is very small, with just over 1,200 connections. Growth in the service area is relatively small in comparison to that expected for the rest of the HUA. Approximately 465 additional connections are expected in the Ridgemark WWTP service area. Based on historical influent flows to the plant between 2010 and 2014, it is expected that each connection will contribute approximately 155 gpd. As a result, influent ADWF to the Ridgemark WWTP is expected to grow from 0.18 mgd to approximately 0.24 mgd, as shown in Figure 7.




Figure 7. Projected ADWF at Ridgemark WWTP

APPENDIX D – WATER LOSS AUDITS

		AWWA Fre	ee Water Audit Software	: Water Balance	WAS v5.0
				Americ	an Water Works Associatio
	Wa	ter Audit Report for:	Sunnyslope County Water District		
		Reporting Year:	2015	1/2015 - 1/2016	
		Data Validity Score:	87		
	Water Exported 1,037.140			Billed Water Exported	
			Billed Authorized Consumption	Billed Metered Consumption (water exported is removed) 1,940.100	Revenue Water
Own Sources Adjusted for known		Authorized Consumption	1,940.100	Billed Unmetered Consumption 0.000	1,940.100
errors)		1,965.491	Unbilled Authorized Consumption	Unbilled Metered Consumption 0.000	Non-Revenue Wat (NRW)
1,277.600			25.391	Unbilled Unmetered Consumption 25.391	
	Water Supplied		Apparent Losses	Unauthorized Consumption 5.078	91.160
	2,031.260		9.928	Customer Metering Inaccuracies 0.000	
		Water Losses		Systematic Data Handling Errors 4.850	
Water Imported		65.769	Real Losses	Leakage on Transmission and/or Distribution Mains <i>Not broken down</i>	
1,790.800			55.841	Leakage and Overflows at Utility's Storage Tanks <i>Not broken down</i>	
				Leakage on Service Connections Not broken down	

		e Water Audit So orting Workshee		American	WAS v5.0 Water Works Associatior
Click to access definition Glick to add a comment Click to add a comment	Sunnyslope (2015	County Water District 1/2015 - 1/2016			
Please enter data in the white cells below. Where available, metered values should	ld be used; if r	netered values are unava	ilable please estimate a value. I	ndicate your confidence in the accura	acy of the
AII	volumes to t	be entered as: ACRE-I	FEET PER YEAR		
To select the correct data grading for each input,	determine the	e highest grade where		Master Meter and Supply Error A	Adjustments
WATER SUPPLIED	<		in column 'E' and 'J'	- one	
Volume from own sources: Water imported:	+ ? 10 + ? 10	1,277.600 1,790.800		● O ● O	acre-ft/yr acre-ft/yr
Water exported:	+ ? 7	1,037.140		• •	acre-ft/yr
WATER SUPPLIED:		2,031.260	acre-ft/yr	Enter negative % or value for un Enter positive % or value for over	0
AUTHORIZED CONSUMPTION				Click here:	?
Billed metered:	+ ? 10 + ? 10	1,940.100		for help usir buttons belo	ng option
Billed unmetered: Unbilled metered:	+ ? 10 + ? 10	0.000		Pcnt: Value:	
	+ ? 2	25.391	acre-ft/yr	1.25% 🔘 🔿	acre-ft/yr
Default option selected for Unbilled unme				Line buttons	s to select
AUTHORIZED CONSUMPTION:	?	1,965.491	acre-ft/yr	percentage supp	e of water lied
WATER LOSSES (Water Supplied - Authorized Consumption)		65.769	acre-ft/yr	valu	
Apparent Losses				Pcnt: Value:	
Unauthorized consumption: Default option selected for unauthorized consu			acre-ft/yr	0.25%	acre-ft/yr
Customer metering inaccuracies:			acre-ft/yr		acre-ft/yr
Systematic data handling errors:			acre-ft/yr	0.25%	acre-ft/yr
Default option selected for Systematic data	handling er				
Apparent Losses:		9.920	acre-ft/yr		
Real Losses (Current Annual Real Losses or CARL)	_				
Real Losses = Water Losses - Apparent Losses:	?	55.841	-		
WATER LOSSES:		65.769	acre-ft/yr		
NON-REVENUE WATER = Water Losses + Unbilled Metered + Unbilled Unmetered	?	91.160	acre-ft/yr		
SYSTEM DATA					
Length of mains:	+ ? 9	69.0	miles		
Number of active AND inactive service connections:	+ ? 9	5,500			
Number of <u>active AND inactive</u> service connections: Service connection density:		5,500 80	miles conn./mile main		
Number of active AND inactive service connections:	+ ? 9	5,500	conn./mile main (length of service line	s, <u>beyond</u> the property responsibility of the utility)	
Number of <u>active AND inactive</u> service connections: Service connection density: Are customer meters typically located at the curbstop or property line? <u>Average</u> length of customer service line has been se	+ ? 9 + ? et to zero and	5,500 80 Yes a data grading score	conn./mile main (length of service line boundary, that is the e of 10 has been applied	s, <u>beyond</u> the property responsibility of the utility)	
Number of <u>active AND inactive</u> service connections: Service connection density: Are customer meters typically located at the curbstop or property line? <u>Average</u> length of customer service line:	+ ? 9 + ? et to zero and	5,500 80 Yes	conn./mile main (length of service line boundary, that is the e of 10 has been applied		
Number of <u>active AND inactive</u> service connections: Service connection density: Are customer meters typically located at the curbstop or property line? <u>Average</u> length of customer service line has been se	+ ? 9 + ? et to zero and	5,500 80 Yes a data grading score	conn./mile main (length of service line boundary, that is the e of 10 has been applied		
Number of active AND inactive service connections: Service connection density: Are customer meters typically located at the curbstop or property line? Average length of customer service line: Average length of customer service line has been se Average operating pressure:	+ ? 9 + ? to zero and + ? 9	5,500 80 Yes d a data grading score 65.0	conn./mile main (length of service line boundary, that is the c of 10 has been applied psi		
Number of active AND inactive service connections: Service connection density: Are customer meters typically located at the curbstop or property line? Average length of customer service line has been se Average operating pressure: COST DATA Total annual cost of operating water system: Customer retail unit cost (applied to Apparent Losses):	+ ? 9 ? et to zero and + ? 9 + ? 9 + ? 9	5,500 80 Yes d a data grading score 65.0 \$6,012,867 \$2.47	conn./mile main (length of service line boundary, that is the c of 10 has been applied psi \$/Year \$/100 cubic feet (ccf)	responsibility of the utility)	
Number of active AND inactive service connections: Service connection density: Are customer meters typically located at the curbstop or property line? Average length of customer service line has been se Average operating pressure: COST DATA Total annual cost of operating water system: Customer retail unit cost (applied to Apparent Losses): Variable production cost (applied to Real Losses):	+ ? 9 ? et to zero and + ? 9 + ? 9 + ? 9 + ? 9	5,500 80 Yes d a data grading score 65.0 \$6,012,867 \$2.47 \$1,634.00	conn./mile main (length of service line boundary, that is the e of 10 has been applied psi \$/Year \$/100 cubic feet (ccf) \$/acre-ft Use Cust		
Number of active AND inactive service connections: Service connection density: Are customer meters typically located at the curbstop or property line? Average length of customer service line has been se Average operating pressure: COST DATA Total annual cost of operating water system: Customer retail unit cost (applied to Apparent Losses):	+ ? 9 ? et to zero and + ? 9 + ? 9 + ? 9 + ? 9	5,500 80 Yes d a data grading score 65.0 \$6,012,867 \$2.47 \$1,634.00	conn./mile main (length of service line boundary, that is the e of 10 has been applied psi \$/Year \$/100 cubic feet (ccf) \$/acre-ft Use Cust	responsibility of the utility)	
Number of active AND inactive service connections: Service connection density: Are customer meters typically located at the curbstop or property line? Average length of customer service line. Average length of customer service line has been se Average operating pressure: COST DATA Total annual cost of operating water system: Customer retail unit cost (applied to Apparent Losses): Variable production cost (applied to Real Losses): Retail costs are less than (or equal WATER AUDIT DATA VALIDITY SCORE:	+ ? 9 ? et to zero and + ? 9 + ? 9 + ? 9 + ? 9 at to) production	5,500 80 Yes d a data grading score 65.0 \$6,012,867 \$2.47 \$1,634.00	conn./mile main (length of service line boundary, that is the e of 10 has been applied psi \$/Year \$/Year \$/100 cubic feet (ccf) \$/acre-ft □Use Cust y and correct if necessary	responsibility of the utility)	
Number of active AND inactive service connections: Service connection density: Are customer meters typically located at the curbstop or property line? Average length of customer service line. Average length of customer service line has been se Average operating pressure: COST DATA Total annual cost of operating water system: Customer retail unit cost (applied to Apparent Losses): Variable production cost (applied to Real Losses): Retail costs are less than (or equal WATER AUDIT DATA VALIDITY SCORE:	+ ? 9 ? * * * ? 9 * ? 9 * ? 9 + ? 9 + ? 9 + ? 9 * ? 9	5,500 80 Yes d a data grading score 65.0 \$6,012,867 \$2.47 \$1,634.00 on costs; please review RE IS: 87 out of 100 **	conn./mile main (length of service line boundary, that is the c of 10 has been applied psi \$/Year \$/100 cubic feet (ccf) \$/acre-ft Use Cust y and correct if necessary	responsibility of the utility)	
Number of active AND inactive service connections: Service connection density: Are customer meters typically located at the curbstop or property line? Average length of customer service line has been se Average operating pressure: COST DATA Total annual cost of operating water system: Customer retail unit cost (applied to Apparent Losses): Variable production cost (applied to Real Losses): Retail costs are less than (or equal WATER AUDIT DATA VALIDITY SCORE:	+ ? 9 ? * * * ? 9 * ? 9 * ? 9 + ? 9 + ? 9 + ? 9 * ? 9	5,500 80 Yes d a data grading score 65.0 \$6,012,867 \$2.47 \$1,634.00 on costs; please review RE IS: 87 out of 100 **	conn./mile main (length of service line boundary, that is the c of 10 has been applied psi \$/Year \$/100 cubic feet (ccf) \$/acre-ft Use Cust y and correct if necessary	responsibility of the utility)	
Number of active AND inactive service connections: Service connection density: Are customer meters typically located at the curbstop or property line? Average length of customer service line. Average length of customer service line. Average length of customer service line has been se Average operating pressure: COST DATA Total annual cost of operating water system: Customer retail unit cost (applied to Apparent Losses): Variable production cost (applied to Real Losses): Retail costs are less than (or equation of the system: WATER AUDIT DATA VALIDITY SCORE: A weighted scale for the components of consumption of the system of the	+ ? 9 ? et to zero and + ? 9 +	5,500 80 Yes d a data grading score 65.0 \$6,012,867 \$2.47 \$1,634.00 on costs; please review RE IS: 87 out of 100 ** loss is included in the ca	conn./mile main (length of service line boundary, that is the c of 10 has been applied psi \$/Year \$/100 cubic feet (ccf) \$/acre-ft Use Cust y and correct if necessary	responsibility of the utility)	
Number of active AND inactive service connections: Service connection density: Are customer meters typically located at the curbstop or property line? Average length of customer service line has been se Average length of customer service line has been se Average operating pressure: COST DATA Total annual cost of operating water system: Customer retail unit cost (applied to Apparent Losses): Variable production cost (applied to Real Losses): Variable production cost (applied to Real Losses): Retail costs are less than (or equal WATER AUDIT DATA VALIDITY SCORE: A weighted scale for the components of consump PRIORITY AREAS FOR ATTENTION:	+ ? 9 ? et to zero and + ? 9 +	5,500 80 Yes d a data grading score 65.0 \$6,012,867 \$2.47 \$1,634.00 on costs; please review RE IS: 87 out of 100 ** loss is included in the ca	conn./mile main (length of service line boundary, that is the c of 10 has been applied psi \$/Year \$/100 cubic feet (ccf) \$/acre-ft Use Cust y and correct if necessary	responsibility of the utility)	
Number of active AND inactive service connections: Service connection density: Are customer meters typically located at the curbstop or property line? Average length of customer service line has been se Average length of customer service line has been se Average operating pressure: COST DATA Total annual cost of operating water system: Customer retail unit cost (applied to Apparent Losses): Variable production cost (applied to Real Losses): Variable production cost (applied to Real Losses): Retail costs are less than (or equal WATER AUDIT DATA VALIDITY SCORE: A weighted scale for the components of consump PRIORITY AREAS FOR ATTENTION: Based on the information provided, audit accuracy can be improved by addressing	+ ? 9 ? et to zero and + ? 9 +	5,500 80 Yes d a data grading score 65.0 \$6,012,867 \$2.47 \$1,634.00 on costs; please review RE IS: 87 out of 100 ** loss is included in the ca	conn./mile main (length of service line boundary, that is the c of 10 has been applied psi \$/Year \$/100 cubic feet (ccf) \$/acre-ft Use Cust y and correct if necessary	responsibility of the utility)	
Number of active AND inactive service connections: Service connection density: Are customer meters typically located at the curbstop or property line? Average length of customer service line has been se Average length of customer service line has been se Average operating pressure: COST DATA Total annual cost of operating water system: Customer retail unit cost (applied to Apparent Losses): Variable production cost (applied to Real Losses): Variable production cost (applied to Real Losses): Retail costs are less than (or equal WATER AUDIT DATA VALIDITY SCORE: A weighted scale for the components of consump PRIORITY AREAS FOR ATTENTION: Based on the information provided, audit accuracy can be improved by addressir 1: Unauthorized consumption	+ ? 9 ? et to zero and + ? 9 +	5,500 80 Yes d a data grading score 65.0 \$6,012,867 \$2.47 \$1,634.00 on costs; please review RE IS: 87 out of 100 ** loss is included in the ca	conn./mile main (length of service line boundary, that is the c of 10 has been applied psi \$/Year \$/100 cubic feet (ccf) \$/acre-ft Use Cust y and correct if necessary	responsibility of the utility)	

Click to access definition Water Audit Report for: City of Hollister Click to add a comment Water Audit Report for: City of Hollister Reporting Year: 2015 1/2015 - 1/2016 Please enter data in the white cells below. Where available, metered values should be used; if metered values are unavailable please estimate a value. Indicate your confidence in the accuracy of the All volumes to be entered as: ACRE-FEET PER YEAR	
All volumes to be entered as: ACRE-FEET PER YEAR	
To select the correct data grading for each input, determine the highest grade where Master Meter and Supply Error Adjustments	
WATER SUPPLIED < Enter grading in column 'E' and 'J'> Pcnt: Value:	
Water imported: + ? 7 1,037.445 acre-ft/yr + ?	e-ft/yr e-ft/yr
Enter negative % or value for under-registration	e-ft/yr n
WATER SUPPLIED: 2,986.370 acre-ft/yr Enter positive % or value for over-registration	
AUTHORIZED CONSUMPTION Click here: ? Billed metered: ? 10 2,498.053 acre-ft/yr for help using option	
Billed unmetered: + ? 10 0.000 acre-ft/yr buttons below Unbilled metered: + ? 10 0.000 acre-ft/yr Pcnt: Value:	
	e-ft/yr
AUTHORIZED CONSUMPTION: 2 2.535.383 acre-ft/vr Use buttons to select	
supplied	
WATER LOSSES (Water Supplied - Authorized Consumption) 450.987 acre-ft/yr value	
Apparent Losses Pcnt: Value:	
Unauthorized consumption: + ? 7.466 acre-ft/yr 0.25% O acre- Default option selected for unauthorized consumption - a grading of 5 is applied but not displayed	e-ft/yr
	e-ft/yr
Systematic data handling errors: + ? 9 6.245 acre-ft/yr 0.25% C acre-ft/yr Default option selected for Systematic data handling errors - a grading of 5 is applied but not displayed	e-ft/yr
Apparent Losses: ? 13.711 acre-ft/yr	
Real Losses (Current Annual Real Losses or CARL)	
Real Losses = Water Losses - Apparent Losses: ? 437.276 acre-ft/yr	
WATER LOSSES: 450.987 acre-ft/yr	
NON-REVENUE WATER: 2 488.316 acre-ft/yr	
= Water Losses + Unbilled Metered + Unbilled Unmetered SYSTEM DATA	
Length of mains: + ? 1 69.0 miles	
Number of active AND inactive service connections: + ? 9 6,200 Service connection density: ? 90 conn./mile main	
Are customer meters typically located at the curbstop or property line? Yes (length of service line, beyond the property	
Average length of customer service line: + ? Average length of customer service line has been set to zero and a data grading score of 10 has been applied	
Average operating pressure: + ? 1 65.0 psi	
COST DATA Total annual cost of operating water system: + ? 1 \$6,012,867 \$/Year	
Customer retail unit cost (applied to Apparent Losses): + ? 10 \$2.07 \$/100 cubic feet (ccf)	
Variable production cost (applied to Real Losses): + ? 1 \$1,634.00 \$/acre-ft Use Customer Retail Unit Cost to value real losses Retail costs are less than (or equal to) production costs; please review and correct if necessary	
WATER AUDIT DATA VALIDITY SCORE:	
*** YOUR SCORE IS: 71 out of 100 ***	
A weighted scale for the components of consumption and water loss is included in the calculation of the Water Audit Data Validity Score	
PRIORITY AREAS FOR ATTENTION:	
Based on the information provided, audit accuracy can be improved by addressing the following components:	
1: Total annual cost of operating water system	
2: Variable production cost (applied to Real Losses)	
3: Water imported	

		AWWA Fre	ee Water Audit Software		WAS v5. an Water Works Association
	Wa	ter Audit Report for:	City of Hollister		
		Reporting Year:		1/2015 - 1/2016	
		Data Validity Score:	71		
	Water Exported 0.000			Billed Water Exported	
			Billed Authorized Consumption	Billed Metered Consumption (water exported is removed) 2,498.053	Revenue Water
Own Sources Adjusted for known		Authorized Consumption	2,498.053	Billed Unmetered Consumption 0.000	2,498.053
errors)		2,535.383	Unbilled Authorized Consumption	Unbilled Metered Consumption 0.000	Non-Revenue Wat (NRW)
1,948.925			37.330	Unbilled Unmetered Consumption 37.330	
	Water Supplied		Apparent Losses	Unauthorized Consumption 7.466	488.316
	2,986.370		13.711	Customer Metering Inaccuracies 0.000	
		Water Losses		Systematic Data Handling Errors 6.245	
Water Imported		450.987	Real Losses	Leakage on Transmission and/or Distribution Mains <i>Not broken down</i>	
1,037.445			437.276	Leakage and Overflows at Utility's Storage Tanks <i>Not broken down</i>	
				Leakage on Service Connections Not broken down	

APPENDIX E – CLIMATE CHANGE VULNERABILITY ASSESSMENT

The Climate Change Vulnerability Assessment is taken from the Climate Change Handbook for Regional Water Planning, USEPA and DWR, 2011. The vulnerability assessment highlights those water-related resources that are important to a region and are sensitive to climate change.

I. Water Demand

- Are there major industries that require cooling/process water in your planning region?
 - There are no major industries that require cooling water.
- Does water use vary by more than 50% seasonally in parts of your region?
 - Seasonal water use, which is primarily outdoor water use, is expected to increase as average temperatures increase and droughts become more frequent.
- □ Are crops grown in your region climate-sensitive? Would shifts in daily heat patterns, such as how long heat lingers before night-time cooling, be prohibitive for some crops?
 - The retailers do not provide any water to agricultural users.
- Do groundwater supplies in your region lack resiliency after drought events?
 - Droughts are expected to become more frequent and more severe in the future. Droughts would result in additional groundwater production and decrease water levels in the short term. The basin can and has recovered from droughts lasting up to four years.
- Are water use curtailment measures effective in your region?
 - The current drought and associated mandates, were effective reducing demand by 25 to 35 percent for Sunnyslope and Hollister

- Are some instream flow requirements in your region either currently insufficient to support aquatic life, or occasionally unmet?
 - The San Benito River is ephemeral and does not have any in stream flow requirements. In addition, the river recharges groundwater over most of the basin increased groundwater production in the Hollister area is unlikely to significantly reduce flow

II. Water Supply

Does a portion of the water supply in your region come from snowmelt?

- Snowmelt is expected to decrease as the climate warms. Water systems supplied by snowmelt are therefore potentially vulnerable to climate change.
- The retailers rely on imported CVP water that is supplied in part by snow melt.
- Does part of your region rely on water diverted from the Delta, imported from the Colorado River, or imported from other climate-sensitive systems outside your region?
 - Some imported or transferred water supplies are sources from climate-sensitive watersheds, including water imported from the Delta.
 - The retailers rely on imported CVP water that is supplied in part by the Delta system.
 - Does part of your region rely on coastal aquifers? Has salt intrusion been a problem in the past?
 - □ Would your region have difficulty in storing carryover supply surpluses from year to year?
 - The basin has sufficient groundwater storage to potential store water as a reserve for droughts/ Systems that can store more water may be more resilient to droughts.
 - □ Has your region faced a drought in the past during which it failed to meetlocal water demands?

- The region has handled the current multiple through municipal conservation and reliance on groundwater storage
- Does your region have invasive species management issues at your facilities, along conveyance structures, or in habitat areas?

III. Water Quality

- □ Are increased wildfires a threat in your region? If so, does your region include reservoirs with fire-susceptible vegetation nearby which could pose a water quality concern from increased erosion?
 - Some areas are expected to become more vulnerable to wildfires over time. To identify whether this is the case for parts of your region, the California Public Interest Energy Research (PIER)Program has posted wildfire susceptibility projections as a Google Earth application at: <u>http://cal-adapt.org/fire/</u>. These projections are only the results of a single study and are not intended for analysis, but can aid in qualitatively answering this question. Read the application's disclaimers carefully to be aware of its limitations.
- Does part of your region rely on surface water bodies with current or recurrent water quality issues related to eutrophication, such as low dissolved oxygen or algal blooms? Are there other water quality constituents potentially exacerbated by climate change?
 - Warming temperatures will result in lower dissolved oxygen levels in water bodies, which are exacerbated by algal blooms and in turn enhance eutrophication. Changes in streamflows may alter pollutant concentrations in water bodies.
- Are seasonal low flows decreasing for some waterbodies in your region? If so, are the reduced low flows limiting the waterbodies' assimilative capacity?
 - In the future, low flow conditions are expected to be more extreme and last longer. This may result in higher pollutant concentrations where loadings increase or remain constant.
- Are there beneficial uses designated for some water bodies in your region that cannot always be met due to water quality issues?

- In the future, low flows are expected decrease, and to last longer. This may result in higher pollutant concentrations where loadings increase or remain constant.
- Does part of your region currently observe water quality shifts during rain events that impact treatment facility operation?
 - While it is unclear how average precipitation will change with temperature, it is generally agreed that storm severity will probably increase. More intense, severe storms may lead to increased erosion, which will increase turbidity in surface waters. Areas that already observe water quality responses to rainstorm intensity may be especially vulnerable.

IV. Sea Level Rise

Has coastal erosion already been observed in your region?

- Coastal erosion is expected to occur over the next century as sea levels rise.
- Are there coastal structures, such as levees or breakwaters, in your region?
 - Coastal structures designed for a specific mean sea level may be impacted by sea level rise.
- □ Is there significant coastal infrastructure, such as residences, recreation, water and wastewater treatment, tourism, and transportation) at less than six feet above mean sea level in your region?
 - Coastal flooding will become more common, and will impact a greater extent of property, as sea levels rise. Critical infrastructure in the coastal floodplain may be at risk.
 - Digital elevation maps should be compared with locations of coastal infrastructure.
- Are there climate-sensitive low-lying coastal habitats in your region?
 - Low-lying coastal habitats that are particularly vulnerable to climate change include estuaries and coastal wetlands that rely on a delicate balance of freshwater and salt water.
- Are there areas in your region that currently flood during extreme high tides or storm surges?

- Areas that are already experiencing flooding during storm surges and very high tides, are more likely to experience increased flooding as sea levels rise.
- □ Is there land subsidence in the coastal areas of your region?
 - Land subsidence may compound the impacts of sea level rise.

Do tidal gauges along the coastal parts of your region show an increase over the past several decades?

- Local sea level rise may be higher or lower than state, national, or continental projections.
- Planners can find information on local tidal gauges at <u>http://tidesandcurrents.noaa.gov/sltrends/sltrends_states.shtml?region=ca</u>

V. Flooding

Does critical infrastructure in your region lie within the 200-year floodplain? DWR's best available floodplain maps are available at: <u>http://www.water.ca.gov/floodmgmt/lrafmo/fmb/fes/best_available_maps/</u>

- While it is unclear how average precipitation will change with temperature, it is generally agreed that storm severity will probably increase. More intense, severe storms may lead to higher peak flows and more severe floods.
- Refer to FEMA floodplain maps and any recent FEMA, US Army Corps of Engineers, or DWR studies that might help identify specific local vulnerabilities for your region. Other follow-up questions that might help answer this question:
 - What public safety issues could be affected by increased flooding events or intensity? For example, evacuation routes, emergency personnel access, hospitals, water treatment and wastewater treatment plants, power generation plants and fire stations should be considered.
 - 2. Could key regional or economic functions be impacted from more frequent and/or intense flooding?

Does part of your region lie within the Sacramento-San Joaquin Drainage District?

- The SSJDD contains lands that are susceptible to overflows from the Sacramento and San Joaquin Rivers, and are a key focus of the Central Valley Flood Protection Plan. (<u>http://www.water.ca.gov/cvfmp/program.cfm</u>).
- Does aging critical flood protection infrastructure exist in your region?

- Levees and other flood protection facilities across the state of California are aging and in need of repair. Due to their overall lowered resiliency, these facilities may be particularly vulnerable to climate change impacts.
- DWR is evaluating more than 300 miles of levees in the San Joaquin and Sacramento Rivers Valleys and the Delta (<u>http://www.water.ca.gov/levees/</u>).

□ Have flood control facilities (such as impoundment structures)been insufficient in the past?

- Reservoirs and other facilities with impoundment capacity may be insufficient for severe storms in the future. Facilities that have been insufficient in the past may be particularly vulnerable.
- Are wildfires a concern in parts of your region?
 - Wildfires alter the landscape and soil conditions, increasing the risk of flooding within the burn and downstream areas. Some areas are expected to become more vulnerable to wildfires over time. To identify whether this is the case for parts of your region, the California Public Interest Energy Research Program (PIER) has posted wildfire susceptibility projections as a Google Earth application at: <u>http://cal-adapt.org/fire/</u>. These projections are the results of only a single study and are not intended for analysis, but can aid in qualitatively answering this question. Read the application's disclaimers carefully to be aware of its limitations.

VI. Ecosystem and Habitat Vulnerability

- Does your region include inland or coastal aquatic habitats vulnerable to erosion and sedimentation issues?
 - Erosion is expected to increase with climate change, and sedimentation is expected to shift. Habitats sensitive to these events may be particularly vulnerable to climate change.
- Does your region include estuarine habitats which rely on seasonal freshwater flow patterns?
 - Seasonal high and low flows, especially those originating from snowmelt, are already shifting in many locations.
- Do climate-sensitive fauna or flora populations live in your region?
 - Some specific species are more sensitive to climate variations than others.

- Do endangered or threatened species exist in your region? Are changes in species distribution already being observed in parts of your region?
 - Species that are already threatened or endangered may have a lowered capacity to adapt to climate change.
- Does the region rely on aquatic or water-dependent habitats for recreation or other economic activities?
 - Economic values associated with natural habitat can influence prioritization.
- Are there rivers in your region with quantified environmental flow requirements or known water quality/quantity stressors to aquatic life?
 - Constrained water quality and quantity requirements may be difficult to meet in the future.
- Do estuaries, coastal dunes, wetlands, marshes, or exposed beaches exist in your region? If so, are coastal storms possible/frequent in your region?
 - Storm surges are expected to result in greater damage in the future due to sea level rise. This makes fragile coastal ecosystems vulnerable.
- Does your region include one or more of the habitats described in the Endangered Species Coalition's Top 10 habitats vulnerable to climate change (<u>http://www.itsgettinghotoutthere.org/</u>)?
 - These ecosystems are particularly vulnerable to climate change.
- Are there areas of fragmented estuarine, aquatic, or wetland wildlife habitat within your region? Are there movement corridors for species to naturally migrate? Are there infrastructure projects planned that might preclude species movement?
 - These ecosystems are particularly vulnerable to climate change.

VII. Hydropower

- □ Is hydropower a source of electricity in your region?
 - As seasonal river flows shift, hydropower is expected to become less reliable in the future.

- □ Are energy needs in your region expected to increase in the future? If so, are there future plans for hydropower generation facilities or conditions for hydropower generation in your region?
 - Energy needs are expected to increase in many locations as the climate warms. This increase in electricity demand may compound decreases in hydropower production, increasing its priority for a region.

APPENDIX F – SB 20X20 COMPLIANCE

TODD ENGINEERS

GROUNDWATER · WATER RESOURCES · HYDROGEOLOGY · ENVIRONMENTAL ENGINEERING

January 8, 2013

DRAFT MEMORANDUM

To: Jeff Cattaneo, San Benito County Water District

From: Iris Priestaf, Chad Taylor, and Maureen Reilly, Todd Engineers

Re: Revised Addendum to the 2010 Hollister Area Urban Water Management Plan (UWMP)

Introduction

The Department of Water Resources (DWR) has reviewed the 2010 Hollister Area Urban Water Management Plan (UWMP) and the staff member in charge of the review, Gwen Huff, has requested a specific revision of gross water use, baselines per capita daily use, and the per capita demand targets. In the UWMP, the Hollister Urban Area regional gross water use, baselines, and targets were calculated for Hollister and Sunnyslope separately and then the region's goals were presented as a weighted average of the two. However, DWR indicates that because the portion of Lessalt Water Treatment Plant that is delivered to Hollister and Sunnyslope was not monitored discretely for each service area, we cannot look at the two entities as separate providers but must combine their gross water use as a regional total.

Combining baseline water use

Gross water use includes all water into the system:

- groundwater monitored at the point of production
- CVP imports to Lessalt treatment plant total inflow metered, but Hollister and Sunnyslope individual portions are not
- unaccounted for water losses, etc.

Total HUA water use in 2005 totaled 6.14 MGD or 6,871 AFY; total HUA water deliveries in 2005 totaled 6,791 AFY (UWMP Table 3-1). The difference between the gross water use (used in baseline calculations) and the water deliveries was 100 AFY of unaccounted for water, including system losses and leaks.

Revisions to the baseline water use and water use targets

Combining Hollister and Sunnyslope values and calculating the gross water use, baselines, and targets as a region will reduce the 10-year baseline by four gallons per person per day (gpcd) to 157 gpcd. Table 1 shows the baseline selected for the regional alliance and Table 2 shows the baseline period calculations for the Hollister Urban Area. The original UWMP reported a 10-year baseline of 161 gpcd (shown in Table 3); different baseline periods were selected for each Hollister and Sunnyslope to achieve the most favorable baseline. The 5-year range baseline remains the same as in the UWMP, because the same years were selected for Hollister and Sunnyslope (Table 4). Therefore, the minimum water use requirements remain the same, as they are based on the 5-year baseline.

The water demand targets are calculated as a percentage of baseline; purveyors must achieve 10 percent of the baseline water use by 2015 and 20 percent by 2020. The new targets are shown in Table 5 and the targets reported in the UWMP are shown in Table 6. The targets are reduced by 3.6 gpcd and 3.2 gpcd for 2015 and 2020 respectively.

Conclusion

Ms. Huff at DWR communicated that DWR will accept the numbers reported in the submitted UWMP if the new targets (based on the regional baseline rather than the weighted average of the supplier's baseline) were within a few GPCD of the reported regional gross water, baseline and target. Given that the difference in the baseline is four gpcd and the difference in the targets is less than four gcpd, it is our opinion that the UWMP does not need to be revised and the plan does not need to be re-adopted.

	Table 1						
	Base Period Ranges						
Base	Parameter	Value	Units				
	2008 total water deliveries	6,460	AFY				
40 45 45	2008 total volume of delivered recycled water	0	AFY				
10- to 15- Year Base	2008 recycled water as a percent of total deliveries	0	percent				
Period	Number of years in base period ¹	10	years				
i chou	Year beginning base period range	1997					
	Year ending base period range ²	2006					
5-Year Base	Number of years in base period	5	years				
Period	Year beginning base period range	2003					
i enou	Year ending base period range ³	2007					

¹ If the 2008 recycled water percent is less than 10 percent, then the first base period is a continuous 10-year period. If the amount of recycled water delivered in 2008 is 10 percent or greater, the first base period is a continuous 10- to 15-year period. ² The ending year must be between December 31, 2004 and December 31, 2010.

³The ending year must be between December 31, 2007 and December 31, 2010.

Table 2 Base Daily Per Capita Water Use Hollister Urban Area 10-Year Range					
Base P	eriod Year	Distribution System	Daily System Gross Water Use (mgd)	Annual Daily Per Capita Water	
Sequence Year	Calendar Year	Population		Use (gpcd)	
Year 1	1996	32,341	4.92	152	
Year 2	1997	35,114	5.79	165	
Year 3	1998	35,948	5.18	144	
Year 4	1999	38,157	5.69	149	
Year 5	2000	39,092	6.44	165	
Year 6	2001	40,157	6.37	159	
Year 7	2002	40,661	6.60	162	
Year 8	2003	40,464	6.52	161	
Year 9	2004	40,369	6.55	162	
Year 10	2005	40,307	6.14	152	
			Base Daily Per Capita Water Use	157	

Table 3 Base Daily Per Capita Water Use Reported in the 2010 UWMP				
Population ¹	Annual Daily Per Capita Water Use (gpcd)			
23,254	149			
15,838	178			
39,092	161			
	Per Capita Water Use in the 2010 UWMP Population ¹ 23,254 15,838			

1Population based on US Census 2000.

Table 4 Base Daily Per Capita Water Use Hollister Urban Area 5-Year Range					
Base Period YearDistributionDaily SystemAnnual DailySequenceCalendarSystemGross WaterWater UseYearYearPopulationUse (mgd)(gpcd)					
Year 1	2003	40,464	6.52	161	
Year 2	2004	40,369	6.55	162	
Year 3	2005	40,307	6.14	152	
Year 4	2006	40,458	5.91	146	
Year 5	2007	40,230	6.17	153	
		Base Daily Per C	apita Water Use	155	

Table 5 Baseline and Target Per Capita Water Use (gcpd)							
Retailer	Population	Baseline Water Use		Minimum Water Use Reduction Requirement		Target Water Use	
		10-year	5-year	2015	2020	2015	2020
HUA	39,092	157	155	152	147	141.5	125.7

Table 6 Reported in the 2010 UWMP Baseline and Target Per Capita Water Use (gcpd)							
Retailer	Population	Population Baseline Water Use Baseline Water Use Reduction Target Water Use Requirement					/ater Use
		10-year	5-year	2015	2020	2015	2020
Hollister	23,254	149	137	140	130	135	120
Sunnyslope	15,838	178	182	176	173	161	143
HUA	39,092	161	155	154	147	145.1	129.0

SB X7-7 Table 0: Units of Measure Used in UWMP*

(select one from the drop down list)

Acre Feet

*The unit of measure must be consistent with Table 2-3

NOTES:

Baseline	Parameter	Value	Units			
	2008 total water deliveries	6,460	Acre Feet			
	2008 total volume of delivered recycled water	0	Acre Feet			
10- to 15-year	2008 recycled water as a percent of total deliveries	0.00%	Percent			
baseline period	Number of years in baseline period ¹	10	Years			
	Year beginning baseline period range 199					
	Year ending baseline period range ² 2005					
Ever	Number of years in baseline period	5	Years			
5-year baseline period	Year beginning baseline period range 2003					
baseline periou	Year ending baseline period range ³ 2007					
lelivered in 2008 is 10 pe	er percent is less than 10 percent, then the first baseline period is a continuous 10 rcent or greater, the first baseline period is a continuous 10- to 15-year period.)-year period. If the amo	ount of recycled water			
The ending year must be	e between December 31, 2004 and December 31, 2010.					
The ending year must be	e between December 31, 2007 and December 31, 2010.					

SB X7-7 Table 2: Method for Population Estimates				
	Method Used to Determine Population (may check more than one)			
	 Department of Finance (DOF) DOF Table E-8 (1990 - 2000) and (2000-2010) and DOF Table E-5 (2011 - 2015) when available 			
	2. Persons-per-Connection Method			
~	3. DWR Population Tool			
	4. Other DWR recommends pre-review			
NOTES:				

SB X7-7 Table 3: Service Area Population				
Y	'ear	Population		
10 to 15 Ye	ear Baseline P	opulation		
Year 1	1996	32,597		
Year 2	1997	35,120		
Year 3	1998	35,972		
Year 4	1999	38,200		
Year 5	2000	39,134		
Year 6	2001	40,165		
Year 7	2002	40,655		
Year 8	2003	40,488		
Year 9	2004	40,399		
Year 10	2005	40,343		
Year 11				
Year 12				
Year 13				
Year 14				
Year 15				
5 Year Base	eline Populati	on		
Year 1	2003	40,488		
Year 2	2004	40,399		
Year 3	2005	40,343		
Year 4	2006	40,549		
Year 5	2007	40,284		
2015 Comp	pliance Year P	opulation		
2	015	42,642		
NOTES: The	e populations	for Hollister and		

NOTES: The populations for Hollister and Sunnyslope were calculated speeratly then added together.

Baseline Year Fm SB X7-7 Table 3Volume Into Distribution System Fm SB X7-7 Table 310 to 15 V=T Baseline - STOS Water UYear 11996Year 219976,486Year 31998Year 419996,378Year 520007,235Year 62001Year 72002Year 82003Year 92004Year 102005Year 11000Year 120Year 130Year 14000Year 150731010Year 1401010Year 150100Year 142003Year 32005Year 32005Year 32005Year 32005Year 42006Year 42006	Exported Water	Change in Dist. System Storage (+/-)	Deduction Indirect Recycled Water Fm SB X7-7 Table 4-B 0 0 0 0 0 0	Water Delivered for Agricultural Use	Process Water Fm SB X7-7 Table(s) 4-D	Annual Gross Water Use 5,525 6,486
Year 119965,525Year 219976,486Year 319985,798Year 419996,378Year 520007,235Year 620017,141Year 720027,397Year 820037,301Year 920047,356Year 1020057,052Year 1200Year 1300Year 1400Year 1500Year 120037,301Year 320047,356	se		0 0 0		0	
Year 2 1997 6,486 Year 3 1998 5,798 Year 4 1999 6,378 Year 5 2000 7,235 Year 6 2001 7,141 Year 7 2002 7,397 Year 8 2003 7,301 Year 9 2004 7,356 Year 10 2005 7,052 Year 12 0 0 Year 13 0 0 Year 14 0 0 Year 15 0 0 Year 15 0 0 Year 14 0 0 Year 15 0 0 Year 14 2003 7,301 Year 2 2004 7,356 Year 3 2005 6,872			0 0 0		0	
Year 3 1998 5,798 Year 4 1999 6,378 Year 5 2000 7,235 Year 6 2001 7,141 Year 7 2002 7,397 Year 8 2003 7,301 Year 9 2004 7,356 Year 10 2005 7,052 Year 11 0 0 Year 12 0 0 Year 13 0 0 Year 14 0 0 Year 15 0 0 Year 1 2003 7,301 Year 13 0 0 Year 14 0 0 Year 15 0 0 Year 15 0 0 Year 14 2003 7,301 Year 1 2003 7,301 Year 2 2004 7,356 Year 3 2005 6,872			0 0			6,486
Year 4 1999 6,378 Year 5 2000 7,235 Year 6 2001 7,141 Year 7 2002 7,397 Year 8 2003 7,301 Year 9 2004 7,356 Year 10 2005 7,052 Year 11 0 0 Year 12 0 0 Year 13 0 0 Year 14 0 0 Year 15 0 0 Year 14 0 0 Year 15 0 0 Year 15 0 0 Year 1 2003 7,301 Year 2 2004 7,356			0		0	0,100
Year 5 2000 7,235 Year 6 2001 7,141 Year 7 2002 7,397 Year 8 2003 7,301 Year 9 2004 7,356 Year 10 2005 7,052 Year 11 0 0 Year 12 0 0 Year 13 0 0 Year 14 0 0 Year 15 0 0 Year 14 0 0 Year 15 0 0 Year 14 0 7,301 Year 15 0 0 Year 15 0 0 Year 14 2003 7,301 Year 1 2003 7,301 Year 2 2004 7,356 Year 3 2005 6,872					0	5,798
Year 6 2001 7,141 Year 7 2002 7,397 Year 8 2003 7,301 Year 9 2004 7,356 Year 10 2005 7,052 Year 11 0 0 Year 12 0 0 Year 13 0 0 Year 14 0 0 Year 15 0 0 Year 15 0 0 Year 12 0, 0 Year 13 0, 0 Year 14 0 0 Year 15 0 0 Year 15 0 0 Year 15 0 0 Year 14 2003 7,301 Year 1 2003 7,301 Year 2 2004 7,356 Year 3 2005 6,872			0		0	6,378
Year 7 2002 7,397 Year 8 2003 7,301 Year 9 2004 7,356 Year 10 2005 7,052 Year 11 0 0 Year 12 0 0 Year 13 0 0 Year 14 0 0 Year 15 0 0 Year 15 0 0 Year 15 0 0 Year 15 0 0 Year 14 0 0 Year 15 0 0 Year 15 0 0 Year 15 0 0 Year 1 2003 7,301 Year 2 2004 7,356 Year 3 2005 6,872			Ŭ		0	7,235
Year 8 2003 7,301 Year 9 2004 7,356 Year 10 2005 7,052 Year 11 0 0 Year 12 0 0 Year 13 0 0 Year 14 0 0 Year 15 0 0 Year 15 0 0 Year 14 0 0 Year 15 0 0 Year 14 0 0 Year 15 0 0 Year 15 0 0 Year 15 0 0 Year 1 2003 7,301 Year 1 2004 7,356 Year 3 2005 6,872			0		0	7,141
Year 9 2004 7,356 Year 10 2005 7,052 Year 11 0 0 Year 12 0 0 Year 13 0 0 Year 14 0 0 Year 15 0 0 10 - 15 year baseline average gross wa 5 Year Baseline - Gross Water Use Year 1 2003 7,301 Year 2 2004 7,356 Year 3 2005 6,872			0		0	7,397
Year 10 2005 7,052 Year 11 0 0 Year 12 0 0 Year 13 0 0 Year 14 0 0 Year 15 2003 7,301 Year 1 2003 7,356 Year 3 2005 6,872			0		0	7,301
Year 11 0 0 Year 12 0 0 Year 13 0 0 Year 14 0 0 Year 15 0 0 Year 15 0 0 10 - 15 year baseline average gross was 5 Year Baseline - Gross Water Use Year 1 2003 7,301 Year 2 2004 7,356 Year 3 2005 6,872			0		0	7,356
Year 12 0 0 Year 13 0 0 Year 14 0 0 Year 15 0 0 Year 15 0 0 10 - 15 year baseline average gross wa 5 5 Year Baseline - Gross Water Use Year 1 Year 2 2004 7,301 Year 3 2005 6,872			0		0	7,052
Year 13 0 0 Year 14 0 0 Year 15 0 0 Year 15 0 0 10 - 15 year baseline average gross was 5 5 Year Baseline - Gross Water Use Year 1 Year 2 2004 7,301 Year 3 2005 6,872			0		0	0
Year 14 0 0 Year 15 0 0 10 - 15 year baseline average gross was 3 3 5 Year Baseline - Gross 3 3 Year 1 2003 7,301 Year 2 2004 7,356 Year 3 2005 6,872			0		0	0
Year 15 0 0 10 - 15 year baseline average gross waster to see the second seco			0		0	0
10 - 15 year baseline average gross wa5 Year Baseline - Gross Water UseYear 12003Year 22004Year 320056,872			0		0	0
5 Year Baseline - Gross Water Use Year 1 2003 7,301 Year 2 2004 7,356 Year 3 2005 6,872			0		0	0
Year 120037,301Year 220047,356Year 320056,872	10 - 15 year baseline average gross water use					
Year 2 2004 7,356 Year 3 2005 6,872						
Year 3 2005 6,872			0		0	7,301
			0		0	7,356
Year 4 2006 6,625			0		0	6,872
			0		0	6,625
Year 5 2007 6,906			0		0	6,906
5 year baseline average gross water use						7,012
2015 Compliance Year - Gross Water U	e					
2015 4,941			0		0	4,941
* NOTE that the units of measure must		sistent through	nout the UWM	1P, as reported	d in Table 2-3	

SB X7-7 Table 4-A: Volume Entering the Distribution System(s) Complete one table for each source.						
Name of Se	ource	CVP Water				
This water	source is:					
	The supplie	er's own water	source			
~	A purchase	d or imported	source			
Fm SB X7-		Volume Entering Distribution System	Meter Error Adjustment* <i>Optional</i> (+/-)	Corrected Volume Entering Distribution System		
10 to 15 Year Baseline - Water into Distribution System						
Year 1	1996			0		
Year 2	1997			0		
Year 3	1998			0		
Year 4	1999			0		
Year 5	2000			0		
Year 6	2001			0		
Year 7	2002	21		21		
Year 8	2003	2494		2,494		
Year 9	2004	2101		2,101		
Year 10	2005	1975		1,975		
Year 11	0			0		
Year 12	0			0		
Year 13	0			0		
Year 14	0			0		
Year 15	0			0		
5 Year Baseline - Water into Distribution System						
Year 1	2003	2494		2,494		
Year 2	2004	2101		2,101		
Year 3	2005	1795		1,795		
Year 4	2006	1872		1,872		
Year 5	2007	1476		1,476		
2015 Comp	oliance Yea	r - Water into I	Distribution Sys	tem		
20	15	1714		1,714		
* Mete	r Error Adjust	ment - See guidar Methodologies D	nce in Methodology Document	v 1, Step 3 of		
NOTES:						

SB X7-7 Table 4-A: Volume Entering the Distribution				
Name of S	ource	COH WELLS		
This water	source is:			
~	The supplie	er's own water	· source	
	A purchase	d or imported	source	
Baseline Year Fm SB X7-7 Table 3		Volume Entering Distribution System	Meter Error Adjustment* <i>Optional</i> (+/-)	Corrected Volume Entering Distribution System
10 to 15 Ye	ear Baseline	e - Water into [Distribution Sys	tem
Year 1	1996	3386		3,386
Year 2	1997	3848		3,848
Year 3	1998	3441		3,441
Year 4	1999	3558		3,558
Year 5	2000	4021		4,021
Year 6	2001	3851		3,851
Year 7	2002	4120		4,120
Year 8	2003	2754		2,754
Year 9	2004	2865		2,865
Year 10	2005	3240		3,240
Year 11	0			0
Year 12	0			0
Year 13	0			0
Year 14	0			0
Year 15	0			0
5 Year Base	eline - Wate	er into Distribu	ition System	
Year 1	2003	2754		2,754
Year 2	2004	2865		2,865
Year 3	2005	3240		3,240
Year 4	2006	2620		2,620
Year 5	2007	3025		3,025
2015 Comp	oliance Year	r - Water into I	Distribution Sys	tem
	15	1949		1,949
* Mete	er Error Adjust	ment - See guidar Methodologies D	nce in Methodology Document	1, Step 3 of
NOTES:				

SB X7-7 Table 4-A: Volume Entering the Distribution						
Name of S		SSCWD Wells				
This water	source is:					
~	The supplier's own water source					
	A purchased or imported source					
Baselir Fm SB X7-	ne Year -7 Table 3	Volume Entering Distribution System	Meter Error Adjustment* <i>Optional</i> (+/-)	Corrected Volume Entering Distribution System		
10 to 15 Ye	ear Baseline	e - Water into I	Distribution Sys	tem		
Year 1	1996	2139		2,139		
Year 2	1997	2638		2,638		
Year 3	1998	2357		2,357		
Year 4	1999	2820		2,820		
Year 5	2000	3214		3,214		
Year 6	2001	3290		3,290		
Year 7	2002	3256		3,256		
Year 8	2003	2053		2,053		
Year 9	2004	2390		2,390		
Year 10	2005	1837		1,837		
Year 11	0			0		
Year 12	0			0		
Year 13	0			0		
Year 14	0			0		
Year 15	0			0		
5 Year Base	eline - Wate	er into Distribu	ition System			
Year 1	2003	2053		2,053		
Year 2	2004	2390		2,390		
Year 3	2005	1837		1,837		
Year 4	2006	2133		2,133		
Year 5	2007	2405		2,405		
2015 Com	oliance Year	r - Water into l	Distribution Sys	tem		
20	15	1278		1,278		
* Mete	er Error Adjust	ment - See guidar Methodologies D	nce in Methodology Document	1, Step 3 of		
NOTES:						

SB X7-7 T	SB X7-7 Table 4-B: Indirect Recycled Water Use Deduction (For use only by agencies that are deducting indirect recycled water)									
			Surfac	e Reservoir A	ugmentation		G	roundwater Rec	harge	
Baselir Fm SB X7-	ne Year -7 Table 3	Volume Discharged from Reservoir for Distribution System Delivery	Percent Recycled Water	Recycled Water Delivered to Treatment Plant	Transmission/ Treatment Loss	Recycled Volume Entering Distribution System from Surface Reservoir Augmentation	Recycled Water Pumped by Utility*	Transmission/ Treatment Losses	Recycled Volume Entering Distribution System from Groundwater Recharge	Total Deductible Volume of Indirect Recycled Water Entering the Distribution System
10-15 Year	Baseline - I	Indirect Recycle	d Water Us	e						
Year 1	1996			0		0			0	0
Year 2	1997			0		0			0	0
Year 3	1998			0		0			0	0
Year 4	1999			0		0			0	0
Year 5	2000			0		0			0	0
Year 6	2001			0		0			0	0
Year 7	2002			0		0			0	0
Year 8	2003			0		0			0	0
Year 9	2004			0		0			0	0
Year 10	2005			0		0			0	0
Year 11	0			0		0			0	0
Year 12	0			0		0			0	0
Year 13	0			0		0			0	0
Year 14	0			0		0			0	0
Year 15	0			0		0			0	0
	r	ect Recycled Wa	ater Use			-	Γ		-	
Year 1	2003			0		0			0	0
Year 2	2004			0		0			0	0
Year 3	2005			0		0			0	0
Year 4	2006			0		0			0	0
Year 5	2007	direct Recycled	Mator Hor	0		0			0	0
		direct Recycled	water Use	0		0			0	0
)15			0		0			0	0
	-				-	-	cycled Water	Pumped by Utilit	y". The volume re	eported in this cell must
	n total grou	undwater pump	ed - See Me	thodology 1,	Step 8, section 2.	.C.				
NOTES:										

SB X7-7 Table 4-C: Process Water Deduction Eligibility

(For use only by agencies that are deducting process water) Choose Only One

	Criteria 1 - Industrial water use is equal to or greater than 12% of gross water use. Complete SB X7-7 Table 4-C.1
	Criteria 2 - Industrial water use is equal to or greater than 15 GPCD. Complete SB X7-7 Table 4-C.2
	Criteria 3 - Non-industrial use is equal to or less than 120 GPCD. Complete SB X7-7 Table 4-C.3
	Criteria 4 - Disadvantaged Community. Complete SB x7-7 Table 4-C.4
NOTES:	

SB X7-7 Table 5: Gallons Per Capita Per Day (GPCD)							
Fm SB X	ine Year 7-7 Table 3 ear Baseline G	Service Area Population Fm SB X7-7 Table 3	Annual Gross Water Use Fm SB X7-7 Table 4	Daily Per Capita Water Use (GPCD)			
			5 5 25	454			
Year 1	1996	32,597	5,525	151			
Year 2	1997	35,120	6,486	165			
Year 3	1998	35,972	5,798	144			
Year 4	1999	38,200	6,378	149			
Year 5	2000	39,134	7,235	165			
Year 6	2001	40,165	7,141	159			
Year 7	2002	40,655	7,397	162			
Year 8	2003	40,488	7,301	161			
Year 9	2004	40,399	7,356	163			
Year 10	2005	40,343	7,052	156			
Year 11	0	0	0				
Year 12	0	0	0				
Year 13	0	0	0				
Year 14	0	0	0				
Year 15 0		0	0				
10-15 Year	10-15 Year Average Baseline GPCD157						
5 Year Bas	eline GPCD						
Baseline Year Fm SB X7-7 Table 3		Service Area Population <i>Fm SB X7-7</i> <i>Table 3</i>	Gross Water Use Fm SB X7-7 Table 4	Daily Per Capita Water Use			
Year 1	2003	40,488	7,301	161			
Year 2	2004	40,399	7,356	163			
Year 3	2005	40,343	6,872	152			
Year 4	2006	40,549	6,625	146			
Year 5	2007	40,284	6,906	153			
5 Year Ave	rage Baseline	GPCD		155			
2015 Com	pliance Year G	GPCD					
2	015	42,642	4,941	103			
NOTES:							

SB X7-7 Table 6 : Gallons per Capita per Day Summary From Table SB X7-7 Table 5				
10-15 Year Baseline GPCD 157				
5 Year Baseline GPCD	155			
2015 Compliance Year GPCD 103				
NOTES:				

SB X7-7 Table 7: 2020 Target Method Select Only One						
Targe	et Method	Supporting Documentation				
\checkmark	Method 1	SB X7-7 Table 7A				
	Method 2	SB X7-7 Tables 7B, 7C, and 7D Contact DWR for these tables				
	Method 3	SB X7-7 Table 7-E				
	Method 4	Method 4 Calculator				
NOTES:						

SB X7-7 Table 7-A: Target Method 1 20% Reduction					
10-15 Year Baseline GPCD	2020 Target GPCD				
157	126				
NOTES:					

SB X7-7 Table 7-F: Confirm Minimum Reduction for 2020 Target						
5 Year Baseline GPCD From SB X7-7 Table 5	Maximum 2020 Target*	Calculated 2020 Target Fm Appropriate Target Table	Confirmed 2020 Target			
155	147	126	126			
* Maximum 2020 Target is 95% of the 5 Year Baseline GPCD						
NOTES:						

SB X7-7 Table 8: 2015 Interim Target GPCD						
Confirmed 2020 Target <i>Fm SB X7-7</i> Table 7-F	10-15 year Baseline GPCD <i>Fm SB X7-7</i> Table 5	2015 Interim Target GPCD				
126	157	142				
NOTES:	NOTES:					

			Optional	Adjustments <i>(in</i>	GPCD)			Did Supplier
Actual 2015 GPCD		Extraordinary Events	Weather Normalization	Economic Adjustment	TOTAL Adjustments	Adjusted 2015 GPCD	2015 GPCD Achieve (Adjusted if Targeted applicable) Reduction for 2015?	
103	142	From Methodology 8 (Optional)	From Methodology 8 (Optional)	From Methodology 8 (Optional)	0	103	103	YES

APPENDIX G – WATER SHORTAGE CONTINGECY PLAN



March 29, 2016

MEMORANDUM

То:	Shawn Novak, San Benito County Water District
From:	Maureen Reilly, PE
Re:	Water Shortage Contingency Plan (WSCP)

The Urban Water Management Plan requires agencies to document their Water Shortage Contingency Plan (WSCP). The current Hollister Urban Area (HUA) plan is a general plan and does not provide detailed prohibitions and limits for end users in the area. Mindful of recent drought conditions, we recommend that a new WSCP be developed and approved by each agency, in parallel with the UWMP process.

The following is a recommended four-stage rationing plan with voluntary and mandatory rationing depending on the severity of the water supply shortage. This water shortage response was based in part on the Sunnyslope *No Water Waste* Ordinance No. 45 and was first documented for the HUA as part of the 2000 UWMP. Due to recent drought conditions and state mandated water demand reduction, the prohibited uses and restrictions were refined and expanded. In order to support consistency within the greater Pajaro River region, the Santa Clara County Model Water Conservation Ordinance has been used as a template and is included as Attachment A. This WSCP is draft and intended for review by each agency: City of Hollister, Sunnyslope County Water District, and San Benito County Water District.

DECLARATION OF SHORTAGE CONDITIONS

The Water Supply Shortage conditions may be declared by Resolution of any one of the agencies and adopted at a regular or special public meeting held in accordance with state law Procedures for Determination/Notification of Water Supply Shortage. The mandatory conservation requirements applicable to the level of Water Supply Shortage conditions will take effect immediately after the shortage level is declared.

Causes of supply shortages could include but are not limited to:

- reduced CVP allocations
- groundwater levels declining at a critical rate or reaching a critical level
- drought with reduced runoff and recharge from precipitation
- infrastructure failure (e.g., failed well, ruptured tank, severed pipeline)

- water quality impacts
- natural disasters interrupting supply.

A declaration of shortage would be justified through description of the causes, including one or more of the above, and depending on the shortage severity (e.g., rapidity of onset, magnitude, potential duration) would indicate a stage of action (see below). Each stage includes a required amount of demand reduction; however, the supply shortage itself does not have to be quantified. This allows timely response and provides flexibility to decision makers.

STAGES OF ACTION

The four stages are responsive to the severity of a supply reduction and expressed in terms of an appropriate reduction in demand. We recommend description of the stages as a percent demand reduction regardless of the cause of the shortage.

The table below shows the four stages of action, the desired demand reduction, and a summary of actions.

Stage	Program	Demand Reduction	Summary of actions
1	Voluntary	Up to 15 %	Restrictions on outdoor irrigation to avoid wasteFix Leaks
2	Mandatory	Up to 25 %	 Stage 1 activities become mandatory The operation of non-recirculating decorative fountains using potable water is restricted No refilling of swimming pools
3	Mandatory	Up to 35 %	 Continue Stage 1-2 activities No irrigation with 48 hours of rainfall No new landscaping or plantings installed between May and October Leaks must be fixed within 48 hours
4	Mandatory	Above 50%	 Continue Stage 1-3 activities Irrigation of outdoor landscaping with potable water is forbidden at all times Leaks must be fixed within 24 hours

PROHIBITIONS AND LIMITATIONS BY STAGE

Stage 1

The first stage applies voluntary rationing to reach the demand reduction goal of 15 percent.

Draft Water Shortage Contingency Plan / Hollister Urban Area

- Recommended Watering Hours: Watering or irrigating of lawn, landscape or other vegetated area with potable water is discouraged between the hours of 9:00 a.m. and 5:00 p.m. Pacific Standard/Daylight Savings Time.
- 1.2. Recommended Limit on Watering Duration: Watering or irrigating of lawn, landscape or other vegetated area with potable water using a landscape irrigation system or a watering device that is not continuously attended is recommended to be limited to no more than three days a week with a duration of fifteen (15) minutes watering per water day per station. This subsection does not apply to landscape irrigation systems that exclusively use very low- flow drip type irrigation systems when no emitter produces more than two (2) gallons of water per hour and weather based controllers or stream rotor sprinklers that meet a 70% efficiency standard. The use of recycled water is exempt from this prohibition.
- 1.3. Eliminate Excessive Water Flow or Runoff: Watering or irrigating of any lawn, landscape or other vegetated area in a manner that causes or allows excessive water flow or runoff onto an adjoining sidewalk, driveway, street, alley, gutter or ditch is strongly discouraged.
- 1.4. Discourage Washing Down Hard or Paved Surfaces: Washing down hard or paved surfaces, including but not limited to sidewalks, walkways, driveways, parking areas, tennis courts, patios or alleys, is discouraged except by use of a hand-held bucket or similar container, a hand-held hose equipped with a positive self-closing water shut-off device, a low- volume, high-pressure cleaning machine equipped to recycle any water used, or a low-volume high-pressure water broom.
- 1.5. Fix Leaks, Breaks or Malfunctions: Excessive use, loss or escape of water through breaks, leaks or other malfunctions in the water user's plumbing or distribution system for any period of time after such escape of water should have reasonably been discovered and corrected are encouraged to be corrected as soon as practical.
- 1.6. Recirculating Water for Water Fountains and Decorative Water Features: Operating a water fountain or other decorative water features that uses recirculated water is encouraged.
- 1.7. Washing Vehicles: Using water to wash or clean a vehicle, including but not limited to any automobile, truck, van, bus, motorcycle, boat or trailer, whether motorized or not is discouraged, except by use of a hand-held bucket or similar container or a hand-held hose equipped with a positive self-closing water shut-off nozzle or device. Washing vehicles at commercial conveyor car wash systems with re-circulating water systems is recommended.
- 1.8. Drinking Water Served Upon Request: Eating or drinking establishments, including but not limited to a restaurant, hotel, cafe, cafeteria, bar, or other public place where food or drinks are sold, served, or offered for sale, are encouraged to providing drinking water to any person only when expressly requested.
- 1.9. Commercial Lodging Establishments Encouraged to Provide Guests Option to Decline Daily Linen Services: Hotels, motels and other commercial lodging establishments are encouraged to provide customers the option of not having

towels and linen laundered daily. Commercial lodging establishments are encouraged to prominently display notice of this option in each bathroom using clear and easily understood language.

- 1.10. Installation of Single Pass Cooling Systems: Installation of single pass cooling systems is discouraged in buildings requesting new water service.
- 1.11. Installation of Non-recirculating Water System in Commercial Car Wash and Laundry Systems: Installation of non-recirculating water systems is discouraged in new commercial conveyor car wash and new commercial laundry systems.
- 1.12. Restaurants Encouraged to Use Water Conserving Dish Wash Spray Valves: Food preparation establishments, such as restaurants or cafes, are encouraged to use water conserving dish wash spray valves.
- 1.13. Commercial Car Wash Systems: All commercial conveyor car wash systems are encouraged to install operational re-circulating water systems.
- 1.14. Pool Covers: It is recommended that all existing pools use a pool cover or solar blanket to reduce water loss due to evaporation.

Stage 2

The second stage seeks a 25 percent reduction of future supplies, and uses restricted building permits, mandatory rationing, and reduction by customer types. Stage 2 continues the voluntary reductions in Stage 1. In addition, the following reduction requirements become mandatory:

- 2.1. Limits on Watering Hours: Watering or irrigating of lawn, landscape or other vegetated area with potable water is prohibited between the hours of 9:00 a.m. and 5:00 p.m. Pacific Standard/Daylight Savings Time on any day, except by use of a hand-held bucket or similar container, a hand-held hose equipped with a positive self-closing water shut-off nozzle or device, or for very short periods of time for the express purpose of adjusting or repairing an irrigation system. The use of recycled water is exempt from this prohibition.
- 2.2. Limit on Watering Duration: Watering or irrigating of lawn, landscape or other vegetated area with potable water using a landscape irrigation system or a watering device that is not continuously attended is limited to no more than fifteen (15) minutes watering per designated water day per station. This subsection does not apply to landscape irrigation systems that exclusively use very low-flow drip type irrigation systems when no emitter produces more than two (2) gallons of water per hour and weather based controllers or stream rotor sprinklers that meet a 70% efficiency standard. The use of recycled water is exempt from this prohibition.
- 2.3. Limits on Watering Days: Watering or irrigating of lawn, landscape or other vegetated area with potable water is limited to three days per week from April through October. The watering days are designated depending upon house address (odd house and no house address Monday, Wednesday, and Friday, even house address Tuesday, Thursday, and Saturday). During the months of November through

March, watering or irrigating of lawn, landscape or other vegetated area with potable water is limited to no more than one day per week (odd house and no house address - Monday, even house address - Tuesday). This provision does not apply to landscape irrigation zones that exclusively use very low flow drip type irrigation systems when no emitter produces more than two (2) gallons of water per hour. This provision also does not apply to watering or irrigating by use of a handheld bucket or similar container, a hand-held hose equipped with a positive selfclosing water shut-off nozzle or device, or for very short periods of time for the express purpose of adjusting or repairing an irrigation system.

- 2.4. No Excessive Water Flow or Runoff: The application of water is prohibited to outdoor landscapes in a manner that causes runoff such that water flows onto adjacent property, non- irrigated areas, private and public walkways, driveway, street, alley, gutter, ditch, parking lots, or structures.
- 2.5. No Washing Down Hard or Paved Surfaces: Washing down hard or paved surfaces is prohibited, including but not limited to buildings, structures, sidewalks, walkways, driveways, parking areas, tennis courts, patios or alleys.
- 2.6. Obligation to Fix Leaks, Breaks or Malfunctions: All leaks, breaks, or other malfunctions in the water user's plumbing or distribution system must be repaired within seventy-two (72) hours of notification by the city unless other arrangements are made with the city.
- 2.7. Recirculating Water Required for Water Fountains and Decorative Water Features: Operating a water fountain or other decorative water feature that does not use recirculated water is prohibited.
- 2.8. Limits on Washing Vehicles: Using water to wash or clean a vehicle is prohibited, including but not limited to any automobile, truck, van, bus, motorcycle, boat or trailer, whether motorized or not, except by use of a hand-held bucket or similar container or a hand-held hose equipped with a positive self-closing water shut-off nozzle or device. This subsection does not apply to any commercial car washing facility.
- 2.9. Drinking Water Served Upon Request Only: Eating or drinking establishments, including but not limited to a restaurant, hotel, cafe, cafeteria, bar, or other public place where food or drinks are sold, served, or offered for sale, are prohibited from providing drinking water to any person unless expressly requested.
- 2.10. Commercial Lodging Establishments Must Provide Guests Option to Decline Daily Linen Services: Hotels, motels and other commercial lodging establishments must provide customers the option of not having towels and linen laundered daily. Commercial lodging establishments must prominently display notice of this option in each bathroom using clear and easily understood language.
- 2.11. No Installation of Single Pass Cooling Systems: Installation of single pass cooling systems is prohibited in buildings requesting new water service.

- 2.12. No Installation of Non-re-circulating in Commercial Car Wash and Laundry Systems: Installation of non-re-circulating water systems is prohibited in new commercial conveyor car wash and new commercial laundry systems.
- 2.13. Commercial Car Wash Systems: Within one year of passage of this Ordinance, all commercial conveyor car wash systems must have installed operational recirculating water systems, or must have secured a waiver of this requirement from the city.
- 2.14. Pool Covers and Refilling of Existing Pools: All new pools shall be required to have a pool cover or solar blanket to reduce water loss through evaporation. Refilling of existing private pools is prohibited, except to maintain water levels, unless the pool is in imminent danger of failure.

Stage 3

Stage 3 aims for a 35 percent reduction. It allows the agencies to restrict water uses to priority needs and the prohibited or limited uses of water become more restrictive.

- 3.1. Limits on Watering Days: Watering or irrigating of lawn, landscape or other vegetated area with potable water is limited to two days per week from April through October. The watering days are designated depending upon house address (odd house and no house address - Monday and Thursday, even house address -Tuesday, and Friday). During the months of November through March, watering or irrigating of lawn, landscape or other vegetated area with potable water is limited to no more than one day per week (odd house and no house address - Monday, even house address - Tuesday). This provision does not apply to landscape irrigation zones that exclusively use very low flow drip type irrigation systems when no emitter produces more than two (2) gallons of water per hour. This provision also does not apply to watering or irrigating by use of a hand-held bucket or similar container, a hand-held hose equipped with a positive self-closing water shut-off nozzle or device, or for very short periods of time for the express purpose of adjusting or repairing an irrigation system. Use of recycled water for irrigation is exempt from these restrictions.
- 3.2. Irrigating Within 48 Hours of Rainfall: The applications of potable water to outdoor landscapes during and within 48 hours following measurable rainfall is prohibited.
- 3.3. Irrigation outside Newly Constructed Homes: The irrigation with potable water outside of newly constructed homes and buildings in a manner inconsistent with regulations or other requirements established by the California Building Standards Commission is prohibited.
- 3.4. Installation of New Turf: Adding new turf landscaping is prohibited.
- 3.5. Prohibition against Watering Turf in Medians: The irrigation with potable water of ornamental turf on public street medians, including roundabouts is prohibited.
- 3.6. Obligation to Fix Leaks, Breaks or Malfunctions: All leaks, breaks, or other malfunctions in the water user's plumbing or distribution system must be repaired

within forty- eight (48) hours of notification by the city unless other arrangements are made with the city.

- 3.7. Limits on Filling Ornamental Lakes or Ponds: Filling or re-filling ornamental lakes or ponds with potable water is prohibited, except to the extent needed to sustain aquatic life, provided that such animals are of significant value and have been actively managed within the water feature prior to declaration of a supply shortage level under this section.
 - 3.8. New Pools. Installation and filling of new private pools are prohibited,
- 3.9. Drought Water Rates: Each agency may consider adopting rate structures and other pricing mechanisms to maximize water conservation. These rates should be consistent with Prop218 requirements.
- 3.10. Any of the HUA agencies reserve the right to restrict water use for priority uses.

Stage 4

The final stage seeks a 50 percent reduction and adds flow restrictions and a per capita allotment by customer type. The prohibited or limited uses of water in the previous stages are continued or made more restrictive.

- 4.1. No Watering or Irrigating. Watering or irrigating of lawn, landscape or other vegetated area with potable water is prohibited. This restriction does not apply to recycled water.
 - a. Maintenance of vegetation, including trees and shrubs, that are watered using a hand-held bucket or similar container, hand-held hose equipped with a positive self-closing water shut-off nozzle or device;
 - b. Maintenance of existing landscape necessary for fire protection;
 - c. Maintenance of existing landscape for soil erosion control;
 - d. Maintenance of plant materials identified to be rare or essential to the well-being of protected species;
 - e. Maintenance of landscape within active public parks and playing fields, day care centers, golf course greens, and school grounds, provided that such irrigation does not exceed two (2) days per week for no more than fifteen (15) minutes watering per designated water day per station and is prohibited between the hours of 9:00 a.m. and 5:00 p.m. Pacific Standard/Daylight Savings Time.
 - f. Actively irrigated environmental mitigation projects.
- 4.2. Obligation to Fix Leaks, Breaks or Malfunctions. All leaks, breaks, or other malfunctions in the water user's plumbing or distribution system must be repaired within twenty four (24) hours of notification by the city unless other arrangements are made with the city.
- 4.3. Limits on New Potable Water Service: Upon declaration of a Level 4 Water Shortage Emergency condition, the agency may limit the issuance of new potable water

services, temporary meters and/or statements of immediate ability to serve or provide potable water service (such as, can and will-serve letters, certificates, or letters of availability), except under the following circumstances:

- a. A valid, unexpired building permit has been issued for the project; or
- b. The project is necessary to protect the public health, safety, and welfare; or
- c. The applicant provides substantial evidence of an enforceable commitment that water demands for the project will be offset prior to the provision of a new water meter(s) to the satisfaction of the agency providing service.
- d. This provision does not preclude the resetting or turn-on of meters to provide continuation of water service or the restoration of service that has been interrupted for a period of one year or less.
- 4.4. Limits on Building Permits. Upon declaration of a Stage 4 Water Supply Shortage Emergency condition, the City Administrator is authorized to implement a program in his or her discretion to limit or withhold the issuance of building permits which require new or expanded water service, except to protect the public health, safety and welfare, or in cases which meet the city's adopted conservation offset requirements.
- 4.5. No New Annexations. Upon the declaration of Stage 4, the agencies may suspend consideration of annexations to its service area. This subsection does not apply to boundary corrections and annexations that will not result in any immediate increased use of water.
- 4.6. Each of the HUA agencies reserves the right to restrict flow in water lines.

HARDSHIP WAIVER (APPLICABLE AT ANY STAGE)

A person or property can apply for a waiver to the requirements in the WSCP. The written request must be submitted to one of the HUA agencies with supporting documentation (photographs, maps, drawings, and any other information as appropriate). The waiver may be granted or conditionally granted only upon a written finding of the existence of facts demonstrating an undue hardship to a person using water or to property upon which water is used. The Agency that receives the waiver must act upon any completed application no later than ten days after submittal and may approve, conditionally approve, or deny the waiver. The applicant requesting the waiver must be promptly notified in writing of any action taken.

ENFORCEMENT (APPLICABLE AT ANY STAGE)

- •
- First Violation written notice with an opportunity to correct violation.
- Second Violation \$100 penalty for a violation within 12 months of First Violation.
- Third Violation \$250 penalty for a violation within 12 months of Second Violation.

Draft Water Shortage Contingency Plan / Hollister Urban Area • Fourth Violation - \$500 penalty and installation of a flow restrictor at the water meter at the customer's expense for each and every violation within 12 months of a Third Violation.

Subsequent Violations: Any willful violation occurring subsequent to the issuance of the second written warning will constitute a misdemeanor and may be referred to the City/County District Attorney's office for prosecution pursuant. Misdemeanor convictions could include imprisonment and/or fines. The length of time for imprisonment and the magnitude of the fine vary between Hollister and Sunnyslope. If water service is disconnected, it will be restored only upon payment of a reconnection charge. These penalties apply at any time but are likely to be more closely adhered to during drought periods.

Willful Violations

In addition to fines, the City, Sunnyslope or the District, after written notice, may install a flow restrictor device or discontinue service to consumers who willfully violate provisions of this WSCP.

APPENDIX H – WATER SHORTAGE EMERGENCY RESPONSE

Included on attached CD

APPENDIX I – SBCWD ORDINANCE NO. 2015-04

RESOLUTION NO. 2015-04

A RESOLUTION OF THE BOARD OF DIRECTORS OF THE SAN BENITO COUNTY WATER DISTRICT DECLARING A WATER SHORTAGE EMERGENCY AND IMPLEMENTING THE DISTRICT'S WATER SHORTAGE CONTINGENCY PLANS

The San Benito County Water District Board of Directors does hereby resolve as follows:

PURSUANT to California Water Code Section 350 et seq., the Board of Directors has conducted duly noticed public hearings to establish the criteria under which a water shortage emergency may be declared.

WHEREAS,

The District is a water purveyor to the City of Hollister and the Sunnyslope County Water District for municipal purposes and to agricultural customers in San Benito County for irrigation purposes; and

WHEREAS,

Much of California experienced record dry conditions in January 2014 through January 2015, registering historic lows on the Northern Sierra, Upper Sacramento River and San Joaquin precipitation indices; and

WHEREAS,

The Governor of the State of California, in accordance with the authority vested in him by the state Constitution and statutes, including the California Emergency Services Act, and in particular, section 8625 of the California Government Code proclaimed a State of Emergency to exist in the State of California due to current drought conditions; and

WHEREAS,

The District receives water from the Central Valley Project (CVP) as a federal contractor and it has been projected by the Bureau of Reclamation that south of the Delta contractors will receive a zero allocation for agricultural water users and Municipal and Industrial (M&I) customers will only receive 25% of historical allocations this year;

WHEREAS,

The demand for water service is not expected to lessen;

WHEREAS,

As stated in the Hollister Urban Area Water Management Plan 2010, when the combined total amount of water supply available to the District from all sources falls at or below the Stage II triggering levels, the District will declare a water

shortage emergency. The water supply would not be adequate to meet the ordinary demands and requirements of water consumers without depleting the District's water supply to the extent that there may be insufficient water for human consumption, sanitation, fire protection, and environmental requirements. These conditions are likely to exist until precipitation and inflow dramatically increases.

NOW, THEREFORE, BE IT RESOLVED AND ORDERED by the Board of Directors of the San Benito County Water District that a water shortage emergency condition exists that threatens the adequacy of the water supply, until the water supply is deemed adequate. The Board of Directors hereby implements the following interim Water Shortage Contingency Plan.

1. Interim Overuse Policies Applicable to Agricultural and M&I San Felipe Customers (Contract and Small Parcel): Overuse of water will result in a reduction of water available to other users who are entitled to their allocation and will require that the District locate and purchase water on the open market to compensate for the overused water. If an Agricultural or M&I customer overuses their applicable water allocation, the District shall discontinue water service by closing the customer's valve. The customer will be billed their applicable water rate and power rate for usage in addition to a minimum regulatory conservation charge up to \$2,000/Acre-Foot). This charge is not imposed upon a parcel as an incident of property ownership but is a regulatory charge on water users who choose to overuse water allocations. The charge is intended to recover the District's costs for locating and purchasing water in the open market to back-fill the District's supplies so that other District customers' allocations will not be impacted.

2. <u>Changing Account Service Type</u>: Customers will not be allowed to change account service type. However, the District has the discretion to authorize changing of account service type when such is deemed justified under the circumstances.

3. <u>Transfer of Water from Agricultural Contract Customers to Agricultural</u> <u>Small Parcel Customers</u>: Agricultural Contract customers will be allowed to transfer 2014-2015 rescheduled water and 2015-2016 water to small parcel customers. Transfers will only be allowed to agricultural small parcel customers with permanent crops (e.g. trees and vines) who meet either of the following criteria: 1) parcels are designated "high boron", 2) customer has no access to well water.

4. <u>Voluntary Conservation</u>: While the conditions at present warrant a Stage II action, the District is initially implementing a Stage I voluntary conservation action with a Demand Reduction Goal of 20 percent. As the District continues to

monitor the water supply and conditions, the Board may choose to modify the action level.

5. <u>Miscellaneous</u>: Any and all provisions of the Water User's Handbook that are in conflict with the provisions of this Resolution are hereby suspended during the term of this interim Resolution. This Resolution shall be reviewed periodically but not later than the first meeting in March, 2016, to determine whether a water shortage condition and emergency exists and whether the policies set forth herein should continue in effect. In the event a court of law determines that any provision of this Resolution is invalid, such determination shall not invalidate the remaining provisions of this Resolution.

BE IT FURTHER RESOLVED that the Board of Directors shall periodically conduct proceedings to determine additional restrictions and regulations which may be necessary to safeguard the adequacy of the water supply for domestic, sanitation, fire protection, and environmental requirements.

BE IT FURTHER RESOLVED that the President of the Board is authorized to sign this Resolution on behalf of this Board and District.

PASSED AND ADOPTED by the Board of Directors of the San Benito County Water District this 1st day of April, 2015, by the following vote:


- AYES: DIRECTORS: Tonascia, Flores, Tobias, Bettencourt & Huenemann
- NOES: DIRECTORS: None
- ABSENT: DIRECTORS: None
- ABSTAIN: DIRECTORS: None

<u>/s/Joseph A. Tonascia</u> Joseph A. Tonascia President

ATTEST: <u>/s/Sara Singleton</u> Sara Singleton Assistant Manager

APPENDIX J – WATER CONSERVATION PLAN

Included on attached CD



APPENDIX K – RETAILER RATES

Sunnyslope County Water District Summary of Rates & Fees

Sunnyslope County Water District is committed to providing the best quality service for the least possible cost. The District's rate structure is designed to be sufficient enough to cover the cost of operations, maintenance, administration, and capital improvement projects for the water and wastewater systems.

Water Rates, Effective December 21, 2015:

The District assesses a monthly service charge based on water meter size, plus a monthly consumption rate based on the amount of water consumed. The monthly consumption rates for single-family residential customers are an inclining block with three tiers, while non-single-family customers are charged one rate for all water consumption. The current water rates were approved by the Board of Directors on August 6, 2013 by Ordinance No, 73 and took effect on December 21, 2015.

<u>Customer Class of Service</u>	Monthly 5/8"–3/4"–1" Meter Service <u>Charge</u> *	Monthly Single-Family Consumption Charge <u>(per 100 cu ft)</u>	Monthly Non-Single Family Consumption Charge <u>(per 100 cu ft)</u>
Inside District and SBCWD Zone 3	\$ 25.41		
Tier 1: First 1000 cu ft		\$ 2.47	
Tier 2: 1100 – 2000 cu ft		\$ 3.67	
Tier 3: Over 2100 cu ft		\$ 5.45	
All water consumption			\$ 3.29
Inside District and Outside			
SBCWD Zone 3	\$ 25.41		
Tier 1: First 1000 cu ft		\$ 2.53	
Tier 2: 1100 – 2000 cu ft		\$ 3.73	
Tier 3: Over 2100 cu ft		\$ 5.51	
All water consumption			\$ 3.35

* For the monthly service charge rates on other meter sizes and fire service meters, call the District office at (831) 637-4670.

In 2013, the average single-family customer in the District used 1,584 cubic ft. (cu. ft.) of water per month. March was the lowest month with an average of 852 cu. ft. and July was the highest month with an average of 2,441 cu. ft.

Examples of Monthly Water Charges for Various Quantities of Water Used, based on Inside District Rates for a single-family residence with a 5/8", 3/4", or 1" meter as shown above:

Cu. Ft. Used	Amount Billed
1200	\$ 57.45
1700	\$ 75.80
2000	\$ 86.81

Cu. Ft. Used	Amount Billed
2500	\$ 114.06
3000	\$ 141.31
3500	\$ 168.56

Sunnyslope County Water District Summary of Rates & Fees

Cu. Ft. Used	Amount Billed
4000	\$ 195.81
4500	\$ 223.06
5000	\$ 250.31
5500	\$ 277.56
6000	\$ 304.81

Cu. Ft. Used	Amount Billed
6500	\$ 332.06
7000	\$ 359.31
8000	\$ 413.81
10000	\$ 522.81
12000	\$ 631.81

Sewer Rates, Effective December 21, 2014:

The District currently charges residential sewer customers a monthly service charge plus a monthly volume charge based on the average amount of water consumed** for household purposes. Non-residential sewer customers are assessed a volume charge based on metered water usage. The current sewer rates were approved by the Board of Directors on August 6, 2013 by Ordinance No. 74 and took effect on December 21, 2014. The sewer rates were amended to put a cap on average winter water use in drought years by Ordinance No. 71, and took effect May 3, 2012.

Customer Classification	Monthly Sewer Rates
Single-Family Residential Dwelling (SFR)	\$ 95.93 plus \$ 5.64 per HCF **
Multiple-Family Residential Dwelling (MFR)	\$ 72.98 per unit, plus \$ 5.64 per HCF **
Cottages, Motels, Trailer Parks, Laundries, etc.	\$ 9.20 per HCF of metered water use
Commercial and Industrial	\$ 12.14 per HCF of metered water use

HCF – Hundreds of Cubic Feet (based on metered water usage)

** The consumption charge of \$5.64 per HCF for single- and multi-family dwellings is charged based on the average winter water usage for February and March, and is updated each April. In drought years, as determined by the Board of Directors, customers whose average winter water usage increased by 4 or more HCF for February and March over the prior year, will have their increase capped at the prior year average plus 4 HCF.

Capacity Charges, Effective July 1, 2015

The water and sewer capacity charges (connection fees) were approved by the Board of Directors on August 6, 2013, by Ordinance No. 75. The current charges became effective July 1, 2015. The capacity charges can be adjusted by the Board of Directors annually by reference to the Engineering News Record (ENR) index.

Water Capacity Charges ***

Meter Size	Water Meter <u>Capacity Charge</u>	Meter <u>Installation</u>	<u>Total</u>
5/8"-3/4"-1"	\$ 10,200.00	\$ 405.00	\$ 10,605.00
1 1/2"	\$ 20,425.00	\$ 685.00	\$ 21,110.00
2"	\$ 32,675.00	\$ 880.00	\$ 33,555.00

*** To get capacity and meter installation charges on other meter sizes for water and/or fire service, please call the District office at (831) 637-4670.

Sewer Capacity Charges

Sunnyslope County Water District Summary of Rates & Fees

	Sewer	Installation	
Customer Classification	Capacity Charge	Fee	<u>Total</u>
Single-Family Residential	\$ 18,400.00	\$ 25.00	\$ 18,425.00
Multi-Family Residential	\$ 13,500.00 per unit	\$ 25.00 ea.	
2-Family Unit	\$ 27,600.00	\$ 50.00	\$ 27,650.00
3-Family Unit	\$ 41,400.00	\$ 75.00	\$ 41,475.00
Cottages, Motels, Trailer Parks, Laundries, etc	\$ TBD	\$ TBD	\$ TBD
Commercial and Industrial	\$ TBD	\$ TBD	\$ TBD

TBD –Sewer capacity charges are to be determined by the District Engineer.

Miscellaneous Rates and Fees, Effective January 19, 2007 and July 1, 2008:

The miscellaneous rates and fees were approved by the Board of Directors in February, 2015, by Resolution No. 536, and took effect on February 18, 2015.

Deposits Requir	ed (Refundable after 3	B years of good payment history):	
Total Deposit	Water Deposit	Sewer Customer of:	Sewer Deposit
\$ 400.00	\$ 125.00	Sunnyslope	\$ 275.00
\$ 300.00	\$ 125.00	City of Hollister	\$ 175.00
\$ 800.00	Fire Hydrant Dep	osit	
Delinquent Acco	ount Penalty:		
Late Fee of 10	.0% (basic one-time pe	nalty), PLUS 0.5% continuing penalty on un	paid balance
Miscellaneous F	ees:		
\$ 175.00 C	all-Out Fee — Charg after normal working	ed when District staff is called out to turn w hours.	ater on or off
\$ 50.00 R		Charged when water service is shut-off for no rewater service is re-started.	on-payment
\$ 30.00 R	eturned Check (or AC bank as uncollected for	CH) Fee — Charged when a payment is ret or any reason.	urned by the
\$ 10.00 A	Administrative Collection Fee — Charged when a shut-off notice or door hanger delivery is processed on a past due account.		
\$ 50.00 P	roperty Lien Filing Fe due on a delinquent ac	ee — Charged when the District files a lien count.	for a balance



MENU≡ Home Residents **Business** Visitors Government Services I'd Like To... Contact Employment Q

Utility Billing

Administrative

Finance

Human

Resources Job

Financi <u>al</u>

> **Report** S

Services

Water Service

To start new water services in the City limits, we require a \$75.00 water deposit and a \$75.00 sewer deposit. These deposits will be refunded when the account is closed or at the end of three years.


Current Water Rate Information, as of January 1, 2016.

<u>S</u>	Meter Service Charge	Consumption
 <u>Utility</u> <u>Billing</u> 		Charge
Inform		Monthly Service
ation	Meter Size / Charge No HFC Allocation	Single Family
Dog Licens		Residential
<u>e</u>	5/8" - \$10.41 (Most Single Family Residential	\$2.64 - 0 to 9 hcf
<u>nan</u> sources	Dwellings have 5/8" meters)	\$4.34 - 10 to 15 hcf
■ <u>Job</u>	3/4" - \$10.41	\$4.97 - over 15 hcf
<u>Descri</u>	1" - \$22.05	
ptions	1-1/2" - \$41.26	All Other Classes
Salary Sched	2" - \$61.83	\$3.43 for every hcf
ule	3" - \$121.80	

1 of 4

4" - \$1	81.79
6" - \$3	861.76
8" - \$5	58.86

Download Water/Sewer Utilities Form below to Start or Stop Water or Sewer service. Please complete the form and return it to Finance Utility Payment Center for processing at 339 Fifth Street.



Click on the link above to pay your Utility Bill Online using Visa or MasterCard. (A \$1.25 Processing Fee is charged by (ECH) Electronic Clearing House). Dog Licenses CANNOT be paid by using Utility Bill Pay Online. Currently Dog License Payments are NOT available online.

Sewer Service

Sewer services and street sweeping for customers in the City of Hollister receiving water service from Sunnyslope water department. No deposit is required for this service. (Sewer fee will change every July).

This service includes:

Sewer Fiscal Year 2010/2011 New Sewer

Rate Schedule

Translate »

2 of 4

Customer	/ Previous Rate	/ Current Rate	1	
Quantity Charge				
Class	Monthly	Monthly		
Per HCF				
Single Family	\$78.48			
\$86.32	\$			
Residential				
Multi-Family	\$68.41	\$75.25		
\$				
Residential				
Mobile Homes	\$48.00	\$52.80		
\$				
Commercial/	\$36.03	\$40.62		
\$	φ00.00	ψ 1 0.02		
Industrial				
(Low Strength)				
Commercial/	\$68.60	\$75.45		
\$9.05	<i>QUOIDU</i>	<i>Q</i> , or ro		
Industrial				
(Mod Strength)				
Industrial	\$266.85	\$293.54		
\$16.80	·	•		
(High Strength)				
Elementary &	\$2.86			
\$3.14	\$			
Middle Schools				
(per Pupil)				
High Schools	\$2.86	\$3.14		
\$				
(per Pupil)				

Translate »

Street	\$2.40
Sweeping	

Follow Us on



Copyright 2014 - City of Hollister. All Rights Reserved.

Translate »

APPENDIX L – PUBLIC OUTREACH

Pilot Landscape Irrigation Hardware Rebate Program Eligible Products and Program Requirements



From the Water Resources Association of San Benito County (WRASBC)

Over 50 percent of residential water is used for landscape purposes. Of this amount, 50 percent is wasted due to overwatering or inefficient equipment.

The WRASBC is offering a 50% rebate (up to \$100) for the purchase and installation of the following <u>specific</u> landscape irrigation hardware devices* that assist in conserving water. Labor costs to install these devices and taxes are not eligible to be rebated, only the following materials:

Hose timers: (Only Models Listed) Ideal for use with drip irrigation systems, soaker hoses and hose end sprinklers, a hose timer will shut off your sprinklers after a preset duration to conserve water and prevent overwatering. Just turn your water spigot on and set the timer.

Qualifying models for hose timers:

Claber - Rain Jet	Claber - Rain Jet	Orbit – Green Thumb	Aquastar
'Video 2'	'Logica'	Digital or Rotary Knob	Available at:
Digital Available at: Ewing Irrigation in Gilroy	Rotary Knob Available at: Ewing Irrigation in Gilroy	Available at Ace or True Value Hardware in Hollister	Brigantino Irrigation - Hollister

Rain sensors (Only Models Listed): A rain sensor is an irrigation shutoff device that prevents an automatic irrigation or sprinkler system from turning on during and after a rain storm. These devices override a scheduled irrigation when a water collection cup or sensor on the shutoff device detects water. (Available in wireless or hard wired versions).

Qualifying models for rain sensors:

Clik Hunter wireless Rain	Mini-Clik Hunter wired Rain	Toro – Wired Rain Sensor	Toro – Wireless Rain Sensor
Sensor	Sensor	Available at True Value	Available at True Value
Available at:	Available at:	Hardware – Hollister	Hardware – Hollister
Ewing Irrigation – Gilroy	Ewing Irrigation – Gilroy	Ewing Irrigation - Gilroy	Ewing Irrigation - Gilroy
Brigantino Irrigation -	Brigantino Irrigation - Hollister		
Hollister			

Rotator nozzles (Hunter Industries Only): This is the perfect sprinkler for situations dealing with odd shaped areas or heavy soil conditions, like our local clay soils, that cause water run-off with normal pop-up sprinklers. MP Rotator sprinklers provide even watering to the lawn or garden area more slowly to allow the water to be absorbed by the soil.

Qualifying models for rotator nozzles and sprinkler body with pressure regulator:

MP1000	MP Hunter MPR40 Sprinkler Body
MP2000	The MPR40 Sprinkler Body
MP3000	Built-in regulator set at 40 PSI
Available at Ewing Irrigation – Gilroy OR at Brigantino	Factory-installed drain check valve
Irrigation - Hollister	

*Qualifying Landscape Irrigation Hardware is subject to change without notice

The WRASBC has negotiated <u>special pricing</u> for their customers with <u>Ewing Irrigation</u> in Gilroy. They are a distributor for Hunter Industries. Their address and phone number is: 7170 Forest Street Gilroy, CA 95020 (408) 848-5515. <u>Directions</u>: From Highway 101: go to the 10th Street Exit. Make a left at the light at the end of the off-ramp. Then go to Chestnut Street and turn right. Take the 1st left onto East 9th Street. Take the 1st right onto Forest Street proceed to 7170 Forest Street. Reference Job Number 99182 to receive your discount.

Steps to Receive Your Rebate

Step 1: Make an appointment for a "Pre-Qualification Inspection" site visit with the Water Resources Association of San Benito County (WRASBC), **CALL 637-4378.** The pre-inspection will determine what landscape irrigation hardware can be used for your landscape area. You will be given a rebate application form stating what items you are qualified to purchase from the following landscape irrigation hardware: **MP Rotators, rain sensor or hose timer.**

Step 2: Purchase and install pre-qualified landscape irrigation hardware from a list of specific models that qualify under this program. A list of these products will be provided to you by the WRASBC representative during the Pre-Qualification Inspection. <u>ALL hardware must be installed within **60 days** of the date of the Pre-Qualification Inspection.</u>

Step 3: After installing landscape irrigation hardware call for a final "**Post-Installation Inspection**" appointment within **60 days** of the date of the **Pre-Qualification Inspection**, **CALL 637-4378**. A Water Resources Association representative will do a site visit to confirm approved landscape hardware is installed and develop an irrigation schedule for you to follow. Sales receipts are required for all rebates. If you have a contractor install landscape irrigation hardware ask for a separate invoice for materials stating: "Labor billed separately."

Step 4: Fill out the Pilot Landscape Hardware Rebate Application Form that was given to you at the time of the Pre-Qualification Inspection. Include the following: receipt for landscape irrigation hardware and a copy of your water bill. A Water Resources Association representative will collect these documents at the time of the **Post-Installation Inspection**. You will receive a 50% rebate on what you purchased up to \$100 total (materials only – no labor or tax).

Eligibility Requirements

- 1. The Applicant applying for the rebate(s) must be a water customer of the City of Hollister, the City of San Juan Bautista or the Sunnyslope County Water District.
- 2. Only Pre-Qualified residents shall qualify for a rebate.
- **3.** The purchase and installation of the landscape irrigation hardware must be installed within 60 days of the date of the Pre-Qualification Inspection. Only specific landscape irrigation hardware qualifies. A list of these products / models will be provided by the WRASBC representative at the time of the Pre-Qualification Inspection.
- 4. A rebate form will be given to you at the time of the "**Pre-Qualification Inspection**". A representative from the WRASBC will pick this rebate form up from you, along with a copy of the sales receipt for the purchase of the irrigation hardware and water bill for your property during the "**Post-Installation Inspection**".
- 5. Applicant must attach a legible copy of a valid, dated sales receipt to the rebate application to qualify along with a copy of your water bill.
- 6. Rebates shall be on a one-time basis per address and not to exceed \$100 (materials only).
- 7. A Water Conservation staff member will conduct a Post-Installation Inspection of the property to verify installation within 60 days of the date of the Pre-Qualification Inspection. Your rebate application, sales receipt and water bill will be collected by a Water Resources Association representative at this time.
- 8. Note: Rebate amounts and specified products are subject to change without prior notice and based upon availability of funds and manufacturers products. This rebate program will expire when funds are depleted.
- **9.** The applicant agrees to hold the Water Resources Association of San Benito County and its agents harmless for any liability for damages which arise from participating in this program.
- **10.** Allow 6-8 weeks for processing AFTER Post Installation Inspection to receive your rebate.

Volume 11 Issue 2

Spring/Summer 2015

Don't flush this!

When you use your toilet, shower, washing machine or dishwasher, wastewater leaves your home through pipes that connect to the city sewer system.

Anyone who uses the city sewer system should be responsible for what they flush or pour down drains.

Basically, the only thing you should ever flush down a toilet is human waste (urine and feces) and toilet paper. Here is a list of some things to keep out of the toilet.

- disposable diapers
- tampons and tampon applicators
- sanitary napkins
- cotton balls and swabs
- mini or maxi pads
- condoms
- cleaning wipes of any kind. Even those labeled "flushable".
- facial tissue
- bandages and bandage wrappings
- automotive fluids, paint, solvents, sealants and thinners poisons and hazardous waste

Unused Medications

 Do not flush unused medications down the toilet. You can safely dispose of medications in the garbage, or take medications to an approved prescription drug take-back site
 Fats, Oils and Grease

Fats, Oils and Grease (FOG)

 Grease in sewer pipes causes sewer maintenance problems for property owners and the city. Never pour grease in your sink drain and try to use your garbage disposal less.



Water Conservation Update

DROUGHT UPDATE NEW EMERGENCY WATER CONSERVATION REGULATIONS

California is entering a fourth year of severe drought. The State Water Resources Control Board recently adopted expanded emergency regulations to safeguard the state's remaining water supplies. Locally, our main water supply is derived from groundwater. It is not being naturally replenished by rainfall during the drought. In addition, our imported water has been dramatically cutback due to the lack of rainfall and snowpack.

We need to stretch our water supply as much as possible! All customers are urgently asked to make every effort to conserve water and abide by the following regulations and restrictions. Otherwise, our community may face even more drastic reductions in water use. All customers are mandated to reduce water consumption by 25% **compared to their water use in 2013**. The WRASBC can assist you! (see back page)

OUTDOOR WATER RESTRICTIONS

- Landscape watering shall be limited and restricted to no more than two (2) days per week. Odd numbered addresses are hereby restricted to watering on Tuesdays and Saturdays. Even numbered addresses are herby restricted to watering on Wednesdays and Sundays.
- No watering of landscaping between the hours of 9am and 5pm by means other than drip irrigation or hand watering with a quick acting positive shut off nozzle.
- No washing down sidewalks, driveways, or other hardscape surfaces.
- No watering landscape in a manner that causes runoff to adjacent property, nonirrigated areas, private and public walkways, roadways, or parking lots.
- No washing of cars without the use of a quick acting , positive shutoff nozzle.
- No operation of decorative fountains or other water features unless the water is recirculated.

GENERAL

 Leaks, breaks and malfunctions of irrigation systems and plumbing equipment causing waste of water shall be repaired and corrected within a reasonable amount of time as determined by the District Manager of Sunnyslope County Water District or the City Manager of the City of Hollister.

PROHIBITONS AFFECTING COMMERCIAL BUSINESSES

- Restaurants and other food service establishments can only serve water on request;
- Operators of hotels and motels must provide guests with the option of choosing not to have towels and linens laundered daily and prominently display notice of this option.
- Penalties for violating the outdoor water restrictions shall be:
- First Violation written notice with an opportunity to correct violation.
- Second Violation \$100 penalty for a violation within 12 months of First Violation.
- Third Violation \$250 penalty for a violation within 12 months of Second Violation.
- Fourth Violation \$500 penalty and installation of a flow restrictor at the water meter at the customer's expense for each and every violation within 12 months of a Third Violation.

The WRASBC has free signage for restaurants and hotels

Water Resources Association San Benito County 30 Mansfield Road Hollister, CA 95023 (831) 637-4378 www.wrasbc.org

Representing the City of Hollister, the City of San Juan Bautista, Sunnyslope County Water District, and San Benito County Water District.

WRASBC FREE Services & Rebates:



Turf Removal Rebate

LOCAL FUNDING DEPLETED FOR TURF REMOVAL REBATE AS OF 8/1/15 STATE FUNDING IS AVALABLE GO TO: SAVEOURWATERREBATES.COM

Landscape Hardware Rebates

The Water Resources Association has rebates on hose timers, rain sensors and MP Rotator irrigation nozzles and sprinkler bodies with pressure regulators. 50% rebate (up to \$100) on qualifying products.

Free Water Wise Landscape Plans

The Water Resources Association has FREE water wise landscape plans. Three different garden design

concepts (\$500 value). Installing a water wise garden will save water and money, plus they require less maintenance time.

Home Water Survey (Our most popular service!)

The Survey includes: irrigation check, suggested watering schedule, leak check, showerheads and faucet aerators, high-quality hose nozzle, water softener assistance

Water Softener Assistance and Rebate Program

Have a WRASBC technician inspect and check your water softener to make sure it is set properly for hardness levels. Rebates are available for those customers transitioning to an offsite regeneration service or demolishing their self-regulating water softener that uses salt or potassium. Rebates: \$250-\$300



High Efficiency Clothes Washer Rebates

These washers use half as much water as traditional top loading clothes washers. These machines also use less detergent and help us protect our groundwater supplies. Energy Star ® rated clothes washers qualify. Rebate: \$100

Toilet Program (Free Toilets or Rebates)

Customers that have toilets that are 1992 or older qualify. These older toilets use from 3.5—7 gallons of water for each flush. New toilets flush from 1.28—1.6 gallons per flush. The Water Resources Association has free toilets or a \$75 rebate is available when you purchase your own.

Green Business Certification:

The WRASBC is working together with the San Benito County Chamber of Commerce, San Benito County Integrated Waste Management and PG&E to assist, recognize and promote businesses and government agencies that volunteer to operate in a more environmentally responsible way.



Additional Programs:

A Water Conservation Specialist is available to give presentations at schools, Service Clubs & local community organizations. Learn about the Water Cycle, our local water supply and water issues locally / state-wide. Fieldtrips to the reclamation plant and water treatment plant can also be arranged.

* Special Rules & Conditions apply, call for details. Rebates are subject to available funds



TOILET REBATE PROGRAM

Program Overview: WRASBC offers a rebate program to eliminate pre-1992, 3.5 – 7 gallons per flush toilets with new Low Flow 1.28 gallons per flush toilets. This rebate is for replacing toilets that were manufactured prior to 1992 which are date stamped into the porcelain either in the inside part of the lid on the tank, or on the sidewall inside the tank. Your toilet is NOT eligible if it says "1.6 gpf" behind the toilet seat where the manufacturer's logo is usually found

Eligibility: Eligible residents of San Benito County are those who have water service through the City of Hollister, City of San Juan Bautista, Sunnyslope Water District or reside in CSA 31 (Stonegate). Customers served by private wells are not eligible.

<u>Rebate:</u> There are two types of rebates. (A) The WRASBC offers a free Low Flow Toilet in exchange for your old pre-1992 toilet. Participants have 45 days to return old toilet after receiving free one; or (B) you can apply for a \$75 rebate if you choose to purchase your own toilet (an additional \$10 will be paid if you return your old toilet to the WRASBC for recycling). These rebates are limited to the number of bathrooms in your household with pre-1992 toilets and cannot be used for a new house or bathroom addition. This rebate applies only to purchases within the last six months. All rebate programs are subject to available funds.

Instructions:

A. <u>How to Apply for a Free Toilet:</u>

- 1. Call to schedule an appointment to pick up a free toilet at the WRASBC
- 2. Complete Program Application (this form can be filled out at time of toilet pick up).
- 3. Your water account number and a picture ID need to be presented at time of pick up.
- Return your old toilet for recycling and toilet age verification to WRASBC on Mondays through Fridays, 8:00 5:00 (closed noon to 1:00). If you cannot return the toilet, call the WRASBC and make arrangements to have the toilet picked up for recycling. If your old toilet does not meet the age verification pre-1992 requirement, you will be charged \$125 for the toilet on your next water provider utility bill. Old toilet(s) must be returned within 45 days after the new toilet is picked up.

B. How to Apply for a \$75 Toilet Rebate:

- 1. Complete Rebate Program Application (including a W-9 form). Incomplete applications will not be processed
- 2. Attach copy of your current water bill
- 3. Attach the original receipt of your toilet purchase(s). Original receipts will not be returned
- 4. Return your old toilet to WRASBC on Mondays through Fridays, 8:00 5:00 (closed noon to 1:00). An additional \$10 will be paid if you return your old toilet to the WRASBC for recycling and toilet age verification. If your old toilet does not meet the age verification pre-1992 requirement, your rebate application will be denied.
- **Inspection(s):** No pre-inspection or post-inspection is required, however, WRASBC will verify that your old toilet is pre-1992 to meet the rebate program requirements. A pre-inspection is required for free toilets/toilet rebates of 3 or more.

Upon completion of all requirements of the rebate program, you will receive your rebate within 30-45 days

Water Resources Association San Benito County (WRASBC) P.O. Box 899, 30 Mansfield Road, Hollister, CA 95024-0899

(831) 637-4378

WASHER REBATE PROGRAM

Program Overview: WRASBC offers a rebate program to replace clothes washers that are not ENERGY STAR® rated with new High Efficiency ENERGY STAR® labeled washers that use 50% less energy and 40% less water than older top loading machines. ENERGY STAR® washers can save 13,000 gallons of water per year per household and send less waste water through our local sewer system(s).

Eligibility: Eligible residents of San Benito County are those who have water service through the City of Hollister, City of San Juan Bautista, Sunnyslope Water District or reside in CSA 31 (Stonegate). Customers served by private wells are not eligible.

<u>Rebate:</u> The WRASBC offers a \$100 rebate when you purchase an ENERGY STAR[®] clothes washer. This rebate is limited to <u>one clothes washer per household</u>. This rebate applies only to purchases within the last six months. **All rebate programs are subject to available funds.**

Instructions on How to Apply:

- 1. Complete Rebate Program Application. Incomplete applications will not be processed
- 2. Attach copy of your current water bill
- 3. Attach the original receipt of your ENERGY STAR[®] clothes washer purchase(s). Original receipts will not be returned
- 4. Call the WRASBC to schedule an on-site post-inspection to verify that your new washer has been installed. At that time a <u>FREE Home Water Checkup</u> will be included to provide free showerheads, toilet and faucet kits at NO CHARGE. Paperwork can be picked up at post inspection

Inspection(s): Post-inspection: An on-site post-inspection will be required to verify washer installation. A FREE Home Water Checkup will be included at the time of inspection with free showerheads, toilet and faucet kits offered at NO CHARGE.

Upon completion of all requirements of the rebate program, you will receive your rebate within 30-45 days

Water Resources Association San Benito County (WRASBC) P.O. Box 899, 30 Mansfield Road, Hollister, CA 95024-0899

(831) 637-4378

WATER SOFTENER REBATE PROGRAM

Program Overview: WRASBC offers two different rebate program options for the elimination or replacement of water softener. Most Water Softeners use roughly 75 gallons of water during regeneration. Waste water from Water Softeners contains high levels of sodium (salt and/or potassium) which makes it much more costly to recycle the water and negatively affects the groundwater aquifers.

Eligibility: Eligible residents of San Benito County are those who have water service through the City of Hollister, City of San Juan Bautista, Sunnyslope Water District or reside in CSA 31 (Stonegate). Customers served by private wells are not eligible.

<u>Rebate:</u> The WRASBC offers two different rebates for those who currently have a water softener:

Option 1 is a \$250 rebate to eliminate any type of water softener and switch to an offsite regeneration service. Customers must submit proof by providing a copy of the 1-year minimum contract; or

Option 2 is a \$300 rebate if you demolish your old, self-regulating Water Softener that uses salt/potassium, with a salt-free Water Conditioner, or remove it entirely and do not replace it. This rebate is limited to one Water Softener per household.

This rebate applies only to purchases within the last six months. All rebate programs are subject to available funds.

How to Apply for Option 1 – Contracting for Outside Regeneration Service (\$250 rebate):

- 1. Call to schedule a pre-inspection <u>BEFORE</u> you remove your old water softener (your old water softener cannot be removed before pre-inspection). The WRASBC technician will bring a rebate form and W-9 form for you to fill out.
- 2. After pre-inspection, remove your old water softener and make arrangements with water softener regeneration service to install new unit.
- 3 Call the WRASBC to schedule a post inspection. The WRASBC technician will pick up your rebate form, copy of your minimum1-year service agreement and completed W-9 form.

How to Apply for Option 2 - Demolition of Water Softener with No Replacement (\$300 rebate):

- 1. Call to schedule a pre-inspection <u>BEFORE</u> you remove your old water softener (your old water softener cannot be removed before pre-inspection). The WRASBC technician will bring a rebate form and W-9 form for you to fill out.
- 2. After pre-inspection, remove your old Water Softener as instructed by WRASBC representative within 120 days
- 3. Call the WRASBC to (1) schedule an on-site post-inspection to verify that your old Water Softener has been demolished (valves protruding from the wall have been capped off or a pipe must be soldered from one valve to the other creating a loop); <u>OR</u> (2) verify that you have installed a new salt-free alternative Water Conditioner. The WRASBC technician will pick up your completed rebate application & W-9 form at this time

Inspection(s): Pre-inspection: An on-site pre-inspection is required for both options. Prior to removing your old Water Softener, you must have a pre-inspection by a WRASBC representative who will explain the procedures for both options in detail as described above.

Upon completion of all requirements of the rebate program, you will receive your rebate within 30-45 days

Water Resources Association San Benito County (WRASBC) P.O. Box 899, 30 Mansfield Road, Hollister, CA 95024-0899

(831) 637-4378

LANDSCAPE IRRIGATION HARDWARE REBATE PROGRAM

Program Overview: WRASBC offers a rebate program to purchase new/replacement landscape irrigation hardware/equipment to reduce the amount of water waste. The program includes MP Rotators by Hunter Industries, and Hose Timers and/or Rain Sensors which are on the list provided by WRASBC. The goal is to water early in the morning to minimize evaporation, never water faster than the ground can absorb the water, and adjust sprinklers to avoid watering the sidewalks and driveways.

Eligibility: Eligible residents of San Benito County are those who have water service through the City of Hollister, City of San Juan Bautista, Sunnyslope Water District or reside in CSA 31 (Stonegate). Customers served by private wells are not eligible.

Rebate: The WRASBC offers a maximum of \$100 rebate for materials purchased per household. This program provides a 50% rebate on your purchase price of hardware (excluding labor), up to a maximum of \$100 rebate. This rebate applies only to purchases within the last six months. **All rebate programs are subject to available funds.**

How to Apply:

- 1. Complete Rebate Program Application. Incomplete applications will not be processed.
- 2. Attach copy of your current water bill

.

- 3. Call the WRASBC to schedule an on-site pre-inspection
- 4. After pre-inspection, purchase and install the pre-qualified hardware from the list provided by the WRASBC within 60 days of the pre-inspection
- 5. Call the WRASBC to schedule an on-site post-inspection to verify that hardware has been installed correctly. The WRASBC representative will also develop an irrigation schedule for you to follow

Inspection(s): Pre-inspection: A pre-inspection is required to determine what hardware can be used for your landscape area and what items you are qualified to purchase from the WRASBC-approved list.

Post-inspection: After you have purchased and installed the hardware within 60 days of the preinspection, call WRASBC to schedule an on-site post-inspection to confirm that the hardware is installed.

Upon completion of all requirements of the rebate program, you will receive your rebate within 30-45 days

LOCAL FUNDS DEPLETED – STATE PROGRAM IS BEING OFFERED STATE PROGRAM HAS DIFERENT TERMS Go to: www.saveourwaterrebates.com

(831) 637-4378

TURF REMOVAL REBATE PROGRAM

Program Overview: The WRASBC is offering a program to reduce or limit turf in residential areas. Turf can use up to 80" of water per year. On an average, San Benito County receives 11-13" of rain per year. This program provides an incentive for people to remove turf and plant drought tolerant or native plants that use much less water and are more appropriate for our climate. It will also increase water use efficiency, reduce run off leaving the properties, and foster water-saving practices. In addition to our local program, there is a State program (information available at <u>www.saveourwaterrebates.com</u>.

<u>Eligibility:</u> Eligible homeowners of the property (where the turf removal will take place) in San Benito County are those who have water service through the City of Hollister, City of San Juan Bautista, Sunnyslope Water District or reside in CSA 31 (Stonegate). Customers served by private wells are not eligible.

<u>Rebate:</u> Effective July 1, 2015, the WRASBC offers a rebate of \$1.00 per square foot to replace eligible lawn areas (minimum of 100 sq ft up to a maximum of 1,000 sq ft). The minimum rebate is \$100 and the maximum rebate is \$1,000. **THIS REBATE REQUIRES WRASBC PRE-APPROVAL**. Customers may remove more turf area than is covered by the rebate program, but the per site minimum/maximum amounts still apply. Once installed, the irrigation system must not create runoff, overspray or misting. Turf may not be re-installed while you maintain ownership of the property. <u>If</u> **turf is reinstalled during that time, the entire rebate amount must be refunded**. The WRASBC is solely responsible for determining program eligibility at its discretion and may reject or limit applications at any time for any reason. Landscape that has died or turned brown is considered a qualifying project as long as it is not removed before WRASBC approves it. **All rebate programs are subject to available funds.**

The lawn must be replaced with:

(1) Low-water use, climate-appropriate plants; and/or

(2) Permeable hardscape (pavers or other materials (crushed granite, decorative stone, mulch, etc.) that allows water to pass-through to the soil; and/or

(3) Leak-free, drip irrigation if used in the converted area, must be low volume drip, micro-spray or bubbler and free of malfunctions

Non-Qualifying Turf Projects:

(1) Projects that have been started without obtaining a pre-approval letter from WRASBC

(2) No evidence of a previously maintained turf area.

(3) New construction does not qualify as the Turf Removal Program is aimed at encouraging retrofitting of existing landscapes

(4) Use of non-qualifying materials which include but are not limited to the following: artificial turf, seed, sod, vegetable gardens, vineyards, high water use plants, lawn ornaments, impervious surfaces, cement, dirt, decking, curbing, hot tubs, pools, building extensions, retaining walls, sheds, trellises, playground materials and fences

ALERT: To retain your rebate eligibility, DO NOT INSTALL HIGH-WATER-USE PLANTS in your converted landscape. Only low or moderate water use species are acceptable. High water use plant species are those listed as needing "Regular Water" or "Ample Water" in the *Sunset Western Garden Book* and those classified as High (H) water use on

the WUCOLS (Water Use Classification of Landscape Species) website. See WRASBC Fact Sheet "Low-Water/Drought Resistant Plant List and Resources."

How to Apply:

- 1. Complete Rebate Program Application. Incomplete applications will not be processed.
- 2. Attach copy of your current water bill.
- 3. Call the WRASBC to schedule an on-site pre-inspection or email the Program Manager at <u>snovack@sbcwd.com</u>. During the pre-inspection, your turf area will be measured. You may either have a materials list ready at the time of the pre-inspection or the plan can be submitted by mail or in person after the pre-inspection. The plan needs to show what plants, irrigation system (if needed) and hardscape materials you plan to install in the area where the turf will be removed. The Water Conservation Fact Sheet entitled, "Low-Water/Drought Resistant Plant List and Resources" is available for assist you in preparing your materials list from the WRASBC. Materials list should include major plant materials to be installed (trees, shrubs, groundcover), and hardscape (gravel, stones, rocks, pebbles), etc.
- 4. After the pre-inspection and submission of your materials list, WRASBC will review your list and send you an Approval Letter. After you receive the Approval Letter, remove the lawn area and install your project according to the approved materials list and program guidelines. You are responsible to remove your own turf. Projects must be completed within 120 days of the pre-approval letter. Extensions can be provided on a case by case basis, if requested. However, funds are limited and an extension doesn't reserve or guarantee funds will be available when your project is completed.

5. Call the WRASBC to schedule an on-site post-inspection. The post-inspection must take place within 120 days of receiving the Approval Letter.

Note: The applicant is solely responsible for complying with any and all laws, regulations, policies, conditions, covenants and restriction that may apply and for any and all liabilities arising out of a conversion project. Applicants are encouraged to consult with applicable covenants, conditions and restrictions (CC&Rs) or neighborhood Homeowner's Association (HOA) regulations that may apply to an anticipated conversion project prior to requesting a pre-inspection with the WRASBC. Applicants must also comply with all state and local laws relating to landscape maintenance. The quality, maintenance and appearance of the conversion are the exclusive responsibility of the applicant.

Inspections: Pre-inspection is required: Landscape areas to be converted must be currently maintained and irrigated, HOWEVER BROWN GRASS IS OK. At this time, your turf area will be measured. You may either have a materials list ready at the time of the pre-inspection or the plan can be submitted by mail or in person after the pre-inspection. The list needs to show what plants, irrigation system (if needed) and hardscape materials you plan to install in the area where the turf will be removed. The Water Conservation Fact Sheet entitled, "Low-Water/Drought Resistant Plant List and Resources" is available for assist you in preparing your plan from the WRASBC.

Post-inspection is required: The WRASBC will schedule an on-site post inspection to verify that the lawn area has been removed and your project was installed according to your approved landscape plans and in accordance with program guidelines.

Upon completion of all requirements of the rebate program, you will receive your rebate within 30-45 days